


eSubmit To Appropriate District Office Two Copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised April 3, 2017	
		1. WELL API NO. 30-015-44334		2. Type of Lease ☒ STATE ☐ FEE ☐ FED/INDIAN	
		3. State Oil & Gas Lease No.		5. Lease Name or Unit Agreement Name TURKEY TRACK 43 STATE	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG				6. Well Number: 31H NM OIL CONSERVATION ARTESIA DISTRICT	
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)				JAN 22 2019	
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER		8. Name of Operator OXY USA WTP LP		9. OGRID 192463	
10. Address of Operator P.O. BOX 4294 HOUSTON, TX 77210				11. Pool name or Wildcat TURKEY TRACK; BONE SPRING	
12. Location	Unit Ltr	Section	Township	Range	Lot
Surface:	D	4	19S	29E	
BH:	A	3	19S	29E	
13. Date Spudded 10/05/17	14. Date T.D. Reached 08/23/18	15. Date Rig Released 08/26/18	16. Date Completed (Ready to Produce) 10/23/18		17. Elevations (DF and RKB, RT, GR, etc.) 3410' GR
18. Total Measured Depth of Well 19014'M 8807'V		19. Plug Back Measured Depth 18970'M 8807'V		20. Was Directional Survey Made? YES	21. Type Electric and Other Logs Run Gamma Ray
22. Producing Interval(s), of this completion - Top, Bottom, Name 8731'-18850' BONE SPRING					
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	54.5# J55	414'	17-1/2"	605	
9-5/8"	36# J55	2810'	12-1/4"	1066	
5-1/2"	20# P110	19014'	8-1/2"	3057	
24. LINER RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	
25. TUBING RECORD					
SIZE	DEPTH SET	PACKER SET			
2-7/8"	8397'	8382'			
26. Perforation record (interval, size, and number 6 SPF @ 18821-18653, 18607-18411, 18365-18169, 18251-18055, 17881-17685, 17639-17436, 17397-17201, 17155-16959, 16914-16717, 16671-16475, 16429-16233, 16187-15991, 15917-15749, 15507-15703, 15461-15265, 15219-15023, 14977-14781, 14735-14539, 14493-14297, 14251-14056, 14012-13813, 13767-13571, 13528-13329, 13283-13087, 13041-12845, 12799-12603, 12557-12361, 12315-12119, 12073-11877, 11831-11635, 11589-11397, 11345-11151, 11105-10909, 10863-10667, 10621-10425, 10379-10183, 10137-9941, 10125-9929, 9651-9457, 9411-9215, 9169-8973 and 8927-8731. Total 1008 holes					
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
8731'-18821'		294839 bbls Slick Water + 10500g 15% HCl acid w/ 16187321# sand			
28. PRODUCTION					
Date First Production 10/22/18		Production Method (Flowing, gas lift, pumping - Size and type pump) GAS LIFT		Well Status (Prod. or Shut-in) PROD.	
Date of Test 11/30/18	Hours Tested 24	Choke Size 64/64	Prod'n For Test Period	Oil - Bbl 964	Gas - MCF 990
Water - Bbl. 1468	Gas - Oil Ratio 1027				
Flow Tubing Press. 215 PSI	Casing Pressure 1093 PSI	Calculated 24-Hour Rate	Oil - Bbl. 964	Gas - MCF 990	Water - Bbl. 1468
Oil Gravity - API - (Corr.)					
29. Disposition of Gas (Sold, used for fuel, vented, etc.) TO BE SOLD					30. Test Witnessed By
31. List Attachments FINAL C104, WBD, Directional Survey Certification, GR LOG					
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.					33. Rig Release Date: 08/26/18
34. If an on-site burial was used at the well, report the exact location of the on-site burial:					
Latitude		Longitude		NAD83	
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief					
Signature 		Printed Name LESLIE REEVES		Title REGULATORY ADVISOR	
E-mail Address LESLIE REEVES@OXY.COM		Date 1-21-2019			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Brushy Canyon 3385'	T. Ojo Alamo	T. Penn A"
T. Salado 317'	T. Strawn	T. Kirtland	T. Penn. "B"
T. TNSL 937'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates 1127'	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers 1294'	T. Devonian	T. Cliff House	T. Leadville
T. Queen 1982'	T. Silurian	T. Menefee	T. Madison
T. Grayburg 2313'	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres 2834'	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand 3141'	T. Morrison	
T. Drinkard	T. Bone Springs 3682'	T. Todilto	
T. Abo	T. 1st Bone Spring 6326'	T. Entrada	
T. Wolfcamp	T. 2 nd Bone Spring 6884'	T. Wingate	
T. Penn	T. 3 rd Bone Spring 7935'	T. Chinle	
T. Cisco (Bough C)	T. Strawn	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology

OXY USA WTP LP
Turkey Track 4 3 State #31H
API No. 30-015-44334

