Office	State of New Mo	exico	Form C-103
District I – (575) 393-6161 Energy, Minerals and Natural Resources		Revised July 18, 2013	
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION	DIVISION	30-015-44966
District III – (505) 334-6178	1220 South St. Fra	Ni .	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fean 8	^	STATE FEE
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Sailta Perlyw 8	10 Jan.	6. State Oil & Gas Lease No.
87505	HO CO	, LED	
SUNDRY NOTI	CES AND REPORTS ON WOLLS	Cla	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPO	SALS TO DRILL OR TO DEEPEN OR PL	JG BACK TO A	Fleetwood 36/25 W2NK St Com
DIFFERENT RESERVOIR. USE "APPLIC PROPOSALS.)	CATION FOR PERMIT" (FORM C-101)	SUCH	8. Well Number 2H
·	Gas Well Other NM OIL	. CONSERVATION	
2. Name of Operator	AR	TESIA DISTRICT	9. OGRID Number 14744
Mewbourne Oil Company			7. COMB Number 14744
3. Address of Operator	J	4N 3 1 2019	10. Pool name or Wildcat
PO Box 5270, Hobbs NM 88241		20.0	Purple Sage; Wolfcamp (gas)
4. Well Location		PECEIVED	Turple suge, womening (gus)
Unit Letter _N:	270feet from theSouth	line and _1720_	<del></del>
Section 36	Township 24S	Range 28E	NMPM Lea County
	11. Elevation (Show whether DR	RKB, RT, GR, etc.	)
<u> </u>	2945' GL		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
		1	•
NOTICE OF IN		SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON 🗌	REMEDIAL WOR	K ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRI	ILLING OPNS. □ P AND A □
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMEN	T JOB 🛛
DOWNHOLE COMMINGLE			
CLOSED-LOOP SYSTEM			
OTHER:		OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date			
13. Describe proposed or comp	leted operations. (Clearly state all	pertinent details, and	d give pertinent dates, including estimated date
13. Describe proposed or composed wo	rk). SEE RULE 19.15.7.14 NMA	pertinent details, and C. For Multiple Con	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of
13. Describe proposed or comp	rk). SEE RULE 19.15.7.14 NMA	pertinent details, and C. For Multiple Con	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of
13. Describe proposed or composed starting any proposed wo proposed completion or reco	rk). SEE RULE 19.15.7.14 NMA	pertinent details, and C. For Multiple Con	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of
13. Describe proposed or composed wo proposed completion or reco	rk). SEE RULE 19.15.7.14 NMA( ompletion.	C. For Multiple Co	mpletions: Attach wellbore diagram of
13. Describe proposed or composed we proposed completion or reconstruction of starting any proposed we proposed completion or reconstruction of the second s	rk). SEE RULE 19.15.7.14 NMA(completion.	C. For Multiple Core emented with 450 s	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g
13. Describe proposed or composed of starting any proposed we proposed completion or reconstruction of the starting any proposed we proposed completion or reconstruction of the starting and proposed with the starting and proposed with the starting and proposed with the starting and the starting	rk). SEE RULE 19.15.7.14 NMAG ompletion. of 13 3/8" 54.5# J55 ST&C Csg. C W. Plug down @ 1:00 AM 10/18/1	C. For Multiple Conference with 450 states of conference conferenc	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular
13. Describe proposed or composed we proposed completion or reconstruction of starting any proposed we proposed completion or reconstruction of the second s	rk). SEE RULE 19.15.7.14 NMAG ompletion. of 13 3/8" 54.5# J55 ST&C Csg. C W. Plug down @ 1:00 AM 10/18/1	C. For Multiple Conference with 450 states of conference conferenc	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular
13. Describe proposed or composed of starting any proposed we proposed completion or reconstruction of the starting any proposed we proposed completion or reconstruction of the starting any proposed we are starting any proposed with the starting any proposed with the starting and the starting a	rk). SEE RULE 19.15.7.14 NMAG ompletion. of 13 3/8" 54.5# J55 ST&C Csg. C W. Plug down @ 1:00 AM 10/18/1	C. For Multiple Conference with 450 states of conference conferenc	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular
13. Describe proposed or composed of starting any proposed we proposed completion or reconstruction of the starting any proposed we proposed completion or reconstruction of the starting any proposed we are starting any proposed with the starting any proposed with the starting and the starting a	rk). SEE RULE 19.15.7.14 NMAG completion. of 13 3/8" 54.5# J55 ST&C Csg. C W. Plug down @ 1:00 AM 10/18/1 ted csg to 1500#, held OK. FIT tes	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW	sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular 7. Drilled out with 12 1/4" bit.
13. Describe proposed or composed of starting any proposed we proposed completion or reconstruction of the starting any proposed we proposed completion or reconstruction of the starting any proposed we are starting any proposed we are starting any proposed with a starting any proposed with a starting any proposed we are starting any proposed with a starting any proposed we are starting any proposed or composed or composed we are starting any proposed we proposed we are starting any proposed we proposed we proposed we are starting any proposed we proposed we proposed we proposed we proposed we proposed we proposed completion or reconstruction and starting any proposed we proposed we proposed completion or reconstruction and starting any proposed we proposed completion or reconstruction and starting any proposed we proposed completion or reconstruction and starting and	rk). SEE RULE 19.15.7.14 NMAGE ompletion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/1 ted csg to 1500#, held OK. FIT tes  20' of 9 5/8" 40# N80 LT&C Csg.	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g cmt to the pits. Test BOPE to 5000# & Annular 7. Drilled out with 12 1/4" bit.
13. Describe proposed or composed we proposed completion or recomproposed completion o	rk). SEE RULE 19.15.7.14 NMA6 completion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/1 ted csg to 1500#, held OK. FIT tes  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular J. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM
13. Describe proposed or composed we proposed completion or reconstruction of starting any proposed we proposed completion or reconstruction of the starting any proposed we proposed completion or reconstruction of the starting and proposed with the starting and proposed we proposed with the starting and the starting with	rk). SEE RULE 19.15.7.14 NMA6 completion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/1 ted csg to 1500#, held OK. FIT tes  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g cmt to the pits. Test BOPE to 5000# & Annular 7. Drilled out with 12 1/4" bit.
13. Describe proposed or composed we proposed completion or recomproposed completion o	rk). SEE RULE 19.15.7.14 NMA6 completion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/1 ted csg to 1500#, held OK. FIT tes  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular J. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM
13. Describe proposed or composed we proposed completion or reconstruction of starting any proposed we proposed completion or reconstruction of the starting any proposed we proposed completion or reconstruction of the starting and proposed with the starting and proposed we proposed with the starting and the starting with	rk). SEE RULE 19.15.7.14 NMA6 completion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/1 ted csg to 1500#, held OK. FIT tes  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular J. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM
13. Describe proposed or composed we proposed completion or reconstruction of starting any proposed we proposed completion or reconstruction of 10/17/18  Spud 17 1/2" hole @ 490'. Ran 475' w/1.33 yd. Displaced w/66 bbls of B to 3500#. At 8:00 P.M. 10/09/18, tes  10/21/18  TD'ed 12 1/4" hole @ 2645'. Ran 26 2.47 yd. Tail w/200 sks Class C Near 10/21/18. Circ 101 sks of cmt to the held OK. FIT test to EMW of 10.0 P	rk). SEE RULE 19.15.7.14 NMA6 completion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tes  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular J. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM
13. Describe proposed or composed we proposed completion or reconstruction of starting any proposed we proposed completion or reconstruction of the starting any proposed we proposed completion or reconstruction of the starting and proposed with the starting and proposed we proposed with the starting and the starting with	rk). SEE RULE 19.15.7.14 NMA6 completion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/1 ted csg to 1500#, held OK. FIT tes  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular J. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM
13. Describe proposed or composed we proposed completion or reconstruction of starting any proposed we proposed completion or reconstruction of 10/17/18  Spud 17 1/2" hole @ 490'. Ran 475' w/1.33 yd. Displaced w/66 bbls of B to 3500#. At 8:00 P.M. 10/09/18, tes  10/21/18  TD'ed 12 1/4" hole @ 2645'. Ran 26 2.47 yd. Tail w/200 sks Class C Near 10/21/18. Circ 101 sks of cmt to the held OK. FIT test to EMW of 10.0 P	rk). SEE RULE 19.15.7.14 NMA6 completion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tes  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular J. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM
13. Describe proposed or composed starting any proposed we proposed completion or reconsequence of starting any proposed we proposed completion or reconsequence of the starting any proposed we proposed completion or reconsequence of the starting and starting any proposed with the starting and starting a	rk). SEE RULE 19.15.7.14 NMAGOMPletion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tess  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.  Rig Releas	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k	sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular //. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM e.#. At 4:30 A.M. 10/22/18, tested csg to 1500#,
13. Describe proposed or composed we proposed completion or reconstruction of starting any proposed we proposed completion or reconstruction of 10/17/18  Spud 17 1/2" hole @ 490'. Ran 475' w/1.33 yd. Displaced w/66 bbls of B to 3500#. At 8:00 P.M. 10/09/18, tes  10/21/18  TD'ed 12 1/4" hole @ 2645'. Ran 26 2.47 yd. Tail w/200 sks Class C Near 10/21/18. Circ 101 sks of cmt to the held OK. FIT test to EMW of 10.0 P	rk). SEE RULE 19.15.7.14 NMAGOMPletion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tess  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.  Rig Releas	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k	sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular //. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM e.#. At 4:30 A.M. 10/22/18, tested csg to 1500#,
13. Describe proposed or composed starting any proposed we proposed completion or reconsequence of starting any proposed we proposed completion or reconsequence of the starting any proposed we proposed completion or reconsequence of the starting and starting any proposed with the starting and starting a	rk). SEE RULE 19.15.7.14 NMAGOMPletion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tess  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.  Rig Releas	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k	sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular //. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM e.#. At 4:30 A.M. 10/22/18, tested csg to 1500#,
13. Describe proposed or composed starting any proposed we proposed completion or recomposed with the second starting and the second starting and the second with	rk). SEE RULE 19.15.7.14 NMA6 completion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tes 20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.  Rig Release	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k e Date:	sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular 7. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM e.#. At 4:30 A.M. 10/22/18, tested csg to 1500#, e. and belief.
13. Describe proposed or composed starting any proposed we proposed completion or reconsequence of starting any proposed we proposed completion or reconsequence of the starting any proposed we proposed completion or reconsequence of the starting and starting any proposed with the starting and starting a	rk). SEE RULE 19.15.7.14 NMA6 completion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tes 20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.  Rig Release	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k	sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular //. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM e.#. At 4:30 A.M. 10/22/18, tested csg to 1500#,
13. Describe proposed or composed starting any proposed we proposed completion or recomposed completion or recompletion or recomposed completion or recompletion or recomposed completion or recompletion or recomposed completion or recompletion or recomple	rk). SEE RULE 19.15.7.14 NMAGOMPletion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tess  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.  Rig Release above is true and complete to the barries.	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k e Date:	sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular //. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM e.#. At 4:30 A.M. 10/22/18, tested csg to 1500#,  The and belief.
13. Describe proposed or composed starting any proposed we proposed completion or recomposed with the second starting and proposed with the second with	rk). SEE RULE 19.15.7.14 NMAGOMPletion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tess  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.  Rig Release above is true and complete to the barries.	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k e Date:	sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular //. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM e.#. At 4:30 A.M. 10/22/18, tested csg to 1500#,  The and belief.
13. Describe proposed or composed starting any proposed we proposed completion or recomposed completion or recompletion or recomposed completion or recompletion or recomposed completion or recompletion or recomposed completion or recompletion or recomple	rk). SEE RULE 19.15.7.14 NMAGOMPletion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tess  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.  Rig Release above is true and complete to the barries.	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k e Date:	mpletions: Attach wellbore diagram of sks Class C w/2% CaCl2. Mixed @ 14.8#/g cmt to the pits. Test BOPE to 5000# & Annular V. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM cmt. At 4:30 A.M. 10/22/18, tested csg to 1500#,  The property of the pits of the
13. Describe proposed or composed starting any proposed we proposed completion or recomposed with the second starting and proposed with the second with	rk). SEE RULE 19.15.7.14 NMAGOMPletion.  of 13 3/8" 54.5# J55 ST&C Csg. CW. Plug down @ 1:00 AM 10/18/18 ted csg to 1500#, held OK. FIT tess  20' of 9 5/8" 40# N80 LT&C Csg. tw/additives. Mixed @ 14.8#/g w/pits. Set Cameron mandrel hanger PG. Drilled out with 8 3/4" bit.  Rig Release above is true and complete to the barries.	emented with 450 s 8. Circ 150 sks of c to 10.5 PPG EMW Cemented w/450 sk 1.32 yd. Displaced v hrough BOP w/90k e Date:	sks Class C w/2% CaCl2. Mixed @ 14.8#/g emt to the pits. Test BOPE to 5000# & Annular //. Drilled out with 12 1/4" bit.  See Class C w/additives. Mixed @ 12.2#/g w/w/195 bbls FW. Plug down @ 2:15 PM e.#. At 4:30 A.M. 10/22/18, tested csg to 1500#,  The and belief.