TED STATES OCD Artesia

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5. Lease Serial No. NMNM067896


SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

C. ISI-dia- Allamas au Taiba Nama

abandoned wel	II. Use form 3160-3 (APD)) for such p	roposals.		6. If Indian, Allottee or	I ribe Name		
SUBMIT IN 1	7. If Unit or CA/Agreement, Name and/or No.		hut-Off tegrity thereof. d zones. days ed once r has					
Type of Well Gas Well ☐ Oth	8. Well Name and No. SHUGART WEST 19 6							
Name of Operator MARATHON OIL PERMIAN L		9. API Well No. 30-015-30689-00-S1						
3a. Address 5555 SAN FELIPE ST HOUSTON, TX 77056	(include area code) 3-3179		10. Field and Pool or Exploratory Area SHUGART					
4. Location of Well (Footage, Sec., T	, R., M., or Survey Description)			11. County or Parish, State				
Sec 19 T18S R31E SWNE 19			EDDY COUNTY	, NM				
12. CHECK THE AF	PROPRIATE BOX(ES)	TO INDICAT	TE NATURE O	F NOTICE,	REPORT, OR OTH	ER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION							
Notice of Intent ■	☐ Acidize ☐ Deepen		oen	☐ Product	☐ Production (Start/Resume)		t-Off	
	☐ Alter Casing	☐ Hydi	☐ Hydraulic Fracturing ☐ Re		ation	■ Well Integ	rity;	
☐ Subsequent Report	☐ Casing Repair ☐ New Construction			☐ Recomp	olete	Other		
☐ Final Abandonment Notice	☐ Change Plans			arily Abandon				
	Convert to Injection	☐ Plug	Back	□ Water I	Disposal			
Attach the Bond under which the worfollowing completion of the involved testing has been completed. Final At determined that the site is ready for ff 1) 5-1/2" CIBP @ 7650' w/35x 2) 35sx 5850'-5750' P.S. \$ 13) 40sx 2860'-2760' P.S. & 140' 50sx 568'-468' P.S. & 140' 50sx 568' P.S. & 140' 50sx 56	operations. If the operation responded ment Notices must be file in all inspection. 73 4 (T/As) 9. Add All S w/30sx. Verify. Install DH Completed CONDITIONS 20 Accepted CONDITIONS	Add M. 2/3/I	e completion or reco equirements, includ Plag. Per MMOCD Per 25 Per 25 Per 25	mpletion in a ring reclamatio	SO, SQZ CO SO, SQZ CO (T/Del.) RESO, SQZ OC Tag 825 SQZ OC Tag (ent to the operator has a continuous to the operator has a continuous to the continu	once 45∞.	
14. I hereby certify that the foregoing is	Electronic Submission #4 For MARATHON	N OIL PERMIA	N ĽLC, sent to th	ne Carlsbad	•	FEB 1 2 20	119	
Committed to AFMSS for processing by PRISCILLA PEREZ on 02 Name (Printed/Typed) MELISSA SZUDERA Title REGULAT					MPLIANCE RESTRIC	CT II-ARTESIA	4 O.C.D.	
Signature (Electronic	Submission)		Date 02/06/2	019			<u> </u>	
	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE U	SE			
Approved By Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease			Title SA	<u>ST</u>		2-9 Date	V-19 -	
which would entitle the applicant to condi	uct operations thereon.		Office CF	0			<u>-</u>	
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a statements or representations as	crime for any pe	rson knowingly and thin its jurisdiction.	willfully to m	ake to any department or	agency of the Un	ited	

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **



aratho		VVeilla	Oremontenano		
urati 10			GART WEST 19 FEI	DERAL 6	
YProvince .		30-015	30629		
W MEXICO	Prospect Area	Shift transmin	Well Salare	Water State of the	
	Walto	(od.v)	PRODUCING	(Settlered Senters (4)	
		Children was a series	and the state of the same of t	7 520 00	
MD (flKB)		SHUGART WEST 19 F	FDERAL 8, 2/4/7019 11 49 Vertical schematic (actu	9 46 AM	
	ļ	the same of the sa		Andrewsky a company of the second sec	
0.0					
					11
12,1				_	11
17/2"		Das:Surface Casing Cement:		Des Surface, Category Casilin, ID 12 715 in; Length 608	ng OD <u>13,375</u>
	Category:Cen	nent; Top MD:12.0 ftKB; Blm		Min 12.559 in, Wt. 48.00 lb/f Top MD:12.0 ftXB; Birn MD	t, Grade H40.
518.0	Des:Ir	ntermediate Casina Cement		Destintermediate f: Categor	V.Casino.
11"	Category:Cen MD	nent; Top MD:12.0 flKB; Blm 0:2,810.0 flKB; Com:600 sks		OD 8 625 in, ID:7.921 in; Le	ngth 2 798.00
2,810.0				Grade J55; Top MD 12.0 RK MD 2,810.0 bKB	B Btm
ľ		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		Tubing; 2.875	cossession
,368.1					
,	Des:	Production Casing Cement;			į
	Category:Ce	ment; Top MD:6,368.0 ftkB:			ł
.733.9	Bim MD	:8,350.0 ftKB; Com:270 sks			
	_/	او ومووت		Top MD:7,734.0; Btm MD:7	1.744.0
744.1	1/8019	775		_	
ŀ					
796.9		2000			
- 4	Vide	2600			
7/8	Jares				
086.9					
ŀ				————Cast Iron Bridge Plug; 8.0	90.0
089.9	\sim 2	50 96			
	(Yu)	41530			
ļ	5/4	096 4530 460°			
146.0	Del	460		Top MD:8,146.0; Btm MD:	8.212.0:
		and the second second		Com:8146-8180' & 8197-8	
211.9	Bi	San All Price 1		•	
	,54	601			
282.2	i	», V-		Cast Iron Bridge Plug; 8,2	85.0
	200	145 I			
285.1	2				
319.9	Des:Cement F	Plug; Category:Cement; Top ftKB; 8tm MD:8,350.0 ftKB			
J.3.3	MD:8,320.0	IND, DIN NULL, 1, 200, VIND		Des:Production 1; Catego OD:5.500 in; ID:4.950 in;	Length: 8,338,00
1				A- IO Min-4.825 in: Wt.:15.	.50 lb/ft;
350.1				Grade:K55; Top MD:12.0 MD:8,350,0 flKB	
					. *.
ns to Well:	1	Dy A			
المصرم	n to	PAA			- Miles No. 2 Marie - 12
,			Page 1/1	Repor	t Printed: 2/4/2019

Marathon Oil

Wellbore Schematic

Well Name: SHUGART WEST 19 FEDERAL 6

30 11 30689

SHUGART WEST 19 FEDERAL 6, 2/4/2019 11:49:48 AM

MD (RKB)

Prospoci Area

Prospoci Area

SHUGART WEST 19 FEDERAL 6, 2/4/2019 11:49:48 AM

Vortical schleroute (adduce)

Vertical schematic (actual) D.H.M. Very Dy 0.0 Des:Surface; Category:Casing; OD:13.375
In; ID:12.715 In; Length:506.00 ft; ID
Min:12.559 in; Wt.:48.00 lb/ft; Grade:H40;
Top MD:12.0 ftKB; Birn MD:518.0 ftKB 105 568-46R' MS+TAG 12,1 Des:Surface Casing Cement; Category:Cement; Top MD:12.0 ftKB; Btm MD:518.0 flKB; Com:415 sks 518.0 Destintermediate 1; Category:Casing; Des:Intermediate Casing Cement: OD:8.625 in; ID:7.921 in; Length:2,798.00 Category: Cement; Top MD:12.0 ftKB; Btmft; ID Min:7.796 in; Wt.:32.00 lb/ft; Grade:J55; Top MD:12.0 ftKB; Btm MD:2,810.0 flKB; Com:600 sks 405% 2860-2760 2,810.0 MD:2,810.0 ftKB 35% 5850-5750 PS 6,368.1 Des:Production Casing Cement; Category: Cement; Top MD:6,368.0 flKB: CIBP 7658 W) 35's+ Btm MD:8,350.0 ftKB; Com:270 sks 7,733.9 Top MD:7,734.0; Btm MD:7,744.0 7,744.1 7,796.9 8,086.9 Cast Iron Bridge Plug; 8,090.0 8.089.9 8,146.0 Top MD:8,146.0; Btm MD:8,212.0; Com:8146-8180' & 8197-8212' 8,211.9 8,282.2 Cast Iron Bridge Plug; 8,285.0 8,285.1 Des:Cement Plug; Category:Cement; Top 8,319.9 MD:8,320.0 ftKB; Btm MD:8,350.0 ftKB Des:Production 1; Category:Casing; OD:5.500 in; ID:4.950 in; Length:8,388.00 ft: ID Min:4.825 in; Wt.:15.50 lb/ft; Grade:K55; Top MD:12.0 ftKB; Bim 8,350.1 MD:8,350.0 flKB

irections to Well:

After PAA

Report Printed: 2/4/2019

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:</u>
From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted