<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 MAR 0 7 2019					
		GAS CAPTU	GAS CAPTURE PLAN		RECEIVED		
⊠ Original □ Amended	Operator: Apache Corporation	on OGRID No:	873	Date: Date:	_5/16/2018		

Reason for Amendment:

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

## Well(s)/Production Facility - Name of facility

		· · · · · · · ·	shown in the table beit			
Well Name	API	Well Location	Footages	Expected	Flared or	Comments
		(ULSTR)	Ŭ	MCF/D	Vented	
Salt Fork 3-4 Federal Com 101H <b>30</b>	015-45173	Sec 3 T19S R30E	2255' FSL & 2277' FWL	1300	Flared	Flared only in emergency
Salt Fork 3-4 Federal Com 102H		Sec 3 T19S R31E	2205' FSL & 2284' FWL	1300	Flared	Flared only in emergency
Salt Fork 3-4 Federal Com 301H		Sec 3 T19S R31E	2280' FSL & 2274' FWL	600	Flared	Flared only in emergency
Salt Fork 3-4 Federal Com 302H		Sec 3 T19S R31E	2230' FSL & 2280' FWL	600	Flared	Flared only in emergency

The well(s) that will be located at the production facility are shown in the table below.

## Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to <u>SUMMIT ENERGY, LLC</u> and will be connected to <u>SUMMIT'S</u> <u>LOW</u> pressure gathering system located in <u>EDDY</u> County, New Mexico. It will require <u>0</u> ft of pipeline to connect the facility to <u>LOW</u> pressure gathering system. Apache Corporation provides (periodically) to <u>SUMMIT ENERGY, LLC</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Apache Corporation and <u>SUMMIT ENERGY, LLC</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <u>SUMMIT'S LANE</u> Processing Plant located in <u>Sec. 26, Twp</u> <u>20S, Rng 31E, EDDY County</u>, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

## Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on **SUMMIT ENERGY, LLC** system at that time. Based on current information, it is Apache Corporation's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

## Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
  - Compressed Natural Gas On lease
    - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines