

Quail 2 State Com #581H  
Eddy County, New Mexico

Proposed Wellbore


200' FNL  
306' FEL  
Section 2  
T-26-S, R-30-E

API: 30-025-\*\*\*\*\*

15 45787

KB: 3,268'

GL: 3,243'



Lateral: 15,248' MD, 10,276' TVD  
BH Location: 100' FSL & 330' FEL  
Section 2  
T-26-S, R-30-E

**EOG RESOURCES, INC.**  
**Quail 2 State Com #581H**

## **Hydrogen Sulfide Plan Summary**

- A. All personnel shall receive proper H<sub>2</sub>S training in accordance with Onshore Order III.C.3.a.
- B. Briefing Area: two perpendicular areas will be designated by signs and readily accessible.
- C. Required Emergency Equipment:
  - Well control equipment
    - a. Flare line 150' from wellhead to be ignited by flare gun.
    - b. Choke manifold with a remotely operated choke.
    - c. Mud/gas separator
  - Protective equipment for essential personnel.

Breathing apparatus:

    - a. Rescue Packs (SCBA) — 1 unit shall be placed at each breathing area, 2 shall be stored in the safety trailer.
    - b. Work/Escapes packs — 4 packs shall be stored on the rig floor with sufficient air hose not to restrict work activity.
    - c. Emergency Escape Packs — 4 packs shall be stored in the doghouse for emergency evacuation.

Auxiliary Rescue Equipment:

    - a. Stretcher
    - b. Two OSHA full body harness
    - c. 100 ft 5/8 inch OSHA approved rope
    - d. 1-20# class ABC fire extinguisher
  - H<sub>2</sub>S detection and monitoring equipment:

The stationary detector with three sensors will be placed in the upper dog house if equipped, set to visually alarm @ 10 ppm and audible @ 14 ppm. Calibrate a minimum of every 30 days or as needed. The sensors will be placed in the following places: Rig floor / Bell nipple / End of flow line or where well bore fluid is being discharged.

(Gas sample tubes will be stored in the safety trailer)
  - Visual warning systems.
    - a. One color code condition sign will be placed at the entrance to the site reflecting the possible conditions at the site.
    - b. A colored condition flag will be on display, reflecting the current condition at the site at the time.
    - c. Two wind socks will be placed in strategic locations, visible from all angles.

**EOG RESOURCES, INC.**  
**Quail 2 State Com #581H**

- **Mud program:**  
The mud program has been designed to minimize the volume of H<sub>2</sub>S circulated to surface. The operator will have the necessary mud products to minimize hazards while drilling in H<sub>2</sub>S bearing zones.
- **Metallurgy:**  
All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H<sub>2</sub>S service.
- **Communication:**  
Communication will be via cell phones and land lines where available.

**EOG RESOURCES, INC.**  
**Quail 2 State Com #581H**

**Emergency Assistance Telephone List**

<b><u>PUBLIC SAFETY:</u></b>	<b><u>911 or</u></b>
Lea County Sheriff's Department	(575) 396-3611
Rod Coffman	
Fire Department:	
Carlsbad	(575) 885-3125
Artesia	(575) 746-5050
Hospitals:	
Carlsbad	(575) 887-4121
Artesia	(575) 748-3333
Hobbs	(575) 392-1979
Dept. of Public Safety/Carlsbad	(575) 748-9718
Highway Department	(575) 885-3281
New Mexico Oil Conservation	(575) 476-3440
U.S. Dept. of Labor	(575) 887-1174
<b><u>EOG Resources, Inc.</u></b>	
EOG / Midland	Office (432) 686-3600
<b><u>Company Drilling Consultants:</u></b>	
David Dominique	Cell (985) 518-5839
Mike Vann	Cell (817) 980-5507
<b><u>Drilling Engineer</u></b>	
Steve Munsell	Office (432) 686-3609
	Cell (432) 894-1256
<b><u>Drilling Manager</u></b>	
Aj Dach	Office (432) 686-3751
	Cell (817) 480-1167
<b><u>Drilling Superintendent</u></b>	
Domingo Lopez	Office (432) 686-3702
	Cell (432) 215-9452
<b><u>H&amp;P Drilling</u></b>	
H&P Drilling	Office (432) 563-5757
H&P 651 Drilling Rig	Rig (903) 509-7131
<b><u>Tool Pusher:</u></b>	
Johnathan Craig	Cell (817) 760-6374
Brad Garrett	
<b><u>Safety</u></b>	
Brian Chandler (HSE Manager)	Office (432) 686-3695
	Cell (817) 239-0251