	NOTICES AND REPO	RTS ON WELLS	rtesia	5. Lease Serial No. NMNM88128		
Do not use thi abandoned wel	is form for proposals to II. Use form 3160-3 (API	drill or to re-enter an		6. If Indian, Allottee	or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2			7. If Unit or CA/Agreement, Name and/or No			
 Type of Well Oil Well	······································			II Name and No. VERBEND 12-13 FEDERAL COM 29		
		ATIMA VASQUEZ narex.com		9. API Well No. 30-015-45021-00-X1		
3a. Address 600 N MARIENFELD STE 600 MIDLAND, TX 79701		3b. Bhone No. (include area code) Ph: 1482.620-1933 WSERVATION ARTESIA DISTRICT		10. Field and Pool or Exploratory Area WOLFCAMP		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description))		11. County or Parish, State		
Sec 1 T25S R28E NESW 1379FSL 1396FWL 32.155834 N Lat, 104.044937 W Lon			MAR 1 1 2019		EDDY COUNTY, NM	
		RECEIVED				
12. CHECK THE AF	PROPRIATE BOX(ES)	TO INDICATE NATURE OF	F NOTICE, 1	KEPORT, OR OT	HER DATA	
TYPE OF SUBMISSION	· ·	TYPE OF	TYPE OF ACTION			
	☐ Acidize	Deepen	Productio	on (Start/Resume)	□ Water Shut-Of	
Notice of Intent	Alter Casing	Hydraulic Fracturing	□ Reclama		U Well Integrity	
🛛 Subsequent Report	Casing Repair	□ New Construction	Recompl	lete	🛛 Other	
Final Abandonment Notice	Change Plans	Plug and Abandon	Tempora	arily Abandon	Production Start-	
	Convert to Injection	Plug Back	🗖 Water D	isposal	:	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final At determined that the site is ready for fi 07/28/2018 Spud well.	k will be performed or provide operations. If the operation re bandonment Notices must be fil inal inspection.	give subsurface locations and measur the Bond No. on file with BLM/BIA sults in a multiple completion or reco	red and true ver . Required sub mpletion in a n	rtical depths of all perti sequent reports must b ew interval, a Form 31	e filed within 30 days 60-4 must be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final At determined that the site is ready for fi	rk will be performed or provide operations. If the operation re- bandonment Notices must be fil- inal inspection. 55, 48#, ST&C csg & set . WOC 8 hrs. & notify BLM. RIH w/ 1" a e. WOC 13 hrs. 53 for 30 mins. OK. 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp 800 sx Class C, 13.7 ps 2400 psi for 30 min, good	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco- led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class :sq to 2400 psi.	red and true ver Required sub- mpletion in a n- ing reclamation Class C, 14. ppg, 1.33 yl [8].	rtical depths of all perti sequent reports must b ew interval, a Form 31 i, have been completed .8	inent markers and zones e filed within 30 days 60-4 must be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 07/28/2018 Spud well. 07/28/2018 TD 17-1/2" surface 07/29/2018 RIH w/ 13-3/8", J-1 ppg, 1.35 yld. No cmt returns. 07/30/2018 Tag TOC @ 196' d Class C. Circ 42 sx to surface 07/31/2018 Test csg to 1500 p 08/02/2018 TD 12-1/4" hole @ 08/03/2018 Mix & pump lead: 1.348 yld. Circ 487 sx to surface 08/04/2018 Test csg again to 08/11/2018 TD vertical hole @	rk will be performed or provide operations. If the operation re- bandonment Notices must be fil- inal inspection. e hole @ 461'. 55, 48#, ST&C csg & set . WOC 8 hrs. & notify BLM. RIH w/ 1" a e. WOC 13 hrs. psi for 30 mins. OK. 2 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp ace. WOC 13 hrs. Test of 2400 psi for 30 min, good 210,255'.	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco- led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class :sq to 2400 psi.	red and true ver Required sub- mpletion in a n- ing reclamation Class C, 14. ppg, 1.33 yl [8].	rtical depths of all perti sequent reports must b ew interval, a Form 31 i, have been completed .8	inent markers and zones e filed within 30 days 60-4 must be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 07/28/2018 Spud well. 07/28/2018 TD 17-1/2" surface 07/29/2018 RIH w/ 13-3/8", J-1 ppg, 1.35 yld. No cmt returns. 07/30/2018 Tag TOC @ 196' d Class C. Circ 42 sx to surface 07/31/2018 Test csg to 1500 p 08/02/2018 TD 12-1/4" hole @ 08/03/2018 Mix & pump lead: 1.348 yld. Circ 487 sx to surface 08/04/2018 Test csg again to 08/11/2018 TD vertical hole @	rk will be performed or provide operations. If the operation re bandonment Notices must be fil inal inspection. e hole @ 461'. 55, 48#, ST&C csg & set . WOC 8 hrs. & notify BLM. RIH w/ 1" a a. WOC 13 hrs. bi for 30 mins. OK. 2 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp ace. WOC 13 hrs. Test of 2400 psi for 30 min, good 210,255'. true and correct. Electronic Submission # For CIMAREX	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco- led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class :sq to 2400 psi.	red and true ver Required sub mpletion in a n ing reclamation Class C, 14. ppg, 1.33 yl 18'. s C, 14.8 ppg	rtical depths of all perti sequent reports must b ew interval, a Form 31 i, have been completed .8 Id g, System	inent markers and zones e filed within 30 days 60-4 must be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 07/28/2018 Spud well. 07/28/2018 TD 17-1/2" surface 07/29/2018 RIH w/ 13-3/8", J-1 ppg, 1.35 yld. No cmt returns. 07/30/2018 Tag TOC @ 196' d Class C. Circ 42 sx to surface 07/31/2018 Test csg to 1500 p 08/02/2018 TD 12-1/4" hole @ 08/03/2018 Mix & pump lead: 1.348 yld. Circ 487 sx to surface 08/04/2018 Test csg again to 08/11/2018 TD vertical hole @	rk will be performed or provide operations. If the operation re- bandonment Notices must be fil- inal inspection. e hole @ 461'. 55, 48#, ST&C csg & set . WOC 8 hrs. & notify BLM. RIH w/ 1" a e. WOC 13 hrs. pais for 30 mins. OK. 2 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp ace. WOC 13 hrs. Test of 2400 psi for 30 min, good 2400 psi for 30 min, good 10,255'. true and correct. Electronic Submission # For CIMAREX mitted to AFMSS for proc	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -sg to 2400 psi. I test. 	red and true ver Required sub mpletion in a n ing reclamation Class C, 14. ppg, 1.33 yl 18'. s C, 14.8 ppg	rtical depths of all perti sequent reports must b ew interval, a Form 31 i, have been completed .8 Id g, System (19PP1064SE)	inent markers and zones e filed within 30 days 60-4 must be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 07/28/2018 TD 17-1/2" surface 07/29/2018 RIH w/ 13-3/8", J-4 ppg, 1.35 yld. No cmt returns. 07/30/2018 Tag TOC @ 196' of Class C. Circ 42 sx to surface 07/31/2018 Test csg to 1500 p 08/02/2018 TD 12-1/4" hole @ 08/03/2018 Mix & pump lead: 1.348 yld. Circ 487 sx to surface 08/04/2018 Test csg again to 08/11/2018 TD vertical hole @	rk will be performed or provide operations. If the operation re- bandonment Notices must be fil- inal inspection. e hole @ 461'. 55, 48#, ST&C csg & set . WOC 8 hrs. & notify BLM. RIH w/ 1" a e. WOC 13 hrs. 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp ace. WOC 13 hrs. Test of 2400 psi for 30 min, good 210,255'. true and correct. Electronic Submission # For CIMAREX mitted to AFMSS for proc (ASQUEZ	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -sg to 2400 psi. I test. 454356 verified by the BLM Well ENERGY COMPANY, sent to the essing by PRISCILLA PEREZ or Title REGULA	red and true ver Required sub mpletion in a n ing reclamation Class C, 14, ppg, 1.33 yl 18'. s C, 14.8 ppg 10, 14.8 ppg carlsbad n 02/14/2019 (ATORY ANA	rtical depths of all perti sequent reports must b ew interval, a Form 31 i, have been completed .8 Id g, System (19PP1064SE)	inent markers and zones e filed within 30 days 60-4 must be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 07/28/2018 TD 17-1/2" surface 07/29/2018 RIH w/ 13-3/8", J-4 ppg, 1.35 yld. No cmt returns. 07/30/2018 Tag TOC @ 196' of Class C. Circ 42 sx to surface 07/31/2018 Test csg to 1500 p 08/02/2018 TD 12-1/4" hole @ 08/03/2018 Mix & pump lead: 1.348 yld. Circ 487 sx to surfa 08/04/2018 Test csg again to 08/11/2018 TD vertical hole @ 14. I hereby certify that the foregoing is Name (Printed/Typed) FATIMA V	rk will be performed or provide operations. If the operation re- bandonment Notices must be fil- inal inspection. e hole @ 461'. 55, 48#, ST&C csg & set . WOC 8 hrs. & notify BLM. RIH w/ 1" a e. WOC 13 hrs. bsi for 30 mins. OK. 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp 800 sx Class C, 10.7 pp 800 sx Class C, 1	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -sg to 2400 psi. I test. 454356 verified by the BLM Well ENERGY COMPANY, sent to the essing by PRISCILLA PEREZ or Title REGUL/	red and true ver Required sub- mpletion in a m ing reclamation Class C, 14. ppg, 1.33 yl 8'. s C, 14.8 ppg I Information e Carlsbad n 02/14/2019 (ATORY ANA	rtical depths of all perti sequent reports must b ew interval, a Form 31 , have been completed .8 Id g, System (19PP1064SE) ALYST	inent markers and zones e filed within 30 days 60-4 must be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 07/28/2018 TD 17-1/2" surface 07/29/2018 RIH w/ 13-3/8", J-4 ppg, 1.35 yld. No cmt returns. 07/30/2018 Tag TOC @ 196' of Class C. Circ 42 sx to surface 07/31/2018 Test csg to 1500 p 08/02/2018 TD 12-1/4" hole @ 08/03/2018 Mix & pump lead: 1.348 yld. Circ 487 sx to surfa 08/04/2018 Test csg again to 08/11/2018 TD vertical hole @ 14. I hereby certify that the foregoing is Name (Printed/Typed) FATIMA V	rk will be performed or provide operations. If the operation re- bandonment Notices must be fil- inal inspection. e hole @ 461'. 55, 48#, ST&C csg & set . WOC 8 hrs. & notify BLM. RIH w/ 1" a e. WOC 13 hrs. bsi for 30 mins. OK. 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp 800 sx Class C, 10.7 pp 800 sx Class C, 1	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -sg to 2400 psi. 	red and true ver Required sub mpletion in a n ing reclamation Class C, 14. ppg, 1.33 yl B'. s C, 14.8 ppg I Information e Carlsbad n 02/14/2019 (ATORY ANA D19 OFFICE US	rtical depths of all perti sequent reports must b ew interval, a Form 31 i, have been completed .8 Id g, System (19PP1064SE) ALYST SE	inent markers and zones e filed within 30 days 60-4 must be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 07/28/2018 TD 17-1/2" surface 07/29/2018 RIH w/ 13-3/8", J-4 ppg, 1.35 yld. No cmt returns. 07/30/2018 Tag TOC @ 196' of Class C. Circ 42 sx to surface 07/31/2018 Test csg to 1500 p 08/02/2018 TD 12-1/4" hole @ 08/03/2018 Mix & pump lead: 1.348 yld. Circ 487 sx to surfa 08/04/2018 Test csg again to 08/11/2018 TD vertical hole @ 14. I hereby certify that the foregoing is Name (Printed/Typed) FATIMA V	rk will be performed or provide operations. If the operation re- bandonment Notices must be fil- inal inspection. e hole @ 461'. 55, 48#, ST&C csg & set . WOC 8 hrs. & notify BLM. RIH w/ 1" a e. WOC 13 hrs. bsi for 30 mins. OK. 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp 800 sx Class C, 10.7 pp 800 sx Class C, 1	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco- led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -sg to 2400 psi. 	red and true ver Required sub mpletion in a n ing reclamation Class C, 14. ppg, 1.33 yl B'. s C, 14.8 ppg I Information e Carlsbad n 02/14/2019 (ATORY ANA D19 OFFICE US	rtical depths of all perti sequent reports must b ew interval, a Form 31 i, have been completed .8 Id g, System (19PP1064SE) ALYST SE	inent markers and zones e filed within 30 days 60-4 must be filed once	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 07/28/2018 Spud well. 07/28/2018 TD 17-1/2" surface 07/29/2018 RIH w/ 13-3/8", J-4 ppg, 1.35 yld. No cmt returns. 07/30/2018 Tag TOC @ 196 d Class C. Circ 42 sx to surface 07/31/2018 Test csg to 1500 p 08/02/2018 TD 12-1/4" hole @ 08/03/2018 Mix & pump lead: 1.348 yld. Circ 487 sx to surface 08/04/2018 Test csg again to 08/11/2018 TD vertical hole @ 14. I hereby certify that the foregoing is Corr Name (<i>Printed/Typed</i>) FATIMA V Signature (Electronic S 	rk will be performed or provide operations. If the operation re- bandonment Notices must be fil- inal inspection. e hole @ 461'. 55, 48#, ST&C csg & set. WOC 8 hrs. & notify BLM. RIH w/ 1" a e. WOC 13 hrs. Disfor 30 mins. OK. 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp 800 sx Class C, 14.	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 	red and true ver Required sub mpletion in a n ing reclamation Class C, 14. ppg, 1.33 yl B'. s C, 14.8 ppg I Information e Carlsbad n 02/14/2019 (ATORY ANA D19 OFFICE US	rtical depths of all perti sequent reports must b ew interval, a Form 31 i, have been completed .8 Id g, System (19PP1064SE) ALYST SE CORD	inent markers and zones e filed within 30 days 60-4 must be filed once and the operator has	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 07/28/2018 Spud well. 07/28/2018 TD 17-1/2" surface 07/29/2018 RIH w/ 13-3/8", J-4 ppg, 1.35 yld. No cmt returns. 07/30/2018 Tag TOC @ 196' d Class C. Circ 42 sx to surface 07/31/2018 Test csg to 1500 p 08/02/2018 TD 12-1/4" hole @ 08/03/2018 Mix & pump lead: 1.348 yld. Circ 487 sx to surface 08/04/2018 Test csg again to 08/11/2018 TD vertical hole @ 14. I hereby certify that the foregoing is Corr Name (<i>Printed/Typed</i>) FATIMA V Signature (Electronic S Approved By Conditions of approval, if any, are attached	rk will be performed or provide operations. If the operation re- bandonment Notices must be fil- inal inspection. e hole @ 461'. 55, 48#, ST&C csg & set . WOC 8 hrs. & notify BLM. RIH w/ 1" a e. WOC 13 hrs. bis for 30 mins. OK. 2630'. RIH w/ 9-5/8", J- 800 sx Class C, 13.7 pp ace. WOC 13 hrs. Test of 2400 psi for 30 min, good 2400 psi for 30 min, good 10,255'. true and correct. Electronic Submission # For CIMAREX mitted to AFMSS for proc (ASQUEZ Submission) THIS SPACE FO	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco- led only after all requirements, includi @ 461'. Mix & pump: 825 sx and mix & pump: 266 sx, 14.8 -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -55, 36#, LTC csg & set @ 261 g, 1.67 yld; tail w/ 325 sx Class -56, 26, 26 g, 1.67 yld; tail w/ 325 sx Class -56, 26 g, 1.67 yld; tail w/ 325 sx Class -57, 27 g, 1.67 yld; tail w/ 325	red and true ver Required sub mpletion in a m ing reclamation Class C, 14. ppg, 1.33 yl 8'. s C, 14.8 ppg I Information carlsbad 02/14/2019 (ATORY ANA D19 DFFICE US FUK RE	rtical depths of all perti sequent reports must b ew interval, a Form 31 i, have been completed .8 Id g, System (19PP1064SE) ALYST SE CORD /s/ Jonath	Inent markers and zones e filed within 30 days 60-4 must be filed once and the operator has Date Date	

.

Additional data for EC transaction #454356 that would not fit on the form

32. Additional remarks, continued

08/13/2018 TD 8-3/4" int hole @ 10,920'. 08/14/2018 RIH w/ 7", L-80, 32#, BT&C csg, set @ 9338'-10,920'. RIH w/ 7", RYS-110, 32#, BTC csg & set @ 9338'. 08/15/2018 Mix & pump lead: 725 sx Class C, 10.5 ppg, 3.449 yld; tail w/ 250 sx Class H, 15.6 pg, 1.195 yld. Circ 278 sx cmt to surface. WOC 4 hrs. 08/16/2018 Test csg to 2500 psi for 30 mins. Good test. 9/19/2018 Landed 6" curve @ 11,820'. 10/11/2018 TD 6" prod hole @ 21,947'. 10/13/2018 RIH w/ 4-1/2", HCP-110, 13.5#, BT&C liner & set @ 9209'-21,947'. 10/14/2018 Rix & pump: 870 sx Class C, 14.5 ppg, 1.223 yld. 10/17/2018 Rig release.