Form 3160-5 ~~. (June 2015) DE	UNITED STATES	AND ADDRESS OF		CC OMB Expires:	M APPROVED NO. 1004-0137 January 31, 2018								
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on page 2				 Lease Serial No. NMLC060325 If Indian, Allottee or Tribe Name If Unit or CA/Agreement, Name and/or No. NMNM135686X 									
							1. Type of Well				8. Well Name and No. THUNDERBIRD A 5H		
							2. Name of Operator Contact: SORINA FLORES APACHE CORPORATION E-Mail: sorina.flores@apachecorp.com				9. API Well No. 30-015-44436-00-X1		
3a. Address 303 VETERANS AIRPARK LA MIDLAND, TX 79705	No. (include area code) 818-1167		10. Field and Pool or Exploratory Area LOCO HILLS-GLORIETA-YESO										
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, State									
Sec 33 T16S R30E SWNE 2315FNL 1955FEL 32.878929 N Lat, 103.974731 W Lon				EDDY COUNTY, NM									
12. CHECK THE AI	PPROPRIATE BOX(ES) TO INDIC	CATE NATURE O	F NOTICE, RE	PORT, OR OT	THER DATA								
TYPE OF SUBMISSION		FACTION											
 Notice of Intent Subsequent Report 	Alter Casing Alter Casing Casing Repair	Deepen Hydraulic Fracturing New Construction	 Reclamation Recomplete 	lete S Other Drilling Operations									
Final Abandonment Notice		'lug and Abandon 'lug Back	Temporarily Water Disponent										
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved	eration: Clearly state all pertinent details, inc ally or recomplete horizontally, give subsurf rk will be performed or provide the Bond Nc I operations. If the operation results in a mul pandomnent Notices must be filed only after inal inspection.	ace locations and measu b. on file with BLM/BIA tiple completion or reco	red and true vertical Required subseques moletion in a new i	l depths of all per uent reports must interval, a Form 3	tinent markers and zones. be filed within 30 days 160-4 must be filed once								
BLM-CO-1463 NMB-000736		. RECEIVED											
7/19/18: MIRU, test 9-5/8" csg													
7/20-7/22/18: Drlg cmt to 4050 to btm, drlg 8-1/2" f/4050-4075	0', TOH, repair ST-80 and pipe wran 5', TOH, LD sidetrack assbly, PU cu	gler, LDDC, PU sid rve assbly, TIH.	letrack BHA, wa	ish (OCT	1 2 2018								
7/23/18: Slide/rotate drill curve BHA, TIH.	e f/4075-4916'(landing point), C&C,	TOH, LD curve BH/	A, PU lateral	DISTRICT II	-ARTESIA O.C.D.								
	Electronic Submission #436306 ver For APACHE CORPOR nmitted to AFMSS for processing by F	ATION, sent to the (PRISCILLA PEREZ of	Carlsbad n 09/20/2018 (18F	PP2714SE)									
Name (Printed/Typed) SORINA	LURES		TTING CONTAC										
Signature (Electronic S	Submission)	Date 09/20/2	018										
	THIS SPACE FOR FEDE	·····											
Approved By		ACCEPTEL) FUR REU		Date								
Conditions of approval, if any, are attache certify that the applicant holds legal or equivicity which would entitle the applicant to condu	or e Office SEP	2 1 2018	/s/ Jo	onathon Shepard									
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent (Instructions on page 2)	U.S.C. Section 1212, make it a crime for an statements or representations as to any matter	r within its jurisdiction.	willfully to make to AND MANAGEM	IENT	or agency of the United								

** BLM REVISED **

.

Thunderbird Development Uni 5H (sundry2 cont)

7/24-7/27/18: TIH, drlg 8-1/2" lateral f/4916-12285'(TD), C&C, pmp slug, TOH.

7/28/18: TOH, LD Lateral BHA, PU packers plus reaming assbly, TIH, W&R.

7/29/18: W&R w/8-1/2" reaming assbly f/11500-12285', C&C, TOH to 4020' (KOP), TIH to 12285', C&C, spot starch pill, TOH to 11110'.

7/30/18: TOH, LDDP f/12285-1500', TIH w/DP, slip and cut DL, TOOH, LDDP to 48', LD packers plus reaming assbly, RU CRT & byrd csg.

7/31/18: Wait on weather, Run 7" 29# HCL80 LTC f/surf- 3980, Stage tool @ 4022', MJ @ 4025', 7" XO @ 4048', 5-1/2" 20# HCL80 LTC w/packers plus open hole completion f/4050-12280', RU Par 5

8/1/18: Cmt w/LEAD: 400sx Poz Cl C w/5% salt, 6% bentonite, 0.2% retarder, 0.4#/sk defoamer (2.03yld, 12.6ppg) TAIL: 210sx TXL w/1.3% salt, 5% expanding agent, 0.5% fluid loss, 0.1% anti-settling agent, 0.4#/sk defoamer (1.48yld, 13.0ppg) Circ 232sx to surf, ND BOP, RR 8/1/18.