Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
District I - (575) 393-6161	pergy, Millerals and Natural Resources	Revised July 18, 2013
1023 14. 116.001 151., 110003, 14141 002 10		WELL API NO.
	OIL CONSERVATION DIVISION	30-015-23291
District III – (505) 334-6178	2019 220 South St. Francis Dr.	5. Indicate Type of Lease STATE
1000 Rio Brazos Rd., Aztec, NM 8/410	Santa Fe, NM 87505	STATE FEE 6. State Oil & Gas Lease No.
District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa FDISTRICT II-ARTI 87505		OG 783
SUNDRY NOTICES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		Greasewood BD State
PROPOSALS.)		8. Well Number
1. Type of Well: Oil Well Gas We	ell 🗌 Other P&A	8
2. Name of Operator		9. OGRID Number
EOG Resources, Inc.		7377
3. Address of Operator		10. Pool name or Wildcat
104 South Fourth Street, Artesia, NM 88210		Penasco Draw Yeso, SA
4. Well Location		
Unit Letter E: 2310	feet from the North line and	990 feet from the West line
Section 5	Township 19S Range 25E	NMPM Eddy County
	levation (Show whether DR, RKB, RT, GR, etc.	
3603' GR		
12. Check Approp	riate Box to Indicate Nature of Notice	. Report or Other Data
NOTICE OF INTENT	,	BSEQUENT REPORT OF:
	S AND ABANDON 🔲 📗 REMEDIAL WOF	
TEMPORARILY ABANDON 🔲 CHAN		RILLING OPNS. P AND A
PULL OR ALTER CASING MULT	TIPLE COMPL 🔲 CASING/CEMEN	NT JOB 🔲
DOWNHOLE COMMINGLE		
CLOSED-LOOP SYSTEM	_	_
OTHER:	☐ OTHER:	
		nd give pertinent dates, including estimated date
	EE RULE 19.15.7.14 NMAC. For Multiple Co	ompletions: Attach wellbore diagram of
proposed completion or recompleti	on.	
5/16/10 Pulled all production equipment of	ut of hole. NUBOP. Set 4.5" CIBP @ 2463'. I	Dumned 3 cv Class "C" Cement from CIRD
2420'. EOT @ 2400' circulated 4.5" CSG to surface with 40 bbls plugging mud. CSG did not test. Holes in CSG at ground level. EOT @ 1930' pumped 25 sx Class "C" Cement displaced with 5 ½ bbls plugging mud to Calc. 1568'.		
5/17/19 – Tagged TOC @ 1565'. Cut of wellhead from 7" CSG 3" below ground level. Cement to surface. Approval from		
Gilbert/NMOCD not to perforate 4.5" CSG below surface shoe. EOT @ 1006'. Pumped and circulated 70 sx Class "C" Cement to		
surface.	bolow surface shoe. Bol (a) 1000 . I uniped a	and enfoliated 70 5% class C Centent to
	hole marker. Cut off anchors and cleaned loca	ation. WELL IS PLUGGED AND
A D A NIDONIE D		
Approved for plugging of well bore only. Liability under bond is retained pending receipt		
of C-103 (Subsequent Report of Well Plugsing)		
	which may be found at OCD Web Page under	
	Forms, www.cmnrd.state.nm.us/ocd.	•
Spud Date:	Rig Release Date:	
<u> </u>		
I hereby certify that the information above is	s true and complete to the best of my knowled	ge and belief.
	<i>フ</i>	
SIGNATURE 2111	TITLE Regulatory Specialis	+ DATE May 21 2010
SIGNATURE	TITLE Regulatory Specialis	t DATE <u>May 31, 2019</u>
Type or print name Jeremy Haass	E-mail address: jeremy haass@eog	gresources.com PHONE: <u>575-748-4311</u>
For State Use Only	2 man add 000. <u> 1010111 1114405 (4700)</u>	
20. 2mil 000 0mj	= $1N$. 1 /
APPROVED BY:	TITLE STAH MI	DATE 6/4/19
Conditions of Approval (if any):		