Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					5. Lease Serial No. NMNM117120 6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No.	
Type of Well					8. Well Name and No. ZACH MCCORMICK FED 121H	
Name of Operator Contact: TAMMY R LINK MATADOR PRODUCTION COMPANYE-Mail: tlink@matadorresources.com					9. API Well No. 30-015-44244	
3a. Address 5400 LBJ FREEWAY, SUITE DALLAS, TX 75240	3b. Phone No Ph: 575-62	(include area code) 7-2465		10. Field and Pool or Exploratory Area PIERCE CROSSING; BS		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, State	
Sec 18 T24S R29E Mer NMP NESE 712FNL 321FWL					EDDY COUNTY, NM	
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE OF	F NOTICE,	REPORT, OR OTH	ER DATA
TYPE OF SUBMISSION TYPE OF ACTION						
☐ Notice of Intent	☐ Acidize	Dee	pen	Product	ion (Start/Resume)	☐ Water Shut-Off
Subsequent Report ■	☐ Alter Casing	– <i>'</i>	raulic Fracturing	☐ Reclama		☐ Well Integrity
	Casing Repair	_	Construction	Recomp		☑ Other Drilling Operations
☐ Final Abandonment Notice	☐ Change Plans ☐ Convert to Injection		g and Abandon			ziiiiig speranono
determined that the site is ready for f BLM Bond No. NMB001079 Surety Bond No. RLB0015172 Amended Drilling Sundry 1/25/2018 Spud well, Drill hole 1/27/2018 Pressure test line to plug and displace 730 bbls of 30 bbls cement to surface. Cu 5 minutes. Test Good. NU BO 1/28/2018 RU to Test BOPE 2 test held 10 minutes per BLM	e 17 1/2" f/120' t/515', Ru 2500 psi. Pump 20 bbls o Brine water. Floats held. t conductor and casing. S PE and test per WH BLM !50 psi low x 5000 psi Hig	of FW. 145 bb Got 1 bbl fluid Set 13 5/8" we I. Jh Test annula	Is @ 14.8 ppg, 1 I back. Had good Illhead, weld on a ar 250 psi low x 2	.33 Yield, d I returns and and test 900 2500 psi Hig	rop d 0 psi MAY	CEIVED 172019 ARTESIA O.C.D.
14. I hereby certify that the foregoing is	true and correct. Electronic Submission # For MATADOR PF	464036 verifie	d by the BLM Well OMPANY, sent to	Information the Carlsba	n System ad	
Name (Printed/Typed) TAMMY R LINK			Title PRODUCTION ANALYST			
Signature (Electronic Submission)			Date 05/03/20)19		
	THIS SPACE FO	OR FEDERA	L OR STATE (OFFICE U	SE	
Approved By Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conductive the applicant of conductive the applicant of the states any false, fictitious or fraudulent of the states are states and the states are states and the states are states and the states are states are states are states and the states are states	e subject lease crime for any pe	Office Pendi	ing BLM ar sequently d scanned	pprovals will pe reviewed pe reviewed	agency of the United	
2)	The contract of the contract o	any maner H	1,0) 21.104.01			

Additional data for EC transaction #464036 that would not fit on the form

32. Additional remarks, continued

Good. MU Directional 12 1/4" F/515' t/2,755'.

1/30/2018 9 5/8" 40# J-55, test lines to 3500 psi, pump 30 bbls spacer 225 bbls Lead 713 sxs Class C @ 13.5 ppg, 67 Tail cement 285 sxs Class C @ 14.8 ppg. Pump plug @ 18:30 hrs held pressure 5 minutes. Floats held. Had good returns, got back 95 bbls to surface.

1/31/2018 MU 8 3/4" f/106' t/2610'. Internal test 9 5/8" casing to 2765 psi for 30 minutes drill f/2656' t/7,801'.

2/3/2018 Drill 8 3/4" hole f/7801' t/13,162'.

2/8/2018 Rig in hole w/242 joints of 5 1/2" 20#, P-110 f/1,886' t/13,162', test lines to 6,000 psi pump 20 bbls fresh water spacer. Pump 304 bbls f w/Lead 11.5 ppg, 389 bbls Tail @ 13.2 ppg.

2/9/2018 Cement 5 1/2" production casing, pump 40 bbls mud push spacer, Lead Cement Class H 304 bbls (722 sxs) @ 11.5 ppg, 2.21 YP 1.35. FCP 1570 psi plug bumped @ 2550 psi. Floats held. Bled Back 2 1/2 bbls, good returns. TOC 1500'. Cement Casing and I/d same. Set wellhead and test to 5000 psi for 30 minutes. Good test. Release Rig.