

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department 2.5 2019

Submit Original to Appropriate District Office

Oil Conservation Division DISTRICT/I-ARTESIAO.C.D. 1220 South St. Francis Dr. Santa Fe, NM 87505

Santa 1 6, 1441 67505									
Date:	8-30-18		GAS CA	PTURE PL	AN				
☑ Orig	ginal ended - Reason for .	Amendment:_		Operator & OGRID No.: <u>Mewbourne Oil Company - 14744</u>					
new con	mpletion (new drill,	recomplete to	o new zone, re-fra	ac) activity.		-	facility flaring/venting 4 of 19.15.18.12 NMAC).	for	
Th	11(a) 41a 44:11 1a a 1a a		- 4	1	41 4-1.1 . 11	ı.			
	ll(s) that will be loce the loce of the lo	API	Well Location	Footages	Expected	ow. Flared or	Comments		
"	ch ivallic	Au	(ULSTR)	Toolages	MCF/D	Vented	Comments		
Stir	nger 6 W0IL Fed Com #1H	L- 5-T23S-R27E	1365' FSL & 240' FWL		0	NA	ONLINE AFTER FRAC		
							•.		

Gathering System and Pipeline Notification

Vell(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in
lace. The gas produced from production facility is dedicated to western and will be connected to
Western low/high pressure gathering system located in EDDY County, New Mexico. It will require
' of pipeline to connect the facility to low/high pressure gathering system. Mewbourne Oil Company provides
periodically) to western a drilling, completion and estimated first production date for wells that are scheduled to
e drilled in the foreseeable future. In addition, Mewbourne Oil Company and Western have periodic
onference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at
Western Processing Plant located in Sec. 36 , Blk. 58 T1S , Culberson County, Texas. The actual flow
f the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on ___westerp.___ system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

