

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB NO. 1004-0137  
Expires: January 31, 2018

**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*

5. Lease Serial No.  
NMNM123925  
6. If Indian, Allottee or Tribe Name  
Operator Conv

**SUBMIT IN TRIPLICATE - Other instructions on page 2**

7. If Unit or CA/Agreement, Name and/or No.

1. Type of Well  
 Oil Well  Gas Well  Other

8. Well Name and No.  
HAMBONE FEDERAL COM 25H

2. Name of Operator  
COG OPERATING LLC  
Contact: MAYTE X REYES  
E-Mail: mreyes1@concho.com

9. API Well No.  
30-015-45581

3a. Address  
2208 WEST MAIN STREET  
ARTESIA, NM 88210

3b. Phone No. (include area code)  
Ph: 575-748-6945

10. Field and Pool or Exploratory Area  
PURPLE SASE; WOLFCAMP GAS

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
Sec 8 T26S R29E SESW 330FSL 2410FWL

11. County or Parish, State  
EDDY COUNTY, NM

**12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Change to Original A PD
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

RECEIVED

COG Operating LLC, respectfully requests approval for the following changes to the originally approved APD.

JUN 27 2019

Surface:  
Drill 26? hole to 400? above the salt ? will stop drilling if we encounter salt prior to 400?  
Set 20? 106.5# K-55 BTC casing @ 400?  
Cement in one stage to surface:  
Lead: 450 sx of Class C + 6% gel (13.5 ppg / 1.75 cuft/ sx)  
Tail: 350 sx of Class C + 1% CaCl2 (14.8 ppg/ 1.36 cuft/sx)

SEE ATTACHED FOR  
DISTRICT II-ARTESIA O.C.D.  
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #451694 verified by the BLM Well Information System  
For COG OPERATING LLC, sent to the Carlsbad  
Committed to AFMSS for processing by PRISCILLA PEREZ on 01/30/2019 ()

Name (Printed/Typed) MAYTE X REYES Title REGULATORY ANALYST

Signature (Electronic Submission) Date 01/24/2019

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved By Mustafa Hageel Title Petroleum Engineer Date 02-7-2019  
Carlsbad Field Office  
Office

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**\*\* OPERATOR-SUBMITTED \*\* OPERATOR-SUBMITTED \*\* OPERATOR-SUBMITTED \*\***

RWP 7-5-19

**Additional data for EC transaction #451694 that would not fit on the form**

**32. Additional remarks, continued**

Intermediate 1:

2M BOP System

Drill 17.5? hole to 2800?

Set 13.375? 61# J-55 BTC casing to 2200?

13.375? 72# L-80 BTC casing @ 2800?

Cement in single stage to surface:

Lead: 1400 sx of Class C (12.7 ppg / 1.98 cuft/ sx)

Tail: 400 sx of Class C (14.8 ppg/ 1.36 cuft/sx)

Intermediate 2

3M BOP System

Drill 12.25? hole to 10100?

Set 9.625? 47# HCL-80 BTC @ 10100?

Cement in one stage

Lead: 1200 sx of Halliburton TunedLight Blend (10.3 ppg / 3.48 cuft/ sx)

Tail: 300 sx of Class H (16.4 ppg / 1.08 cuft/sx)

Production

5M BOP System

Drill 8.5? hole to 20984?

Set 5.5? 23# P110 BTC @ 20894?

Cement in one stage to surface

Lead: 1100 sx of 35:36:6 Class C (12.7 ppg / 1.98 cuft/ sx)

Tail: 2600 sx of Halliburton VersaCem Class H Blend ( 14.4 ppg / 1251 cuft/sx)

Flex Hose attached.



# Hydrostatic Test Certificate

ContiTech

Certificate Number 4000	COM Order Reference 974000	Customer Name & Address Nabors Lux Finance 2 S.a.r.L. 8-10 Avenue de la Gare L-1610 LUXEMBOURG
Customer Purchase Order No: 13999606	Project:	
Test Center/Address ContiTech Oil & Marine Corp. 11535 Brittnoore Park Drive Houston, TX 77041 USA	Accepted by COM Inspection Signed: Roger Suarez Date: 6/27/17	Accepted by Client Inspection

We certify that the goods detailed hereon have been inspected as described below by our Quality Management System, and to the best of our knowledge are found to conform the requirements of the above referenced purchase order as issued to ContiTech Oil & Marine Corporation.

Item	Part No.	Description	Qty	Serial Number	Work Press	Test Press	Test Time (minutes)
20		RECERTIFICATION - 3" ID 10K Choke & Kill Hose x 35 ft OAL	1	62205	10,000 psi	15,000 psi	60
				Assest # 66-0945			

# Certificate of Conformity



ContiTech

<b>Certificate Number</b> 4000	<b>COM Order Reference</b> 974000	<b>Customer Name &amp; Address</b> Nabors Lux Finance 2 S.a.r.L. 8-10 Avenue de la Gare L-1610 LUXEMBOURG
<b>Customer Purchase Order No:</b> 13999606		
<b>Project:</b>		
<b>Test Center/Address</b> ContiTech Oil & Marine Corp. 11535 Brittmoores Park Drive Houston, TX 77041 USA	<b>Accepted by COM Inspection</b> Signed: Roger Suarez Date: 6/27/17	<b>Accepted by Client Inspection</b>

We certify that the items detailed below meet the requirements of the customer's Purchase Order referenced above, and are in conformance with the specifications given below.

Item	Part No.	Description	Qty	Serial Number	Specifications
------	----------	-------------	-----	---------------	----------------

20	RECERTIFICATION - 3" ID 10K Choke & Kill Hose x 35 ft OAL	1	62205	ContiTech Standard
			Assest # 66-0945	



# Hose Inspection Report

ContiTech Oil & Marine

Customer	Customer Reference #	COM Reference #	COM Inspector	Date of Inspection
Nabors	13999606	974000	A. Jaimes	06/27/2017

<b>Hose Manufacturer</b>	Contitech Rubber Industrial
--------------------------	-----------------------------

<b>Hose Serial #</b>	62205 (66-0945)	<b>Date of Manufacture</b>	12/2011
<b>Hose I.D.</b>	3"	<b>Working Pressure</b>	10000PSI
<b>Hose Type</b>	Choke and Kill	<b>Test Pressure</b>	15000PSI
<b>Manufacturing Standard</b>	API 16C		

**Connections**

<b>End A:</b> 4.1/16" 10Kpsi API Spec 17D Swivel Flange	<b>End B:</b> 4.1/16" 10Kpsi API Spec 17D Swivel Flange
• Dents	• No damage
<b>Material:</b> Carbon Steel	<b>Material:</b> Carbon Steel
<b>Seal Face:</b> BX155	<b>Seal Face:</b> BX155
<b>Length Before Hydro Test:</b> 35'	<b>Length After Hydro test:</b> 35'

**Conclusion:** Hose #62205 passed the external inspection with no notable damage to the hose armor. The flange face on end A did have minor dents but did not affect the test outcome. It is advised that additional care be taken in order to avoid further damage to the flange face. Internal borescope of the hose showed no damage to the liner. Hose #62205 passed the hydrostatic pressure test by holding a pressure of 15,000PSI for 60 minutes. Hose #62205 is suitable for continued service.

**Recommendations:** In general the hose should be inspected on a regular on-going basis. The frequency and degree of the inspection should as a minimum follow these guidelines:

- Visual inspection: Every 3 to 6 months (or during installation/removal)
- Annual: In-situ pressure test (in addition to the 3 to 6 monthly inspections)
- Initial 5 years service: Major inspection
- 2nd Major inspection: Following subsequent 3 year life cycle
- (Detailed description of test regime available upon request, QCP 206-1)

**\*\*NOTE:** There are a number of critical elements in the hose that cannot be thoroughly checked through standard inspection techniques. Away from dissecting the hose body, the best way to evaluate the condition of the hose is through review of the operating conditions recorded during the hose service life, in particular maximums and peak conditions.

<b>External Damage</b>
<b>Pre - Hydro test</b>
End A has minor dents at the edge of the seal face but did not compromise the hydrostatic pressure test. Additional care should be take in order to avoid further damage



Issued By: Alejandro Jaimes  
Date: 6/27/2017

Checked By: Gerson Mejia-Lazo  
Date: 6/27/2017



CONTITECH RUBBER Industrial Kft.	No: QC-DB- 298 / 2017 Page: 8 / 119
-------------------------------------	--

ContiTech

QUALITY CONTROL INSPECTION AND TEST CERTIFICATE		CERT. N°: 682	
PURCHASER: ContiTech Oil & Marine Corp.		P.O. N°: 4500984922	
CONTITECH RUBBER order N°: 987778	HOSE TYPE: 3" ID Choke and Kill Hose		
HOSE SERIAL N°: 73981	NOMINAL / ACTUAL LENGTH: 13,72 m / 13,80 m		
W.P. 69,0 MPa 10000 psi	T.P. 103,5 MPa 15000 psi	Duration: 60 min.	
Pressure test with water at ambient temperature			
See attachment ( 1 page )			
COUPLINGS Type	Serial N°	Quality	Heat N°
3" coupling with 4 1/16" 10K API Swivel Flange end Hub	8077	AISI 4130	A0939Y
	8083	AISI 4130	037184 85913
		AISI 4130	A0939Y
Not Designed For Well Testing		API Spec 16 C 2 <sup>nd</sup> Edition- FSL2	
TAG NO.: 66-1486		Temperature rate: "B"	
All metal parts are flawless			
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.			
STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.			
COUNTRY OF ORIGIN HUNGARY/EU			
Date:  03. October 2017.	Inspector	Quality Control	ContiTech Rubber Industrial Kft. Quality Control Dept.  <i>[Signature]</i> <i>[Signature]</i>

1/1

5,000 sec  
2017/10/02 18:31:10.000  
2017/10/02 20:26:35.000


Sampling Int.  
Start Time  
Stop Time

File Name 020572\_73980,73981.GEV...020583\_73980,73981.GEV  
File Message 73980,73981  
Device Type GX10  
Serial No. S9P606399  
Data Count 1386

Print Group Press-Temp  
Print Range 2017/10/02 18:31:10.000 - 2017/10/02 20:26:35.000  
Comment 1420566335

Data No.	Cursor A	Cursor B	Difference
	604	1324	720
Absolute Time	2017/10/02 19:21:30.000	2017/10/02 20:21:30.000	01:00:00.000
Tag Comment	Value A	Value B	Value B-A
Pressure(bar)	1084.15	1055.97	-8.18
Ambient Temperature(°C)	21.93	21.73	-0.20

*Agnes*  
ContiTech Rubber  
Industri Kft.  
Quality Control Dept.



## PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	COG OPERATING LLC.
LEASE NO.:	NMNM123925
WELL NAME & NO.:	25H-HAMBONE FEDERAL COM
SURFACE HOLE FOOTAGE:	330'/S & 2410'/W
BOTTOM HOLE FOOTAGE:	200'/N & 2310'/W
LOCATION:	Section. 8., T26S., R.29E., NMP
COUNTY:	EDDY County, New Mexico

Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input checked="" type="radio"/> Conventional	<input type="radio"/> Multibowl	
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP

**All previous COAs still apply, except for the following:**

### A. CASING

1. The **20** inch surface casing shall be set at approximately **400** feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
  - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
  - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
  - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

❖ In **Medium Cave/Karst Areas** if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
2. The minimum required fill of cement behind the **13 3/8** inch first intermediate casing is:

- Cement to surface. If cement does not circulate, contact the appropriate BLM office. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst.**
3. The minimum required fill of cement behind the **9 5/8** inch second intermediate casing is:
    - Cement to surface. If cement does not circulate, contact the appropriate BLM office.
  4. The minimum required fill of cement behind the **5 1/2** inch production casing is:
    - Cement should tie-back at least **200** feet into previous casing string. Operator shall provide method of verification.

#### **B. PRESSURE CONTROL**

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).
2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **2000 (2M)** psi.
3. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the **13 3/8** intermediate casing shoe shall be **3000 (3M)** psi.
4. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the **9 5/8** second intermediate casing shoe shall be **5000 (5M)** psi.

**MHH 02072019**

## GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Chaves and Roosevelt Counties

Call the Roswell Field Office, 2909 West Second St., Roswell NM 88201.

During office hours call (575) 627-0272.

After office hours call (575)

Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,

(575) 361-2822

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)

393-3612

### A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.

4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.

- b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
  - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
  - b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time.
  - c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
  - d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.

- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.