

JUL 1 5 2019

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico JUL I Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division District ILARTESIAO.C.D. 1220 South St. Francis Dr.

Santa Fe, NM 87505

GAS CAPTURE PLAN

Date: 02/28/2019

🛛 Original

Operator & OGRID No.: XTO Permian Operating, LEC [260737]

□ Amended - Reason for Amendment:

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15-18.12 NMAC).

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

| Well Name | API | Well Location (ULSTR) | Footages | Expected MCF/D | Flared or Vented | Comments |
|------------------------------------|-------------|--------------------------|-----------------------|-----------------|---------------------|---------------|
| Big Eddy Unit 30E Yoda 102H | | L-14-20S-31E | 1340'FSL & 620'FWL | 2500 MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30E Anakin 102H | | <u>M</u> -14-20S-31E | 1140'FSL & 680'FWL | 2500 MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30E Jedi 102H | | -M-14-20S-31E | 1065'FSL & 465'FWL | 2500 - MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30E Obi- Wan 102H | 1 1 1 | E-14-20S-31E | 1465'FSL & 405'FWL | 2500 MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30E Qui- Gon 102H | | <u>≡M-14-20S-31E</u> | 1065'FSL & 435'FWL | 2500 MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30E Rey 102H | - | <u>-M-14-20S-31E</u> | 1065'FSL & 405'FWL | 2500 MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30E Rey 103H | | M-14-20S-31E | 1265'FSL & 405'FWL | 2500 MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30E Qui- Gon 103H | | M=14-20S-31E | 1140'FSL & 405'FWL | 2500 MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30E Jedi 103H | | M-14-20S-31E | 740'FSL & 405'FWL | 2500 MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30E Anakin 206H | | M-14-20S-31E | 865'FSL & 620'FWL | 2500 MCF/D | Sold | CTB Connected |
| Big Eddy Unit 30W Yoda 109H | | P-15-20S-31E | 740'FSL & 180'FEL | 2500 MCF/D | Sold | CTB Connected |

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to <u>DCP Midstream</u> and will be connected to <u>DCP Midstream</u> low/high pressure gathering system located in Eddy County, New Mexico. It will require 0' of pipeline to connect the facility to low/high pressure gathering system. <u>XTO Permian Operating, LLC.</u> provides (periodically) to <u>DCP Midstream</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <u>XTO Permian Operating, LLC.</u> and <u>DCP Midstream</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <u>DCP Midstream</u> Processing Plant located in Sec._19_, Twn._19S_, Rng._32E_, Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>DCP Midstream</u> system at that time. Based on current information, it is <u>XTO Permian Operating, LLC</u>'s belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

...

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- -• Compressed Natural Gas On lease
 - - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines
