

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department 5 2019

MCF/D

2500

MCF/D

Vented

CTB Connected

Sold

Submit Original to Appropriate District Office

Oil Conservation Division
1220 South St. Francis DDISTRICTII-ARTESIAO.C.D.
Santa Fe, NM 87505

GAS	CAPT	URE	PLA	N

Date: 01/30/2019		<i>:</i>				
□ Original		Operator	& OGRID 1	No.: <u>XTO Pe</u>	rmian Operat	ing, LLC [260737]
☐ Amended - Reaso	n for Amendment	·			-	
					•	
new completion (new	drill, recomplete	to new zone, re-fra	ac) activity.		-	facility flaring/venting for a for a facility flaring f
Well(s)/Production	Facility – Name o	of facility				
The well(s) that will	be located at the p	roduction facility a	re shown in	the table bel	ow.	•
Well Name	API	Well Location	Footages	Expected	Flared or	Comments

Gathering System and Pipeline Notification

30E

Unit

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to DCP Midstream and will be connected to DCP Midstream and will be connected to DCP Midstream and will require 0' of pipeline to connect the facility to low/high pressure gathering system. XTO Permian Operating, LLC. provides (periodically) to DCP Midstream a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, XTO Permian Operating, LLC, and DCP Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at DCP Midstream Processing Plant located in Sec. 19, Rng. 32E, Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

1540'FSL &

435'FWL

Flowback Strategy

Eddy

Skywalker 101H

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>DCP Midstream</u> system at that time. Based on current information, it is <u>XTO Permian Operating, LLC</u>'s belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

(ULSTR)

L-14-20S-31E

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines