

STRYKER

DIRECTIONAL

RECEIVED

JUL 19 2019

DISTRICT II-ARTESIA O.C.D.

March 14, 2019

New Mexico Energy, Minerals and Natural Resources Department
Attn: Oil Conservation Division
1220 South St. Francis Drive
Santa Fe, NM 87505


Attn: Jackie Lathan

Re: Mewbourne Oil Company
Sapphire 11 12 B3MN State Com #2H
Turkey Track – Bone Spring
Eddy County, New Mexico
API# 30-015-45560

Enclosed please find the original and one (1) copy of the survey performed on the reference well by STRYKER ENERGY DIRECTIONAL SERVICES, L.L.C. Other information required by your office is as follows:

<u>Name & Title</u>	<u>Drainhole No.</u>	<u>Survey Depths</u>	<u>Dates Performed</u>	<u>Type Survey</u>
Victor Anguiano	Original Hole	100ft. to 16,560ft.	01-16-19 to 02-05-19	MWD Survey

A certified plat on which the bottom-hole location is oriented to both surface location and to the lease lines (or unit lines in case of pooling) is attached to the survey report. If any other information is required, please contact the undersigned at the letterhead address and phone number.


Eric Estes

Enclosures

CC:

Mewbourne Oil Company
Attn: Frosty Lathan
P.O. Box 5720
Hobbs, NM 88241

Mewbourne Oil Company
Attn: Robin Terrell
P.O. Box 5720
Hobbs, NM 88241


NMEMaNRD\Mewbourne Oil Company\Sapphire 11 12 B3MN State Com #2H\M191015

STRYKER ENERGY DIRECTIONAL SERVICES, L.L.C.

P.O. Box 1250

Montgomery, TX 77356

Office (936) 582-7296 * Fax (936)-588-4163



March 14, 2019

Survey Certification Report

STATE OF TEXAS

COUNTY OF Montgomery

I, Eric Estes, certify that I am employed by STRYKER ENERGY DIRECTIONAL SERVICES, L.L.C., and that I did on the day(s) of January 16, 2019, through February 5, 2019 conduct or supervise the taking of a SEDS Original Hole MWD Survey from a depth of 100feet to a depth of 16,560feet; that I am authorized and qualified to make this report; that this survey was conducted at the request of Mewbourne Oil Company, for the Sapphire 11-12 B3MN State Com #2H, well API # 30-015-45560 in Eddy County, New Mexico; and that I have reviewed this report and find that it conforms to the principles as set forth by STRYKER ENERGY DIRECTIONAL SERVICES, L.L.C.

A handwritten signature in black ink, appearing to read "Eric V. Estes", is written over a horizontal line.

Eric Estes

STRYKER ENERGY DIRECTIONAL SERVICES, L.L.C.

STRYKER ENERGY DIRECTIONAL SERVICES, L.L.C.

P.O. Box 1250

Montgomery, TX 77356

Office (936) 582-7296 * Fax (936)-588-4163

Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Sapphire 11/12 B3MN St Com 2H
Project:	Eddy County, N.M. Nad (83)	TVD Reference:	3375 + 27 @ 3402.0usft (Patterson 560)
Site:	Section 11/12-19S-29E Sapphire B3MN St Com 2H	MD Reference:	3375 + 27 @ 3402.0usft (Patterson 560)
Well:	Sapphire 11/12 B3MN St Com 2H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Project:		Eddy County, N.M. Nad (83)	
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site:	Section 11/12-19S-29E Sapphire B3MN St Com 2H
--------------	---

Site Position:		Northing:	608,146.60 usft	Latitude:	32° 40' 17.499 N
From:	Map	Easting:	627,547.20 usft	Longitude:	104° 3' 11.398 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.15 °

Well:	Sapphire 11/12 B3MN St Com 2H					
Well Position	+N/-S	0.0 usft	Northing:	608,146.60 usft	Latitude:	32° 40' 17.499 N
	+E/-W	0.0 usft	Easting:	627,547.20 usft	Longitude:	104° 3' 11.398 W
Position Uncertainty		0.0 usft	Wellhead Elevation:	27.0 usft	Ground Level:	3,375.0 usft

Wellbore	Original Hole
-----------------	---------------

Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	01/02/19	7.05	60.38	47,992.82761388

Design	Original Hole
---------------	---------------

Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.0

Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	83.13

Survey Program	Date	From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
	02/05/19	100.0	16,622.0	MWD Survey (Original Hole)	MWD	MWD v3:standard declination

Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Sapphire 11/12 B3MN St Com 2H
Project:	Eddy County, N.M. Nad (83)	TVD Reference:	3375 + 27 @ 3402.0usft (Patterson 560)
Site:	Section 11/12-19S-29E Sapphire B3MN St Com	MD Reference:	3375 + 27 @ 3402.0usft (Patterson 560)
Well:	Sapphire 11/12 B3MN St Com 2H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)
0.0	0.00	0.00	0.0	3,402.0	0.0	0.0	0.0	0.00
100.0	0.49	116.39	100.0	3,302.0	-0.2	0.4	0.4	116.39
200.0	0.67	77.90	200.0	3,202.0	-0.3	1.3	1.4	100.90
300.0	0.78	77.50	300.0	3,102.0	0.0	2.6	2.6	89.73
386.0	0.90	62.49	386.0	3,016.0	0.5	3.7	3.8	83.13
507.0	1.00	64.80	507.0	2,895.0	1.3	5.5	5.7	76.41
627.0	0.90	42.60	626.9	2,775.1	2.5	7.1	7.5	70.82
746.0	1.00	53.50	745.9	2,656.1	3.8	8.6	9.4	66.24
876.0	1.20	65.70	875.9	2,526.1	5.0	10.7	11.9	64.97
1,003.0	1.40	63.60	1,002.9	2,399.1	6.3	13.3	14.7	64.89
1,099.0	1.50	73.10	1,098.8	2,303.2	7.1	15.6	17.2	65.40
1,226.0	0.70	11.70	1,225.8	2,176.2	8.4	17.4	19.3	64.20
1,374.0	0.90	0.60	1,373.8	2,028.2	10.4	17.5	20.4	59.26
1,512.0	2.90	240.70	1,511.7	1,890.3	9.8	14.5	17.5	55.94
1,701.0	3.30	240.90	1,700.5	1,701.5	4.8	5.6	7.4	49.20
1,890.0	5.20	209.00	1,889.0	1,513.0	-5.3	-3.3	6.3	211.98
2,080.0	5.40	207.50	2,078.2	1,323.8	-20.8	-11.6	23.8	209.22
2,269.0	4.90	203.00	2,266.4	1,135.6	-36.1	-18.9	40.7	207.61
2,458.0	5.10	201.00	2,454.7	947.3	-51.4	-25.0	57.1	205.99
2,647.0	4.60	203.90	2,643.0	759.0	-66.1	-31.1	73.1	205.20
2,837.0	5.60	213.30	2,832.2	569.8	-80.9	-39.3	89.9	205.92
3,026.0	6.10	209.60	3,020.3	381.7	-97.3	-49.3	109.1	206.88
3,216.0	6.00	210.80	3,209.2	192.8	-114.6	-59.4	129.1	207.40
3,405.0	5.70	212.30	3,397.2	4.8	-131.0	-69.5	148.3	207.93
3,594.0	5.50	212.60	3,585.3	-183.3	-146.6	-79.4	166.7	208.43
3,783.0	5.40	211.10	3,773.5	-371.5	-161.8	-88.8	184.6	208.77
3,972.0	5.00	211.30	3,961.7	-559.7	-176.5	-97.7	201.7	208.97

Company: Mewbourne Oil Company
Project: Eddy County, N.M. Nad (83)
Site: Section 11/12-19S-29E Sapphire B3MN St Com 2
Well: Sapphire 11/12 B3MN St Com 2H
Wellbore: Original Hole
Design: Original Hole

Local Co-ordinate Reference: Well Sapphire 11/12 B3MN St Com 2H
TVD Reference: 3375 + 27 @ 3402.0usft (Patterson 560)
MD Reference: 3375 + 27 @ 3402.0usft (Patterson 560)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: Stryker_EDM

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)
4,161.0	4.50	210.50	4,150.0	-748.0	-189.9	-105.8	217.4	209.11
4,350.0	5.60	205.00	4,338.3	-936.3	-204.7	-113.4	234.0	208.99
4,539.0	5.20	204.50	4,526.5	-1,124.5	-220.8	-120.9	251.7	208.70
4,729.0	4.30	205.90	4,715.8	-1,313.8	-235.0	-127.5	267.4	208.49
4,918.0	5.80	200.80	4,904.1	-1,502.1	-250.3	-134.0	284.0	208.16
5,103.0	5.10	201.00	5,088.2	-1,686.2	-266.8	-140.3	301.4	207.74
5,292.0	5.20	207.10	5,276.5	-1,874.5	-282.2	-147.2	318.3	207.55
5,487.0	4.30	205.90	5,470.8	-2,068.8	-296.7	-154.4	334.5	207.50
5,676.0	4.80	216.30	5,659.2	-2,257.2	-309.4	-162.2	349.4	207.66
5,865.0	6.60	216.90	5,847.3	-2,445.3	-324.5	-173.4	367.9	208.12
6,054.0	5.60	217.80	6,035.2	-2,633.2	-340.5	-185.6	387.7	208.60
6,244.0	4.20	220.60	6,224.5	-2,822.5	-353.1	-195.8	403.7	209.01
6,433.0	6.10	211.80	6,412.7	-3,010.7	-366.9	-205.6	420.5	209.27
6,623.0	4.80	208.80	6,601.9	-3,199.9	-382.4	-214.7	438.6	209.32
6,812.0	5.70	208.90	6,790.1	-3,388.1	-397.5	-223.1	455.9	209.30
7,001.0	4.90	213.40	6,978.3	-3,576.3	-412.5	-232.1	473.3	209.36
7,190.0	3.90	203.90	7,166.7	-3,764.7	-425.1	-239.1	487.8	209.36
7,379.0	5.50	201.70	7,355.1	-3,953.1	-439.4	-245.1	503.1	209.15
7,568.0	6.00	200.20	7,543.1	-4,141.1	-457.1	-251.8	521.9	208.85
7,757.0	5.00	191.70	7,731.2	-4,329.2	-474.4	-256.9	539.5	208.44
7,947.0	4.70	191.90	7,920.6	-4,518.6	-490.2	-260.2	554.9	207.96
8,136.0	3.20	178.30	8,109.1	-4,707.1	-503.0	-261.6	567.0	207.48
8,274.0	1.10	156.90	8,247.0	-4,845.0	-508.1	-261.0	571.2	207.19
8,369.0	0.80	149.70	8,342.0	-4,940.0	-509.5	-260.3	572.1	207.06
8,426.9	0.66	118.37	8,399.9	-4,997.9	-510.0	-259.8	572.4	207.00
B.B. Sapphire 11 12 B3MN St Com 2H								
8,464.0	0.70	96.00	8,437.0	-5,035.0	-510.1	-259.4	572.3	206.95

Company: Mewbourne Oil Company
Project: Eddy County, N.M. Nad (83)
Site: Section 11/12-19S-29E Sapphire B3MN St Com 2
Well: Sapphire 11/12 B3MN St Com 2H
Wellbore: Original Hole
Design: Original Hole

Local Co-ordinate Reference: Well Sapphire 11/12 B3MN St Com 2H
TVD Reference: 3375 + 27 @ 3402.0usft (Patterson 560)
MD Reference: 3375 + 27 @ 3402.0usft (Patterson 560)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: Stryker_EDM

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)
8,496.0	3.10	100.30	8,469.0	-5,067.0	-510.3	-258.3	572.0	206.85
8,527.0	5.90	101.60	8,499.9	-5,097.9	-510.8	-256.0	571.3	206.62
8,559.0	9.60	101.60	8,531.6	-5,129.6	-511.6	-251.7	570.2	206.20
8,590.0	14.00	105.40	8,561.9	-5,159.9	-513.2	-245.6	568.9	205.57
8,622.0	18.00	107.70	8,592.7	-5,190.7	-515.7	-237.1	567.6	204.70
8,653.0	20.80	107.90	8,621.9	-5,219.9	-518.8	-227.3	566.5	203.66
8,685.0	23.90	106.60	8,651.5	-5,249.5	-522.4	-215.7	565.2	202.44
8,732.0	26.70	107.00	8,694.0	-5,292.0	-528.2	-196.5	563.6	200.40
8,764.0	29.90	107.30	8,722.1	-5,320.1	-532.7	-182.0	562.9	198.86
8,795.0	33.90	108.70	8,748.5	-5,346.5	-537.8	-166.4	562.9	197.20
8,827.0	36.90	109.40	8,774.5	-5,372.5	-543.8	-148.9	563.9	195.31
8,858.0	39.40	109.70	8,798.9	-5,396.9	-550.2	-130.9	565.6	193.38
8,890.0	43.00	109.60	8,823.0	-5,421.0	-557.3	-111.0	568.3	191.27
8,921.0	46.70	109.70	8,845.0	-5,443.0	-564.7	-90.4	571.9	189.10
8,953.0	49.80	109.40	8,866.3	-5,464.3	-572.7	-67.9	576.7	186.77
8,984.0	52.60	109.50	8,885.7	-5,483.7	-580.7	-45.2	582.5	184.45
9,016.0	55.60	109.50	8,904.5	-5,502.5	-589.4	-20.7	589.7	182.01
9,016.3	55.63	109.50	8,904.6	-5,502.6	-589.5	-20.5	589.8	181.99
LP Sapphire 11 12 B3MN St Com 2H								
9,048.0	58.50	109.50	8,921.9	-5,519.9	-598.3	4.6	598.3	179.56
9,079.0	61.50	109.40	8,937.4	-5,535.4	-607.3	29.9	608.0	177.18
9,111.0	64.40	108.80	8,951.9	-5,549.9	-616.6	56.8	619.2	174.73
9,142.0	67.30	108.30	8,964.6	-5,562.6	-625.6	83.6	631.2	172.38
9,174.0	70.20	107.40	8,976.2	-5,574.2	-634.7	112.0	644.5	169.99
9,205.0	72.70	106.60	8,986.0	-5,584.0	-643.3	140.1	658.4	167.71
9,237.0	76.10	105.70	8,994.7	-5,592.7	-651.9	169.7	673.6	165.41
9,268.0	79.80	104.00	9,001.1	-5,599.1	-659.7	199.0	689.0	163.21

Company: Mewbourne Oil Company
Project: Eddy County, N.M. Nad (83)
Site: Section 11/12-19S-29E Sapphire B3MN St Com 2
Well: Sapphire 11/12 B3MN St Com 2H
Wellbore: Original Hole
Design: Original Hole

Local Co-ordinate Reference: Well Sapphire 11/12 B3MN St Com 2H
TVD Reference: 3375 + 27 @ 3402.0usft (Patterson 560)
MD Reference: 3375 + 27 @ 3402.0usft (Patterson 560)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: Stryker_EDM

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)
9,302.0	82.80	103.30	9,006.3	-5,604.3	-667.6	231.7	706.6	160.86
9,389.0	88.00	100.90	9,013.2	-5,611.2	-685.7	316.4	755.2	155.23
9,484.0	88.40	102.40	9,016.2	-5,614.2	-704.9	409.4	815.2	149.85
9,579.0	89.10	102.70	9,018.3	-5,616.3	-725.6	502.1	882.4	145.31
9,673.0	88.40	102.30	9,020.3	-5,618.3	-745.9	593.9	953.5	141.47
9,768.0	89.50	101.80	9,022.1	-5,620.1	-765.7	686.8	1,028.6	138.11
9,863.0	89.10	100.00	9,023.3	-5,621.3	-783.7	780.1	1,105.7	135.13
9,957.0	87.10	98.60	9,026.4	-5,624.4	-798.9	872.8	1,183.2	132.47
10,052.0	87.40	98.40	9,030.9	-5,628.9	-812.9	966.6	1,263.0	130.06
10,146.0	86.40	95.70	9,036.0	-5,634.0	-824.4	1,059.8	1,342.7	127.88
10,241.0	86.20	95.00	9,042.1	-5,640.1	-833.3	1,154.1	1,423.5	125.83
10,335.0	86.20	92.90	9,048.4	-5,646.4	-839.7	1,247.7	1,504.0	123.94
10,430.0	86.70	92.10	9,054.3	-5,652.3	-843.9	1,342.4	1,585.6	122.15
10,525.0	86.40	92.80	9,060.0	-5,658.0	-847.9	1,437.2	1,668.7	120.54
10,619.0	87.80	90.00	9,064.7	-5,662.7	-850.2	1,531.0	1,751.2	119.04
10,714.0	88.60	89.80	9,067.7	-5,665.7	-850.0	1,626.0	1,834.8	117.60
10,808.0	89.20	90.20	9,069.5	-5,667.5	-850.0	1,720.0	1,918.5	116.30
10,903.0	89.80	91.00	9,070.3	-5,668.3	-851.0	1,814.9	2,004.6	115.12
10,997.0	88.70	89.00	9,071.6	-5,669.6	-851.0	1,908.9	2,090.0	114.03
11,092.0	89.20	89.30	9,073.3	-5,671.3	-849.6	2,003.9	2,176.6	112.98
11,186.0	87.60	88.50	9,075.9	-5,673.9	-847.8	2,097.8	2,262.7	112.01
11,281.0	87.40	88.50	9,080.1	-5,678.1	-845.3	2,192.7	2,350.0	111.08
11,376.0	88.30	88.60	9,083.6	-5,681.6	-842.9	2,287.6	2,438.0	110.23
11,470.0	89.50	88.50	9,085.5	-5,683.5	-840.5	2,381.6	2,525.6	109.44
11,565.0	87.50	88.30	9,087.9	-5,685.9	-837.9	2,476.5	2,614.4	108.69
11,660.0	88.20	88.50	9,091.5	-5,689.5	-835.2	2,571.4	2,703.6	107.99
11,755.0	86.30	87.70	9,096.1	-5,694.1	-832.1	2,666.2	2,793.1	107.33

Company: Mewbourne Oil Company
Project: Eddy County, N.M. Nad (83)
Site: Section 11/12-19S-29E Sapphire B3MN St Com 2
Well: Sapphire 11/12 B3MN St Com 2H
Wellbore: Original Hole
Design: Original Hole

Local Co-ordinate Reference: Well Sapphire 11/12 B3MN St Com 2H
TVD Reference: 3375 + 27 @ 3402.0usft (Patterson 560)
MD Reference: 3375 + 27 @ 3402.0usft (Patterson 560)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: Stryker_EDM

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)
11,849.0	86.90	87.70	9,101.6	-5,699.6	-828.3	2,760.0	2,881.6	106.71
11,944.0	86.40	88.50	9,107.2	-5,705.2	-825.2	2,854.8	2,971.6	106.12
12,039.0	87.50	88.30	9,112.2	-5,710.2	-822.5	2,949.6	3,062.1	105.58
12,133.0	88.10	88.10	9,115.9	-5,713.9	-819.6	3,043.5	3,151.9	105.07
12,228.0	88.40	88.50	9,118.8	-5,716.8	-816.8	3,138.4	3,242.9	104.59
12,322.0	88.60	88.30	9,121.2	-5,719.2	-814.2	3,232.3	3,333.3	104.14
12,417.0	89.50	91.00	9,122.8	-5,720.8	-813.6	3,327.3	3,425.3	103.74
12,511.0	89.50	90.90	9,123.6	-5,721.6	-815.1	3,421.3	3,517.0	103.40
12,606.0	90.00	90.90	9,124.0	-5,722.0	-816.6	3,516.3	3,609.9	103.07
12,701.0	87.70	91.40	9,125.9	-5,723.9	-818.5	3,611.2	3,702.8	102.77
12,795.0	87.30	91.50	9,130.0	-5,728.0	-820.9	3,705.1	3,795.0	102.49
12,890.0	86.90	91.30	9,134.8	-5,732.8	-823.2	3,800.0	3,888.1	102.22
12,985.0	86.30	91.10	9,140.5	-5,738.5	-825.2	3,894.8	3,981.2	101.96
13,079.0	88.00	90.60	9,145.1	-5,743.1	-826.6	3,988.6	4,073.4	101.71
13,173.0	87.90	90.90	9,148.5	-5,746.5	-827.8	4,082.6	4,165.7	101.46
13,268.0	89.50	90.60	9,150.7	-5,748.7	-829.1	4,177.5	4,259.0	101.23
13,362.0	90.70	91.30	9,150.5	-5,748.5	-830.6	4,271.5	4,351.5	101.00
13,457.0	91.60	91.70	9,148.6	-5,746.6	-833.1	4,366.5	4,445.2	100.80
13,551.0	87.00	90.10	9,149.7	-5,747.7	-834.6	4,460.4	4,537.8	100.60
13,646.0	87.40	91.10	9,154.4	-5,752.4	-835.6	4,555.3	4,631.3	100.39
13,741.0	89.00	92.10	9,157.4	-5,755.4	-838.2	4,650.2	4,725.2	100.22
13,835.0	91.90	92.70	9,156.6	-5,754.6	-842.2	4,744.1	4,818.3	100.07
13,930.0	93.00	92.70	9,152.6	-5,750.6	-846.6	4,838.9	4,912.4	99.92
14,024.0	91.60	92.10	9,148.8	-5,746.8	-850.6	4,932.8	5,005.6	99.78
14,119.0	87.70	91.60	9,149.4	-5,747.4	-853.6	5,027.7	5,099.6	99.64
14,214.0	87.80	91.20	9,153.1	-5,751.1	-856.0	5,122.6	5,193.6	99.49
14,308.0	87.30	91.40	9,157.1	-5,755.1	-858.1	5,216.5	5,286.6	99.34

Company:	Mewbourne Oil Company	Local Co-ordinate Reference:	Well Sapphire 11/12 B3MN St Com 2H
Project:	Eddy County, N.M. Nad (83)	TVD Reference:	3375 + 27 @ 3402.0usft (Patterson 560)
Site:	Section 11/12-19S-29E Sapphire B3MN St Com 2	MD Reference:	3375 + 27 @ 3402.0usft (Patterson 560)
Well:	Sapphire 11/12 B3MN St Com 2H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	Original Hole	Database:	Stryker_EDM

Survey									
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	
14,402.0	89.70	90.70	9,159.6	-5,757.6	-859.8	5,310.4	5,379.6	99.20	
14,497.0	89.90	90.60	9,159.9	-5,757.9	-860.9	5,405.4	5,473.5	99.05	
14,592.0	88.60	89.80	9,161.2	-5,759.2	-861.2	5,500.4	5,567.4	98.90	
14,686.0	85.50	89.50	9,166.0	-5,764.0	-860.7	5,594.3	5,660.1	98.75	
14,781.0	87.20	89.70	9,172.0	-5,770.0	-860.0	5,689.1	5,753.7	98.60	
14,875.0	90.70	90.60	9,173.8	-5,771.8	-860.2	5,783.0	5,846.7	98.46	
14,970.0	93.30	90.00	9,170.4	-5,768.4	-860.7	5,878.0	5,940.7	98.33	
15,065.0	92.10	91.30	9,166.0	-5,764.0	-861.8	5,972.9	6,034.7	98.21	
15,159.0	93.00	91.40	9,161.8	-5,759.8	-864.0	6,066.7	6,128.0	98.11	
15,254.0	89.30	92.10	9,159.9	-5,757.9	-866.9	6,161.7	6,222.3	98.01	
15,348.0	87.60	91.10	9,162.4	-5,760.4	-869.5	6,255.6	6,315.7	97.91	
15,442.0	86.00	91.20	9,167.7	-5,765.7	-871.4	6,349.4	6,408.9	97.81	
15,537.0	86.30	90.90	9,174.1	-5,772.1	-873.2	6,444.2	6,503.1	97.72	
15,631.0	87.90	91.20	9,178.8	-5,776.8	-874.9	6,538.0	6,596.3	97.62	
15,726.0	88.40	91.40	9,181.9	-5,779.9	-877.0	6,633.0	6,690.7	97.53	
15,821.0	91.00	91.60	9,182.4	-5,780.4	-879.5	6,727.9	6,785.2	97.45	
15,915.0	89.50	92.50	9,182.0	-5,780.0	-882.9	6,821.9	6,878.8	97.37	
16,010.0	90.40	93.10	9,182.0	-5,780.0	-887.5	6,916.7	6,973.5	97.31	
16,104.0	88.10	92.10	9,183.3	-5,781.3	-891.8	7,010.6	7,067.1	97.25	
16,199.0	88.20	92.80	9,186.3	-5,784.3	-895.9	7,105.5	7,161.7	97.19	
16,293.0	88.80	92.90	9,188.8	-5,786.8	-900.5	7,199.3	7,255.4	97.13	
16,388.0	85.30	92.50	9,193.7	-5,791.7	-905.0	7,294.1	7,350.0	97.07	
16,482.0	83.90	92.80	9,202.5	-5,800.5	-909.3	7,387.6	7,443.3	97.02	
16,560.0	82.90	93.60	9,211.5	-5,809.5	-913.6	7,464.9	7,520.6	96.98	
16,622.0	82.90	93.60	9,219.2	-5,817.2	-917.5	7,526.3	7,582.1	96.95	

16622.0' MD Projected to Bit - PBHL Sapphire 11 12 B3MN St Com #2H