State Of New Metcloo		
3. First St. Artesia, NM 88210       OIL CONSERVATION DIVISION       5. Indicate Type         3. First St. Artesia, NM 88210       Santa Fe, NM 87505       5. Indicate Type         9. Kin Brook Rd, Artes, NM 87707       Santa Fe, NM 87505       6. State Gill & Gilll & Gill & Gi	Revised July 18, 2013	
3. First St. Artesia, NM 88210       OIL CONSERVATION DIVISION       5. Indicate Type         3. First St. Artesia, NM 88210       Santa Fe, NM 87505       5. Indicate Type         9. Kin Brook Rd, Artes, NM 87707       Santa Fe, NM 87505       6. State Gill & Gilll & Gill & Gi		
action = 1003 issue (1) acts       MUL 2 3 2019 1220 South St. Francis Dr. Santa Fc, NM 87505       5. Indicate Sympetry State Fc, NM 87505         05       State Francis Dr., Surgering TH ARTESIAOCD.       6. State Oil & G         05       SUNDRY NOTICES AND REPORTS ON WELLS JACKNOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR FLUG BACK TO A TERRIT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH OF SOUTH STREET, Artesia, NM 8210       7. Lease Name of Jackson PI         Name of Operator       9. OGRID Numit GR Resources, Inc.       9. OGRID Numit 7377         Address of Operator       9. OGRID Numit GR Resources, Inc.       7. Township         10. It Lease Name of South Fourth Street, Artesia, NM 88210       10. Pool name on Atoka; Glorieta*         Well Location       11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3318' GR       330         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other NOTICE OF INTENTION TO: REFORM REMEDIAL WORK       SUBSEQUENT RE REMEDIAL WORK       CASING/CEMENT JOB         13. Describe proposed or completed operations.       (Clearly state all pertinent datails, and give pertinent dat of starting any proposed or completion.       OTHER:         (19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C" Completion or recompletion.       Completion free Start Sta		
Ball Color       (30) 410-360       0. Star France Dr., Sar District 1/4 AFRESIAOCCD.         05       SUNDRY NOTICES AND REPORTS ON WELLS       7. Lease Name of Jackson P1         05       SUNDRY NOTICES AND REPORTS ON WELLS       7. Lease Name of Jackson P1         1       Type of Well: Oil Well    Gas Well    Other P&A       1         1       Resources, Inc.       777         Address of Operator       9. OGRID Number         4 South Fourth Street, Artesia, NM 88210       10. Pool name of Atoka; Glorieta-Y         Well Location       11. Elevation (Show whether DR, RKB, RT, GR, etc.)         3318' GR       11. Elevation (Show whether DR, RKB, RT, GR, etc.)         3318' GR       11. Elevation (Show whether DR, RKB, RT, GR, etc.)         11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other       NOTICE OF INTENTION TO:         RFORM REMEDIAL WORK    PLUG AND ABANDON          CASING/CEMENT JOB            MPORARLY ABANDON          CHANGE PLANS          CASING/CEMENT JOB            UL OR ALTER CASING          MULTIPLE COMPL          CASING/CEMENT JOB            13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent data of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach or proposed completion or recompletion.		
Ball Color       (30) 410-360       0. Star France Dr., Sar District 1/4 AFRESIAOCCD.         05       SUNDRY NOTICES AND REPORTS ON WELLS       7. Lease Name of Jackson P1         05       SUNDRY NOTICES AND REPORTS ON WELLS       7. Lease Name of Jackson P1         1       Type of Well: Oil Well    Gas Well    Other P&A       1         1       Resources, Inc.       777         Address of Operator       9. OGRID Number         4 South Fourth Street, Artesia, NM 88210       10. Pool name of Atoka; Glorieta-Y         Well Location       11. Elevation (Show whether DR, RKB, RT, GR, etc.)         3318' GR       11. Elevation (Show whether DR, RKB, RT, GR, etc.)         3318' GR       11. Elevation (Show whether DR, RKB, RT, GR, etc.)         11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other       NOTICE OF INTENTION TO:         RFORM REMEDIAL WORK    PLUG AND ABANDON          CASING/CEMENT JOB            MPORARLY ABANDON          CHANGE PLANS          CASING/CEMENT JOB            UL OR ALTER CASING          MULTIPLE COMPL          CASING/CEMENT JOB            13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent data of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach or proposed completion or recompletion.	🗌 FEE 🛛	
SUNDRY NOTICES AND REPORTS ON WELLS       7. Lease Name of Jackson P1         NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFEND RY PLUG BACK TO A       Jackson P1         TERRINT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH       8. Well Number         1       Type of Well: Oil Well       Gas Well       Other P&A         Name of Operator       9. OGRID Numl       7.7         Address of Operator       10. Pool name of Address of Operator       10. Pool name of Atoka; Glorieta-N         Well Location       11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR         Section       27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       18S       Range       26E       NMPM       Edd         MCICE OF INTENTION TO:       SUBSEQUENT RE       SUBSEQUENT RE       COMMENCE DRILLING OPNS.]       CASING/CEMENT JOB       CASING/CEMENT JOB         MPORARILY ABANDON       CHANGE PLANS       CASING/CEMENT JOB       CASING/CEMENT JOB       CASING/CEMENT JOB         MPOR COMINGLE       OTHER:       OTHER:       OTHER:       CASING/CEMENT JOB       CASING/CEMENT JOB	as Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS NOT USE THIS FORM FOR PROPOSALS TO DRILLOR TO DEEPEN OR PLUG BACK TO A PRENENT RESERVOR. USE 'APPLICATION FOR PERMIT' (FORM C-10) FOR SUCH 2003L3)       7. Lease Name of Jackson P1.         Type of Well: Oil Well       Gas Well       Other P&A       8. Well Number         Jong Status       9. OGRID Numi 7377       10. Pool name of Address of Operator       9. OGRID Numi 7377         4 South Fourth Street, Artesia, NM 88210       10. Pool name of Atoka; Glorieta-Y       10. Pool name of Atoka; Glorieta-Y         Well Location       11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other NOTICE OF INTENTION TO:       SUBSEQUENT RE REMEDIAL WORK         RFORM REMEDIAL WORK       PLUG AND ABANDON       CASING/CEMENT JOB         WWHOLE COMMINGLE       OTHER:       CAMMENCE DRILLING OPNS.         UL OR ALTER CASING       MULTIPLE COMPL       CASING/CEMENT JOB         WNHOLE COMMINGLE       OTHER:       OTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C" ' Cab. (Statewater Repert Well Provide) attach to proposed cric 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes pe		
DNOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A FREMENT RESERVORE. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH       Jackson PI         PRENENT RESERVORE. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH       8. Well Number         Type of Well: Oil Well       Gas Well       Other P&A       1         Name of Operator       9. OGRID Numl       7377         G Resources, Inc.       7377       10. Pool name of Atoka, Glorieta-Y         Well Location       Unit Letter       H       2310       feet from the       North       line and       330       feet from         Section       27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       18S       Range       26E       NMPM       Edd         Mell Location       11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR       GR       GR         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other       NOTICE OF INTENTION TO:       SUBSEQUENT RE       REMEDIAL WORK       COMMENCE DRILLING OPNS         LI OR ALTER CASING       MULTIPLE COMPL       OTHER:       CASING/CEMENT JOB       CASING/CEMENT JOB       GNMENCE DRILLING OPNS         13. Describe proposed or completed operations.       Clearly state all pertinent details, and give	r Unit Agreement Name	
SPOSALS)       8. Well Number         Type of Well: Oil Well       Gas Well Other P&A         Name of Operator       9. OGRID Numi         G Resources, Inc.       7377         Address of Operator       9. OGRID Numi         G Resources, Inc.       7377         Address of Operator       9. OGRID Numi         South Fourth Street, Artesia, NM 88210       Atoka, Glorieta-Y         Well Location       10. Pool name of Atoka, Glorieta-Y         Well Location       27       Township         Stati Fourth Street, Artesia, NM 88210       NPM         Editor       27       Township         Stati Fourth Street, Artesia, NM 88210       NPM         Editor       27       Township         Stati Fourth Street, Artesia, NM 88210       NPM         Editor       27       Township         Stati Fourth Street, Artesia, NM 88210       NPM         Editor       27       Township         Stati Fourth Street, Appropriate Box to Indicate Nature of Notice, Report or Other       NOTICE OF INTENTION TO:         REFORM REMEDIAL WORK       PLUG AND ABANDON       REMEDIAL WORK         LL OR ALTER CASING       MULTIPLE COMPL       COMMENCE DRILLING OPNS.         LL OR ALTER CASING       MULTIPLE COMPL       CASING/CE	3	
Address of Operator       9. OGRID Numi         G Resources, Inc.       7377         Address of Operator       9. OGRID Numi         G Resources, Inc.       10. Pool name of         Address of Operator       10. Pool name of         4 South Fourth Street, Artesia, NM 88210       Atoka; Glorieta-N         Well Location       11. Evolution         Unit Letter       H       2310         feet from the       North       line and       330         Section       27       Township       18S       Range       26E       NMPM       Ede         Sector       NOTICE OF INTENTION TO:       SUBSEQUENT RE       REMEDIAL WORK       CMMENCE DRILLING	· · · · ·	
1) Do Wein       0 das Wein       Description         1) Name of Operator       9. OGRID Numining         G Resources, Inc.       7377         Address of Operator       10. Pool name of Atoka; Glorieta-Network Street, Artesia, NM 88210         Well Location       10. Pool name of Atoka; Glorieta-Network Street, Artesia, NM 88210         Well Location       27         Unit Letter       H         21. Check Appropriate Box to Indicate Nature of Notice, Report or Other         NOTICE OF INTENTION TO:       SUBSEQUENT RE         RFORM REMEDIAL WORK       PLUG AND ABANDON         MPORARLY ABANDON       CHANGE PLANS         LL OR ALTER CASING       MULTIPLE COMPL         OSED-LOOP SYSTEM       COMMENCE DRILLING OPNS.]         HER:       0         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NBONED.         Approved for pluguage of will bene oally.         NBONED.       Approved for pluguage of will bene		
G Resources, Inc.       7377         Address of Operator       10. Pool name of Atoka; Glorieta-N         Well Location       10. Pool name of Atoka; Glorieta-N         Unit Letter       H       2310         feet from the       North       line and       330         Section       27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       18S       Range       26E       NMPM       Edd         11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR       3318' GR       11         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other       NOTICE OF INTENTION TO:       SUBSEQUENT RE         RFORM REMEDIAL WORK       PLUG AND ABANDON       REMEDIAL WORK       COMMENCE DRILLING OPNS.         LL OR ALTER CASING       MULTIPLE COMPL       WWNOLE COMMINGLE       OTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.         /19 - NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"       "Cale.         /19 - NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"       "Cale.		
Address of Operator       10. Pool name of Atoka; Glorieta-         4 South Fourth Street, Artesia, NM 88210       10. Pool name of Atoka; Glorieta-         Well Location       Unit Letter       H       : 2310       feet from the North line and 330       feet from Section         27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       18S       Range       26E       NMPM       Edd         Section       27       Township       11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR         12.       Check Appropriate Box to Indicate Nature of Notice, Report or Other       SUBSEQUENT RE       REMEDIAL WORK       EMEMEDIAL WORK       EMEMEDIAL WORK       EMEMEDIAL WORK       EMEMEDIAL WORK       Commence Dat More Chip       CASING/CEMENT JOB <td< td=""><td>ber</td></td<>	ber	
4 South Fourth Street, Artesia, NM 88210       Atoka; Glorieta-V         Well Location       Unit Letter       H       2310       feet from the       North       line and       330       feet from         Section       27       Township       188       Range       26E       NMPM       Edd         NOTICE OF INTENTION TO:       SUBSEQUENT RE       REMEDIAL WORK       Commence Commence       Commence       Commence       Commence <td></td>		
Well Location       Unit Letter       H       2310       feet from the       North       line and       330       feet from section         Section       27       Township       18S       Range       26E       NMPM       Edd         11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR       11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other       NOTICE OF INTENTION TO:       SUBSEQUENT RE         RFORM REMEDIAL WORK       PLUG AND ABANDON       REMEDIAL WORK       COMMENCE DRILLING OPNS.         LL OR ALTER CASING       MULTIPLE COMPL       CASING/CEMENT JOB         WONHOLE COMMINGLE       OSED-LOOP SYSTEM       OTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach ve proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"       C'' Cale.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ace plug set.       Net Here and to feed and coeff.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.       Appreced for plugalog of well bivero only.         // Lighticry		
Unit Letter       H       :       2310       feet from the       North       line and       330       feet from Section         Section       27       Township       18S       Range       26E       NMPM       Edd         11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR       Image: Comparison of the state of Notice, Report or Other         NOTICE OF INTENTION TO:       SUBSEQUENT RE         RFORM REMEDIAL WORK       PLUG AND ABANDON       Commence Drilling OPNS.         LL OR ALTER CASING       MULTIPLE COMPL       CASING/CEMENT JOB         WNHOLE COMMINGLE       MULTIPLE COMPL       CASING/CEMENT JOB         WNHOLE COMMINGLE       OSED-LOOP SYSTEM       CASING/CEMENT JOB         HER:       0       OTHER:       CASING/CEMENT JOB         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.         /19 – Load & Circ 4.5" CSG to surface with 40 bls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.       NMEL IS PL         NDONED.       Approved for plugaing of woll hore only:	( eso	
Section       27       Township       18S       Range       26E       NMPM       Edd         11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR       11. Elevation (Show whether DR, RKB, RT, GR, etc.)       3318' GR         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other       NOTICE OF INTENTION TO:       SUBSEQUENT RE         RFORM REMEDIAL WORK       PLUG AND ABANDON       CMMENCE DRILLING OPNS.       COMMENCE DRILLING OPNS.         MPORARILY ABANDON       CHANGE PLANS       COMMENCE DRILLING OPNS.       CASING/CEMENT JOB         WNHOLE COMMINGLE       MULTIPLE COMPL       CASING/CEMENT JOB       CASING/CEMENT JOB         WNHOLE COMMINGLE       OTHER:       OTHER:       13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"       Y Cale.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Cale. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL MNDONED.         Approved for plugging of will hore only. Lisation under hord is centained revinding receipt dista		
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3318' GR         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other NOTICE OF INTENTION TO: REFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLUG AND ADANDON CHANGE PLUG AND ABANDON CHANGE PLUG AND ADANDON CHANGE PLUG ADANDON CHA	n the <u>East</u> line	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3318' GR         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other NOTICE OF INTENTION TO: RFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLUG AND ABANDON CHANGE PLUG AND ABANDON CHANGE PLUG AND ABANDON CHANGE PLUS AND ADD ADD ADD ADD ADD ADD ADD ADD ADD	ly County	
3318' GR         12. Check Appropriate Box to Indicate Nature of Notice, Report or Other         NOTICE OF INTENTION TO:         SUBSEQUENT RE         RFORM REMEDIAL WORK       PLUG AND ABANDON         MPORARILY ABANDON       CHANGE PLANS         LL OR ALTER CASING       MULTIPLE COMPL         OKALTER CASING       MULTIPLE COMPL         OSED-LOOP SYSTEM       OTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach vs proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C" 4' Calc.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well bore only.         Labitary under bord at oCD Web Page under Extrangle with a tax be fough at oCD Web Page under Extrangle with and bord is creating pointing receipt of CiVI Subscenart Report of Well Plugaing)         /19 - Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Aprevend for plugging at COD Web Page under Extrangle o		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other         NOTICE OF INTENTION TO:       SUBSEQUENT RE         RFORM REMEDIAL WORK       PLUG AND ABANDON       REMEDIAL WORK       COMMENCE DRILLING OPNS.         MPORARILY ABANDON       CHANGE PLANS       COMMENCE DRILLING OPNS.       COMMENCE DRILLING OPNS.         LL OR ALTER CASING       MULTIPLE COMPL       CASING/CEMENT JOB       OTHER:         13. DEscribe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         Y Calc.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cu off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL (CAU (Storeaust Report of Well Plugal) which mar be found at octal well Plugal) which mar be found at octal well plug under Exercised.         NDONED.       Rig Release Date:       Rig Release Date:		
NOTICE OF INTENTION TO:       SUBSEQUENT RE         RFORM REMEDIAL WORK       PLUG AND ABANDON       REMEDIAL WORK       Remediation       Remediation       Remediation       Remediation       Remediation       Commence of Multiple Completion Commence       Remediation       Remediation <td></td>		
NOTICE OF INTENTION TO:       SUBSEQUENT RE         RFORM REMEDIAL WORK       PLUG AND ABANDON       REMEDIAL WORK       Remediation       Remediation       Remediation       Remediation       Remediation       Commence of Multiple Completion Commence       Remediation       Remediation <td>Data</td>	Data	
RFORM REMEDIAL WORK       PLUG AND ABANDON       REMEDIAL WORK       MPORARILY ABANDON         MPORARILY ABANDON       CHANGE PLANS       COMMENCE DRILLING OPNS.         LL OR ALTER CASING       MULTIPLE COMPL       CASING/CEMENT JOB         WNHOLE COMMINGLE       OSED-LOOP SYSTEM       COTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach w proposed completion or recompletion.         /19 - NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         '2' Calc.         /19 - NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         '4' Calc.         /19 - Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 - Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well bore only.         Liability under bond is recained pending receipt of Call (subsequent Report of Well Plugalog) which mark be topind at OCD Web Page under Forms, www.enartd.state.nm.us/ocd.         Id Date:       Rig Release Date:	Dala	
RFORM REMEDIAL WORK       PLUG AND ABANDON       REMEDIAL WORK       MPORARILY ABANDON         MPORARILY ABANDON       CHANGE PLANS       COMMENCE DRILLING OPNS.         LL OR ALTER CASING       MULTIPLE COMPL       CASING/CEMENT JOB         WNHOLE COMMINGLE       OSED-LOOP SYSTEM       COTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach w proposed completion or recompletion.         /19 - NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         '2' Calc.         /19 - NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         '4' Calc.         /19 - Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 - Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well bore only.         Liability under bond is recained pending receipt of Call (subsequent Report of Well Plugalog) which mark be topind at OCD Web Page under Forms, www.enartd.state.nm.us/ocd.         Id Date:       Rig Release Date:		
MPORARILY ABANDON       CHANGE PLANS       COMMENCE DRILLING OPNS.         LL OR ALTER CASING       MULTIPLE COMPL       CASING/CEMENT JOB         WNHOLE COMMINGLE       OTHER:         OSED-LOOP SYSTEM       OTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         /2 Cale.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Cale. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of woll hore only.         Liability under bond (s retained pending receipt of Well Plugging) which may be found at OCD Web Page under Forms, www.emmid.state.omm.us/ocd.         I Date:       Rig Release Date:	· · · · · · · · · · · · · · · · · · ·	
LL OR ALTER CASING       MULTIPLE COMPL       CASING/CEMENT JOB         OWNHOLE COMMINGLE       OTHER:         OSED-LOOP SYSTEM       OTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         /2 Calc.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well hore only.         Liability under bond (s retained pending receipt of Well Plugging) which may be found in the	P AND A	
DWNHOLE COMMINGLE       OTHER:         OSED-LOOP SYSTEM       OTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach w proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         /2 Calc.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well bore only.         Liability under bond is retained pending receipt of Well Piugging) which may be found at OCD Web Page under Foras, www.churd.state.nm.us/ocd.         1 Date:       Rig Release Date:		
OSED-LOOP SYSTEM       OTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach we proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL MDONED.         Approved for plugging of well hore only.         Lishliter under bond is retained pending receipt of "Cit Subsequent Report of Well Plugging" which may be found at OCD Web Page under Forais, www.emint.state.nm.us/ocd.         I Date:       Rig Release Date:	•	
HER:       OTHER:         13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.         /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C" 4' Calc.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well bore only.         Litblitty under bond (stretating period) which mark be found at OCD Web Page under Fortas, www.emtrd.state.nm.us/ocd.         I Date:       Rig Release Date:		
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion.</li> <li>/19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C" 4' Cale.</li> <li>/19 – Load &amp; Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped &amp; circ to surface 1 ace plug set.</li> <li>/19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.</li> </ul>	-	
d Starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach v proposed completion or recompletion. /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C" 4' Calc. /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set. /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED. Approved for plugging of well hore only. Itability under bound is retained pending receipt of C :0.3 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.critted.state.nm.us/ocd. I Date: Rig Release Date:	inaluding astimated da	
proposed completion or recompletion.          /19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         4' Calc.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well hore only.         Liability under bond (s retained pending receipt of C-103 (subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.chintd.state.nm.us/ocd.         1 Date:       Rig Release Date:	vellbore diagram of	
/19 – NUBOP. Pulled production equipment out of hole. Set 4.5" CIBP @ 2616'. Dumped 3 sx Class "C"         4' Calc.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well hore only.         Midbh may be found to retained pending receipt of C-03 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmmtd.state.nm.us/ocd.         1 Date:       Rig Release Date:	venuore diagram or	
4' Calc.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well hore only.         Liability under bond (scenaring pending receipt of C.103 (Subsequent Report of Well Plugging) witch may be found at OCD Web Page under Forms, www.enard.state.nm.us/ocd.         1 Date:       Rig Release Date:		
4' Calc.         /19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL NDONED.         Approved for plugging of well hore only.         Liability under bond (scenaring pending receipt of C.103 (Subsequent Report of Well Plugging) witch may be found at OCD Web Page under Forms, www.enard.state.nm.us/ocd.         1 Date:       Rig Release Date:	Cement from 2616' to	
/19 – Load & Circ 4.5" CSG to surface with 40 bbls plugging mud. Pressure test to 500 psi for 10 minutes ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL ANDONED.         Approved for plugging of well hore only.         Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmntd.state.nm.us/ocd.         I Date:       Rig Release Date:	Content from 2010 to	
ped 30 sx Class "C" Cement to 736' Calc. Tagged TOC @ 730'. EOT @ 157' pumped & circ to surface 1 ace plug set.         /19 - Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL ANDONED.         Approved for plugging of well hore only.         Liability under bond is retained pending receipt of C:03 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emmrd.state.nm.us/ocd.         I Date:       Rig Release Date:	held FOT @ 1170'	
ace plug set.       /19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PL ANDONED.         Approved for plugging of well hore only.         Liability under bond is retained pending receipt of C-iO-i (Subsequent Report of Well Plug_ing) which may be found at OCD Web Page under Forms, www.emmrd.state.nm.us/ocd.         I Date:       Rig Release Date:		
/19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PLANDONED.         Approved for plugging of well hore only.         Liability under bond is retained pending receipt of C-iO-i (Subsequent Report of Well Plug_ing) which may be found at OCD Web Page under Forms, www.emmrd.state.nm.us/ocd.         I Date:       Rig Release Date:	2 5X Class C Comont.	
And NDONED.         Approved for plugging of well hore only.         Liability under bond is retained pending receipt         of C-103 (Subsequent Report of Well Plugging)         which may be found at OCD Web Page under         Forms, www.enard.state.nm.us/ocd.         I Date:         Rig Release Date:	UCCED AND	
Approved for plugging of well hore only.         Liability under bond (s retained pending receipt of C.103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.chard.state.nm.us/ocd.         I Date:       Rig Release Date:	UUULD AILD	
Labilite under bond is retained pending receipt of C-103 (Subsequent Report of Well Piugaing) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.         I Date:       Rig Release Date:		
d Date:		
d Date:		
I Date: Rig Release Date:		
eby certify that the information above is true and complete to the best of my knowledge and belief.		
eby certify that the information above is true and complete to the best of my knowledge and belief.		
eoy certify that the information above is true and complete to the best of my knowledge and belief.		
- 11.5<		
$T \times \times$		
NATURE		
	22, 2019	
e or print name Jeremy Haass E-mail address: jeremy_haass@eogresources.com		
State Use Only	2 <u>2, 2019</u> Phone: <u>575-748-4311</u>	
ROVED BY: Statement TITLE THE MAN DA		