Form 3160-5

### UNITED STATES

FORM APPROVED

, ——	PARTMENT OF THE I	NTERIOR	OCD A	tesia		D. 1004-0137 nuary 31, 2018
SUNDEY NOTICES AND DEPORTS ON WELLS				5. Lease Serial No. NMNM067896		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposation SERVATION AND OIL					6. If Indian, Allottée or Tribe Name	
SUBMIT IN	TRIPLICATE - Other inst	tructions on p	AUG 212	019	7. If Unit or CA/Agree	ement, Name and/or No.
Type of Well     Gas Well	ner		DECEIV		8. Well Name and No. SHUGART WEST	198
Name of Operator     MARATHON OIL PERMIAN L	Contact: LC E-Mail: jvancuren@	JENNIFER VA	N CUREN		9. API Well No. 30-015-30923-0	0-S1
3a. Address 5555 SAN FELIPE ST HOUSTON, TX 77056		3b. Phone No. (include area code) Ph: 713.296.2500			10. Field and Pool or Exploratory Area SHUGART	
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description	,	·		11. County or Parish, State	
Sec 19 T18S R31E NWNE 66	60FNL 2310FEL				EDDY COUNTY	, NM
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICAT	E NATURE O	F NOTICE,	REPORT, OR OTH	IER DATA
TYPE OF SUBMISSION			TYPE OF	ACTION		
Subsequent Report    Subsequent Report   Final Abandonment Notice    Subsequent Report   Subsequent Re	ally or recomplete horizontally, rk will be performed or provide a operations. If the operation re bandonment Notices must be fil inal inspection.	□ New □ Plug □ Plug nt details, includi give subsurface I the Bond No. on sults in a multiple ed only after all r	aulic Fracturing. Construction and Abandon Back  ng estimated startin ocations and measu faile with BLM/BIA completion or rece equirements, includ	Reclam Recomp Recomp Tempor Water I g date of any p red and true ve Required sul impletion in a r ing reclamatio	olete arily Abandon Disposal roposed work and appro- rtical depths of all pertin because treports must be new interval a Form 316	ent markers and zones. filed within 30 days 0-4 must be filed once und the operator has
Below ground  14. I hereby certify that the foregoing is	s true and correct. Electronic Submission #	471447 verified	by the BLM Wel	l Information		
For MARATHON OIL PERMIAN LLC, sent to Committed to AFMSS for processing by PRISCILLA PEREZ Name (Printed/Typed) JENNIFER VAN CUREN Title REG			CILLA PEREZ of	n 07/01/2019	•	
Name (Printed/Typed) JENNIFE	R VAN CUREN		Title REGUL	ATORY AN	ALYSI	
Signature (Electronic S	Submission)		Date 07/01/2	019		
·	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE U	SE	
_Approved By	us a.lim	·	Title &	RET		7.20-19 Date
Conditions of approval, it any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduct the conduction of th	uitable title to those rights in the		Office <i>Lf</i>	0		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any face, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



## Marathon Oil

# Wellbore Schematic Well Name: SHUGART WEST 19 FEDERAL 8 30-0/5-30923

Country UNITED STATES	Field Name SHUGART	Latitude (*) 32.73821400			North/South Reference FNL
KB-Ground Distance (ft) 16.00	KB-Mud Line Distance (ft)	Ground Elevation (ft) 3,627.00	Drilling Rig Spud Date	Well Original Completion Date	Well First Production Date 5/31/2016

3001530923	16.00	0/3/1/2010
	SHUGART WEST 19 FEDERAL 8,	, 6/27/2019 8:53:37 AM
MD (ftKB)	Vertical s	chematic (actual)
		,
	6.5	
0.0	Acher 312	
	177/	17/2"
	Anher 515 B. Salt 1771	
16.1		Des:Conductor 1; Category:Casing; OD:20.000 in; ID:19.120 in; Length:24.00 ft;
	Des:Conductor Cement; Category:Cement; Top MD:16.0 ftKB; Btm MD:40.0 ftKB	/ ID Min:0.000 in; Wt.:94.00 lb/ft; Grade:K-55;
` 40.0	100 MB. 10.0 MAD. 40.0 MAD	Top MD:16.0 ftKB; Btm MD:40.0 ftKB
	Des:Conductor Cement; Category:Cement; ورود	Des:Surface; Category:Casing; OD:13.375 in; ID:12.720 in; Length:744.00 ft; ID
,	Top MD:16.0 ftKB; Btm MD:760.0 ftKB	Min:0.000 in; Wt.:48.00 lb/ft; Grade:H-40; Top
759.8	Des:Surface Casing Cement; Category:Cement; Top MD:16.0 ftKB; Btm	MD:16.0 ftKB; Blm MD:760.0 ftKB Des:Intermediate 1; Category:Casing;
	Category: Cement; Top MD: 16.0 ftkB; Btm ———————————————————————————————————	OD:8.625 in; ID:7.920 in; Length:2,784.00 ft;
2,799.9	YA .> 1929 MD:2,800.0 ftKB	/ ID Min:0.000 in; Wt.:32.00 lb/ft; Grade:J-55; Top MD:16.0 ftKB; Btm MD:2,800.0 ftKB
3084 8	<u> </u>	20000000000000000000000000000000000000
2340 te	BS 5760  BS 5760	
7,003.9	Del 45 ml 700 2700	
	Del 700 10C 21	
7,503.0	BS 5/60	
7,505.0		
		Anchor/catcher; 4.500
7,505.9	·	
,	Stage tool 4315	
	Stage tool 4513	
7,679.1		
	David of the Control Country	Top MD:7,679.0; Btm MD:7,689.0
7,689.0	Des:Production Casing Cement; Category:Cement; Top MD:7,004.0 ftKB; Btm	Tubing; 2.875
	MD:8,400.0 ftKB	1 ubing, 2.073
7.000.0		
7,939.0		
		X Profile Nipple; seat nipple; 2.375
7,940.0	· .	
	:	Sand Separator; 2.875
	·	Gand Separator, 2.073
7,960.0		
		Mud Anchor: 2.875
7,991.1	:	
		7689-7679
		1601-1611
8,091.9		
,		Top MD:8,092.0; Btm MD:8,126.0
8,126.0		
0,120,0		
	Prior to PAA	Des:Production 1; Category:Casing;
8,399.9	MILLON TO PATH	O <u>D:5.500</u> in; ID:4.950 in; Length:8,384.00 ft; ID Min:0.000 in; Wt.:15.50 lb/ft; Grade:J-55;
		Top MD:16.0 ftKB; Btm MD:8,400.0 ftKB
L.,		

## Marathon Oil

www.marathonoil.com

# Wellbore Schematic Well Name: SHUGART WEST 19 FEDERAL 8 30-0/5-30923

Province Country V MEXICO UNITED STATES	Field Name SHUGART	Latitude (*) 32.73821400	Longilude (*) -103.90726200		North/South Reference FNL
70 UWI KB-Ground Distance (ft) 1530923 16.00	KB-Mud Line Distance (fl)	Ground Elevation (ft) 3,627.00	Drilling Rig Spud Date	Well Original Completion Date	Well First Production Date 5/31/2016
1000020	l				

API/IPO UM 3001530923	KB-Ground Distance (ft) KB-Mud Line Distance (ii) Ground Elevation (ii) Ground Elevation (ii) Ground Elevation (iii) Ground Elevation (ii
	SHUGART WEST 19 FEDERAL 8, 6/27/2019 8:53:37 AM
MD (ftKB)	Vertical schematic (actual)
0.0	@305X - SURFIEY D. H.M.
16.1	Des:Conductor 1; Category:Casing;  OD:20.000 in; ID:19.120 in; Length:24.00 ft;  To MD:45.0 ft/R Rhm MD:40.0 ft/R
40.0	Top MD:16.0 ftKB; Btm MD:40.0 ftKB  Des:Surface; Category:Casing; OD:13.375  in; ID:12.720 in; Length:744.00 ft; ID  Top MD:16.0 ftKB; Btm MD:760.0 ftKB  Min:0.000 in; Wt.:48.00 lb/ft; Grade:H-40; Top
759.8	Des:Surface Casing Cement; Category:Cement; Top MD:16.0 ftKB; Btm MD:760.0 ftKB Des:Intermediate 1; Category:Casing; OD:8.625 in; ID:7.920 in; Length:2,784.00 ft; MD:2,800.0 ftKB  ID Min:0.000 in; Wt.:32.00 lb/ft; Grade:J-55;
2,799.9	Top MD:16.0 ftKB; 8tm MD:2,800.0 ftKB  Tubing; 2.875
7,003.9	810-710 P.S 4105X 2850-2750 P.S TAG-
7,503.0	P, S TAG- 353X 5810-5710 P, S @
7,505.9	CIBP @ 7600' W1 255X @
7,679.1	Top MD:7,679.0; Btm MD:7,689.0
7,689.0	Des:Production Casing Cement; Category:Cement; Top MD:7,004.0 ftKB; Btm ———————————————————————————————————
7,939.0	
7,940.0	
7,960.0	
7,991.1	
8,091.9	Top MD:8,092.0; Btm MD:8,126.0
8,126.0	
8,399.9	Des:Production 1; Category:Casing; OD:5.500 in; ID:4.950 in; Length:8,384.00 ft; ID Min:0.000 in; Wt.:15.50 lb/ft; Grade:J-55; Top MD:16.0 ftKB; Btm MD:8,400.0 ftKB

Page 1/1

Report Printed: 6/27/2019

#### BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

#### Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>minety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged</u>.
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken:</u>
From March 1<sup>st</sup> through June 15<sup>th</sup> annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted