

District I - (575) 393-6161

District II - (575) 748-1283

District III - (505) 334-6178

District IV - (505) 476-3460

1000 Rio Brazos Rd., Aztec, NM 87416

1220 S. St. Francis Dr., Santa Fe, NM 87505

1220 S. St. Francis Dr., Santa Fe, NM 87505

1220 S. St. Francis Dr., Santa Fe, NM 87505

1220 S. St. Francis Dr., Santa Fe, NM 87505

Energy, Minerals and Natural Resources

Revised July 18, 2013

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

DISTRICT IV ARTESIA O.C.D.

WELL API NO.

30-015-22294

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
Ferguson IF

8. Well Number

2

9. OGRID Number

7377

10. Pool name or Wildcat

Atoka; Glorieta-Yeso

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

EOG Resources, Inc.

3. Address of Operator

104 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter M : 330 feet from the South line and 990 feet from the West line

Section 28 Township 18S Range 26E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3390'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

CLOSED-LOOP SYSTEM ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☒

CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/29/19 - MIRU and POOH with production equipment. NU BOP. Set a 4-1/2" CIBP at 2380'. Tagged CIBP. Circulated 52 bbls with 13 sx salt water gel as plugging mud. Tested to 600 psi for 10 mi, no leak off. Spotted 10 sx Class "C" cement on top of CIBP to 2236' calc.

8/30/19 - Tagged TOC at 2212'. Tested to 600 psi, no leak off. Perforated at 1200'. Attempted to establish injection rate with 500 psi, no leak off or injection into perforations. Spotted a 35 sx Class "C" cement plug from 1258'-921' calc TOC. Tagged TOC at 909'. Spotted 10 sx Class "C" cement and circulated from 96' up to surface.

9/19/19 - Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. **WELL IS PLUGGED AND ABANDONED.**

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms. www.cranrd.state.nm.us/oed.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Specialist DATE September 27, 2019

Type or print name Tina Huerta E-mail address: tina\_huerta@eogresources.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: [Signature] TITLE Staff DATE 10/1/19

Conditions of Approval (if any):

78