Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD A	Artesia
-------	---------

FORM APPROVED OMB NO. 1004-0137 1, 2018

Expires:	January	3
erial No.		

Expues, January	
Lease Serial No. NMNM81586	
141411 41410 1000	

5.

SUNDRY NOTICES AND REPORTS ON WELLS			NMNM81586 6. If Indian, Allottee or Tribe Name				
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.							
SUBMIT IN TRIPLICATE - Other instructions on page 2				7. If Unit or CA/Agreement, Name and/or No.			
Type of Well Oil Well					8. Well Name and No. RIVERBEND FED		
2: Name of Operator Contact: DAVID STEWART OXY USA INCORPORATED E-Mail: david_stewart@oxy.com					9. API Well No. 30-015-28390-00-\$1		
3a. Address 5 GREENWAY PLAZA SUITE HOUSTON, TX 77046-0521	3b. Phone No. (include area code) Ph: 432.685.5717			10. Field and Pool or Exploratory Area E PIERCE CROSSING			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, State		
Sec 23 T24S R29E NWNW		EDDY COUNTY, NM			/, NM		
12. CHECK THE AF	PPROPRIATE BOX(ES)	TO INDICAT	E NATURE OI	F NOTICE, I	REPORT, OR OTH	IER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION					
Notice of Intent	☐ Acidize	□ Deepe	en	☐ Production	on (Start/Resume)	■ Water Shut-Off	
· 	☐ Alter Casing	☐ Hydra	ulic Fracturing	□ Reclamat	tion	■ Well Integrity	
☐ Subsequent Report	□ Casing Repair	□ New	Construction	☐ Recompl	ete	Other	
☐ Final Abandonment Notice	☐ Change Plans	🔀 Plug a	and Abandon	□ Temporarily Abandon			
	☐ Convert to Injection	n Plug Back		☐ Water Di	sposal	:	
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator hadetermined that the site is ready for final inspection. TD-9000' PB-4570' Perfs-3070-4470' 10-3/4" 40.5# csg @ 451' w/470sx, 14-3/4" hole, TOC-Surf-Circ 7-5/8" 26.4# csg @ 2900' w/700sx, 9-5/8" hole, TOC-Surf-Circ 4-1/2" 11.6# csg @ 9000',DVT @ 6730',4570'w/1220sx, 6-3/4" hole, TOC-1400'-CBL 1. CIBP @ 3020' w/ 25sx cmt to 2745' 2. M&P 25sx cmt @ 1750-1500' WOC-Tag 3. Perf @ 501', sqz 120sx cmt to surface. 10# MLF between plugs - Above ground steel tanks will be utilized SEE ATTACHED FOR CONDITIONS OF APPROVAL					NSERVATION DISTRICT 2 1 2019 EIVED		
	# Electronic Submission For OXY US nmitted to AFMSS for prod	A INCORPORAT essing by PRIS	ED, sent to the CILLA PEREZ or	Carlsbad n 07/11/2019 (19PP2776SE)		
Name(Printed/Typed) DAVID STEWART			THE REGUL	ATORY ADV			
Signature (Electronic S	Submission)		Date 07/11/20	019			
	THIS SPACE FO	OR FEDERAL	OR STATE	OFFICE US	E		
Approved By	es a. lason	~	Title SAC	7		7-28-19 Date	
Conditions of approval if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conductive the applicant to conduct the applicant the applicant to conduct the applicant the	nitable title to those rights in the ct operations thereon.	e subject lease	Office CFC	5			
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s	U.S.C. Section 1212, make it a statements or representations as	crime for any pers to any matter with	on knowingly and in its jurisdiction.	willfully to mal	ke to any department or	agency of the United	
(Instructions on page 2) ** BLM REV	ISED ** BLM REVISE	D ** BLM RE	/ISED ** BLN	REVISED	** BLM REVISE	D **	

OXY USA Inc. - Proposed Riverbend Federal #8 API No. 30-015-28390

120sx @ 501'-Surface 14-3/4" hole @ 451' 10-3/4" csg @ 451' Rugtler Anhy 550 w/ 470sx-TOC-Surf-Circ Perf @ 501' 25sx @ 1750-1500' Base (Anhy 2808 CIBP @ 3020' w/ 25sx to 2745' Del. 3000 9-7/8" hole @ 2900' 7-5/8" csg @ 2900' Bell 3062 Clarg 3894 w/ 700sx-TOC-Surf-Circ Perfs @ 3070-3165' Perfs @ 3946-4000' Perfs @ 4320-4470' Bash 5178 Cmt plug @ 4570' Cmt plug @ 6728' BS 6768 6-3/4" hole @ 9000' 4-1/2" csg @ 9000' w/ 1220sx-TOC-1400'-CBL DVT's @ 6730', 4570' PB-89531

TD-9000'

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.
- 8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.