

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*5. Lease Serial No.
NMNM91078

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

SUBMIT IN TRIPLICATE - Other instructions on page 28. Well Name and No.
RANA SALADA FED COM 0605 231H9. API Well No.
30-015-46085-00-X110. Field and Pool or Exploratory Area
PURPLE SAGE-WOLFCAMP (GAS)11. County or Parish, State
EDDY COUNTY, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

NOVO OIL AND GAS NORTHERN DELA

Contact: KURT SHIPLEY

Email: kshipley@novoog.com

3a. Address

1001 WEST WILSHIRE BOULEVARD SUITE 206
OKLAHOMA CITY, OK 73116

3b. Phone No. (include area code)

Ph: 405-286-3916

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 1 T23S R28E 1127FNL 395FEL
32.338951 N Lat, 104.033241 W Lon

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Change to Original A
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	PD

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Due to poor availability of the approved casing, substitute casing for the intermediate casing is requested. The casing substitute has a non-API connection but is superior in strength to the originally proposed casing. Also, due to poor availability of the stage collar with this connection a single stage cementing segment is being proposed.

Casing Request:

7 5/8", 29.70 ppf, RYS110, USS-Eagle SFH SC to be set at 9800' TMD.

Design Safety Factors: Collapse 2.71, Burst 6.31, Tension 2.29

Casing specification sheet is attached.

Carlsbad Field Office
OCD Artesia**NM OIL CONSERVATION**
ARTESIA DISTRICT

AUG-21 2019

Existing COAs Still Apply, Except for the Following:

RECEIVED

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #474713 verified by the BLM Well Information System
For NOVO OIL AND GAS NORTHERN DELA, sent to the Carlsbad
Committed to AFMSS for processing by CANDY VIGIL on 07/24/2019 (19CV0077SE)

Name (Printed/Typed) BRIAN WOOD

Title CONSULTANT

Signature

(Electronic Submission)

Date 07/23/2019

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By JEROMY PORTER

Title PETROLEUM ENGINEER

Date 07/29/2019

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Carlsbad

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

RWT 10-25-19

Additional data for EC transaction #474713 that would not fit on the form

32. Additional remarks, continued

Cementing Request:

Lead: 380 sx; 1026 cu ft; 20% excess; 2.70 cu ft/sx; 10.50 ppg; Class H + gel + extender + retarder + LCM + beads; 500 psi 24 hour compressive strength

Tail: 100 sx; 126 cu ft; 20% excess; 1.26 cu ft/sx; 14.50 ppg; Class H + gel + retarder + LCM; 1200 psi 24 hour compressive strength.

Conditions of Approval

- 7 5/8" Intermediate Casing must be kept at least 1/3 fluid filled to meet BLM Collapse Requirement.
- Cement to Surface. Excess Cement calculates to 18%, additional Cement might be required.

JJPO7292019

Revisions to Operator-Submitted EC Data for Sundry Notice #474713

	Operator Submitted	BLM Revised (AFMSS)
Sundry Type:	APDCH NOI	APDCH NOI
Lease:	NMNM61349	NMNM91078
Agreement:		
Operator:	NOVO OIL & GAS N DELAWARE LLC 1001 W. WILSHIRE BLVD, SUITE 206 OKLAHOMA CITY, OK 73116 Ph: 405-404-0414	NOVO OIL AND GAS NORTHERN DELA 1001 WEST WILSHIRE BOULEVARD SUITE 206 OKLAHOMA CITY, OK 73116 Ph: 4054040414
Admin Contact:	KURT SHIPLEY VP-OPERATIONS E-Mail: kshipley@novoog.com Cell: 405-404-0414 Ph: 405-286-3916	KURT SHIPLEY VP-OPERATIONS E-Mail: kshipley@novoog.com Cell: 405-404-0414 Ph: 405-286-3916
Tech Contact:	BRIAN WOOD CONSULTANT E-Mail: brian@permitswest.com Ph: 505-466-8120	BRIAN WOOD CONSULTANT E-Mail: brian@permitswest.com Ph: 505-466-8120
Location:		
State:	NM	NM
County:	EDDY COUNTY	EDDY
Field/Pool:	PURPLE SAGE WOLFCAMP	PURPLE SAGE-WOLFCAMP (GAS)
Well/Facility:	RANA SALADA FED COM 0605 231H Sec 1 T23S R28E Mer NMP NENE 1127FNL 395FEL	RANA SALADA FED COM 0605 231H Sec 1 T23S R28E 1127FNL 395FEL 32.338951 N Lat, 104.033241 W Lon



U. S. Steel Tubular Products

7/23/2019 8:28:16 AM

7.625" 29.70lbs/ft (0.375" Wall) USS RYS110 USS-EAGLE SFH® SC

MECHANICAL PROPERTIES		Pipe	USS-EAGLE SFH® SC	
Minimum Yield Strength		110,000	--	psi
Maximum Yield Strength		125,000	--	psi
Minimum Tensile Strength		120,000	--	psi
DIMENSIONS		Pipe	USS-EAGLE SFH® SC	
Outside Diameter		7.625	7.901	in.
Wall Thickness		0.375	--	in.
Inside Diameter		6.875	6.794	in.
Standard Drift		6.750	6.750	in.
Alternate Drift		--	6.750	in.
Nominal Linear Weight, T&C		29.70	--	lbs/ft
Plain End Weight		29.06	--	lbs/ft
SECTION AREA		Pipe	USS-EAGLE SFH® SC	
Critical Area		8.541	6.879	sq. in.
Joint Efficiency		--	80.5	%
PERFORMANCE		Pipe	USS-EAGLE SFH® SC	
Minimum Collapse Pressure		5,350	5,350	psi
External Pressure Leak Resistance		--	5,350	psi
Minimum Internal Yield Pressure		9,460	9,460	psi
Minimum Pipe Body Yield Strength		940,000	--	lbs
Joint Strength		--	757,000	lbs
Compression Rating		--	757,000	lbs
Reference Length		--	17,364	ft
Maximum Uniaxial Bend Rating		--	53.3	deg/100 ft
MAKE-UP DATA		Pipe	USS-EAGLE SFH® SC	
Make-Up Loss		--	5.96	in.
Minimum Make-Up Torque		--	19,000	ft-lbs
Maximum Make-Up Torque		--	21,000	ft-lbs
Maximum Operating Torque		--	44,100	ft-lbs

Legal Notice

All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

U. S. Steel Tubular Products
460 Wildwood Forest Drive, Suite 300S
Spring, Texas 77380

1-877-893-9461
connections@uss.com
www.usstubular.com