Form 3160-5 (June 2015)

## UNITED STATES DAG BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS AND TOSION  Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					NMNM16331  6. If Indian, Allottee or Tribe Name	
1. Type of Well ☐ Gas Well ☐ Other					8. Well Name and No. CB HAYES 10 3 FED COM 005 2H	
Name of Operator					9. API Well No. 30-015-45667-00-X1	
3a. Address 6301 DEAUVILLE BLVD MIDLAND, TX 79706	. (include area code) 7-7655	ode) 10. Field and Pool or Exploratory Area POKER LAKE-DELAWARE				
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish,	State
Sec 15 T23S R28E NENE 519FNL 1330FEL 32.311359 N Lat, 104.070953 W Lon					EDDY COUNTY, NM	
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE O	F NOTICE,	REPORT, OR OT	HER DATA
TYPE OF SUBMISSION	TYPE OF ACTION					
☐ Notice of Intent	☐ Acidize	☐ Dee		_	ion (Start/Resume)	■ Water Shut-Off
_	☐ Alter Casing	Hyd	raulic Fracturing	lic Fracturing		☐ Well Integrity
Subsequent Report	Casing Repair		Construction	☐ Recomplete		
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon			arily Abandon	Diffing Operations
	☐ Convert to Injection	☐ Plug Back ☐ Water		☐ Water D	Disposal	
13. Describe Proposed or Completed Op. If the proposal is to deepen direction: Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation res- pandonment Notices must be file inal inspection.	give subsurface the Bond No. or sults in a multipl	locations and measu 1 file with BLM/BIA e completion or reco	red and true ve  Required sub impletion in a r ing reclamation	rtical depths of all perti- sequent reports must be new interval, a Form 31, n, have been completed	nent markers and zones. e filed within 30 days 60-4 must be filed once and the operator has
5/10/19 - Test full BOPE to 250 psi low/6650 psi high.				GC	for record. NMC	) 9 DCD
5/11/19 - Test 13-3/8" surf csg to 1,500 psi for 30 minutes, good test.  5/12/19-5/23/19 - Drill 12-1/4" intermediate hole to 8,964'.						
5/12/19-5/23/19 - Drill 12-1/4" 5/23/19 - Notified Omar @ BL 8,954"; DV tool @ 2,528', float	M of intent to run & ceme	nt csg. Ran 9	1-5/8" <u>43.50#,</u> HC	CL-80 LTC c	a acar de plan	CONSERVATION ESIA DISTRICT
5/25/19 - Cemented in place w/Lead: <u>1.340.sx</u> , Class C, Yld: 2.50cuft/sk, Dens: 11.90#/gal 379 sx, Class C, Yld: 1.33cuft/sk, Dens: 14.80#/gal, 140 bbl to surface, full returns through job, WOC per BLM requirements. Released rig					se SE	P 2 3 2019
					· R	ECEIVED
14. I hereby certify that the foregoing is	Flectronic Submission #	ISA INCORPO	RATED, sent to t	the Carlsbad		
Name (Printed/Typed) LAURA B	Title REGUL	ATORY SP	ECIALIST			
Signature (Electronic	Submission)	.*	Date 08/20/2	019		
	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE U	SE	
Aumound Du			Title Acc	epted fo	or Record	AUG <sub>at</sub> 2 2 2019
Approved By	<u> </u>	onathon				
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			1	Carisbad Fie	•	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## Additional data for EC transaction #479419 that would not fit on the form

## 32. Additional remarks, continued

6/30/19 - Test full BOPE to 250 psi low/6650 psi high.

7/1/19 - Test 9-5/8" csg to 2,358 psi for 30 min, good test. Drill 8-1/2" production hole.

7/14/19 - Reached TD 20,040'.

7/15/19 - Notify BLM of intent to run & cement casing.

7/16/19 - Ran 5-1/2" 20#, P110-IC TXP-BTC csg to 20,020', float collar @ 19,974', float shoe @ 20,017'.

7/18/19 - Released rig

7/19/19 - Cemented in place w/Lead: 3.461 sx. Class C, Yld: 1.40cuft/sk, Dens: 14.50#/gal & Tail: 116 sx, Class H, Yld: 2.18cuft/sk, Dens: 15.00#/gal, 144 bbls to surface, full returns throughout job, WOC per BLM requirements.