Form 3160-5 (June 2015) DF	UNITED STATE EPARTMENT OF THE I	S C	arlsba	nd Fie	Id Offer	APPROVED O. 1004-0137 anuary 31, 2018
	UREAU OF LAND MANA NOTICES AND REPO	GEMENT		D Ar	Chiss Serial No.	
Do not use th	is form for proposals to II. Use form 3160-3 (AP	drill or to re-er	nter an		6. If Indian, Allottee of	
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agre	ement, Name and/or No.
1. Type of Well					8. Well Name and No. STEVENS A 15	<u> </u>
Oil Well Gas Well Other Name of Operator BURNETT OIL COMPANY INC E-Mail: LGARVIS@BURNETTOIL.COM					9. API Well No. 30-015-35321-0)0-S1
3a. Address 3b. Phone No. (include area code) 801 CHERRY STREET UNIT 9 SUITE 1500 Ph. 817-583-8730 FORT WORTH, TX 76102-6881 Fx: 817-332-8438					10. Field and Pool or CEDAR LAKE	Exploratory Area
4. Location of Well <i>(Footage, Sec., T</i>			400		11. County or Parish,	State
Sec 13 T17S R30E SENW 1820FNL 2310FWL				EDDY COUNTY	Y, NM	
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICATE	NATURE O	FNOTICE	, REPORT, OR OTH	IER DATA
TYPE OF SUBMISSION			TYPE OF	ACTION		
Notice of Intent	🗖 Acidize	🗖 Deeper	1	Produc	tion (Start/Resume)	U Water Shut-Off
Subsequent Report	Alter Casing		lic Fracturing	Reclam		U Well Integrity
	Casing Repair	_	onstruction		•	Other
Final Abandonment Notice	Change Plans	🔲 Plug ar	nd Abandon ack	□ Tempor	rarily Abandon Disposal	
following completion of the involved testing has been completed. Final Al determined that the site is ready for f Burnett is requesting approva	bandonment Notices must be fil inal inspection.	led only after all req	uirements, includi	ing reclamatio	on, have been completed a NIM OIL CC	A DISTRICT
1. Total Disturbance 460.4 x 460.1 2. Inside top of pit 350? X 350? 3. Inside Bottom 260? X 260? 4. 17? Deep				OCT 2.4 2019 SEE ATTACHED FOR		
5. 3:1 Slope 6. At a 15? Water level we wil 7. There will be no new flowlir 8. No new roads, existing road 9. Lined by minimum 30 mil pl	e or electrical disturbance d will be utilized.	,	-11-19	ONDIT: ניסר	$f(X) = \frac{1}{2} S = \frac{1}{2} \frac$	ROXAL achel
14. I hereby certify that the foregoing is Con Name (Printed/Typed) LESLIE G	# Electronic Submission For BURNETT nmitted to AFMSS for proc	OIL COMPANY I essing by JUANA	NC, sent to the MEDRANO or	e Carlsbad	(19JM0096SE)	
						<u></u>
Signature (Electronic S			OR STATE (SE	
C.A.	TuAA-		AFI	$\overline{N-1}$	I M	19/7/2014
Approved By Conditions of approval, if any, are attached	a. Approval of this notice does	not warrant or	Title	- Lg n	(/_)	Date
certify that the applicant holds legal or equivalent would entitle the applicant to condu- Title 18 U.S.C. Section 1001 and Title 43	ict operations thereon.		Office (/1		ake to any department or	agency of the United
States any false, fictitious or fraudulent	statements or representations as	to any matter withi	n its jurisdiction.			agency of the Onneu
(Instructions on page 2) ** BLM REV	ISED ** BLM REVISEI	D ** BLM REV	ISED ** BLM	I REVISEI	D ** BLM REVISE	D **

• '

RWND	2449
------	------

Additional data for EC transaction #483526 that would not fit on the form

*

32. Additional remarks, continued

۰.

۰,

Revisions to Operator-Submitted EC Data for Sundry Notice #483526

• .

.

•

	Operator Submitted	BLM Revised (AFMSS)
Sundry Type:	NEWCON NOI	NEWCON NOI
Lease:	NMLC030570A	NMLC030570A
Agreement:		
Operator:	BURNETT OIL CO.INC. BURNETT PLAZA - UNIT 9 801 CHERRY STREET - SUITE 15F FORT WORTH, TX 76102 Ph: 817-583-8730	BURNETT OIL COMPANY INC FORMING HERRY ISATRE HODZUNIT 9 SUITE 1500 FORT WORTH, TX 76102-6881 Ph: 817.332.5108
Admin Contact:	LESLIE GARVIS REGULATORY MANAGER E-Mail: LGARVIS@BURNETTOIL.COM	LESLIE GARVIS REGULATORY MANAGER E-Mail: LGARVIS@BURNETTOIL.COM
	Ph: 817-583-8730 Fx: 817-332-8438	Ph: 817-583-8730 Fx: 817-332-8438
Tech Contact:	LESLIE GARVIS REGULATORY MANAGER E-Mail: LGARVIS@BURNETTOIL.COM	LESLIE GARVIS REGULATORY MANAGER E-Mail: LGARVIS@BURNETTOIL.COM
	Ph: 817-583-8730 Fx: 817-332-8438	Ph: 817-583-8730 Fx: 817-332-8438
Location: State: County:	NM EDDY	NM EDDY
Field/Pool:	CEDAR LAKE YESO	CEDAR LAKE
Well/Facility:	STEVENS A 15 Sec 13 T17S R30E Mer NMP SENW 1820FNL 2310FWL	STEVENS A 15 Sec 13 T17S R30E SENW 1820FNL 2310FWL

PRODUCED WATER FRAC POND CONDITIONS OF APPROVAL

A copy of the application (APD, Grant, or Sundry Notice) and attachments, including stipulations, survey plat and diagram, will be on location during construction. BLM personnel may request to see a copy of your permit during construction to ensure compliance with all conditions of approval. Construction will cease until the permit is on location.

Holder agrees to comply with the following conditions of approval to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this permit.

2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated.

3. Required Standard Conditions of Approval:

a. Notification

Contact the Supervisory Environmental Protection Specialist, Jim Amos, at 575-234-5909 at least 24 hours prior to starting construction.

b. Contamination

The operator will preclude releases of oil into open ponds. The operator must remove any accumulation of oil, condensate, or contaminant in a pond within 48 hours of discovery.

c. Authorized Disturbance

Confine all construction and maintenance activity to the approved authorized area applied for in the application. The entire proposed frac pond will be fenced off with a three-strand wire fence to deter unauthorized surface disturbance. The fence will be installed prior to any work taking place and will stay in place until all work has been completed.

d. Liner

The pond must have at least two 60 mil liners. The pond liner shall be maintained in good working condition, with no tears or holes, until the pond is closed. No trash, pipe, barrels, wireline, or metal equipment is permitted in the pond.

e. Freeboard

Ponds shall be constructed to preclude the accumulation of precipitation runoff and maintain a minimum of 2 feet of freeboard between the maximum fluid level and the lowest point of containment at all times. If pond fluids threaten to rise to a level allowing less than 2 feet of freeboard, steps shall immediately be taken to prevent introduction of additional fluids until sufficient pond capacity has been restored through fluid removal or an alternative containment method is approved and installed.

f. Monitor:

Personnel or a monitor must be onsite when the pond is in use.

g. Escape Ramps

The operator will construct and maintain frac ponds to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or other methods of avian and terrestrial wildlife escape in frac ponds. Escape ramps must be installed at every corner of the frac pond and in the center of each side if that side exceeds 100 feet in length. Escape ramps must be in contact with the side of the frac pond, bottom of the frac pond, and the top of the frac pond berm. Escape ramps <u>cannot</u> be made of metal and <u>cannot</u> be steeper than a 3:1 slope (Horizontal Distance: Vertical Distance) or 30% slope. (*Examples of escape ramps: 12'' wide wooden planks wrapped in matting, felt lining, etc.*)

h. Exclosure Netting

The operator will prevent humans, wildlife (including avian wildlife), and livestock access to fluid ponds that contain or have potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will install approved netting over ponds containing fluid in accordance with the requirements below. (*Note: The BLM does not approve of the use of flagging, strobe lights, metal reflectors, or noise makers as techniques for deterring wildlife.*)

Minimum Netting Requirements - The operator will:

- Construct a rigid structure made of steel tubing or wooden posts with cable strung across the pond at no more than seven (7) foot intervals along the X- and Y-axes to form a grid of 7 foot squares.
- Suspend netting a minimum of 2 feet above the fluid surface.
- Use a maximum netting mesh size of $1\frac{1}{2}$ inches to exclude most birds.
- Cover the top and all sides of the netting support frame with netting and secure the netting at the ground surface around the entire pond to prevent wildlife entry at the netting edges. (*Note:* Hog wire panels or other wire mesh panels or fencing used on the sides of the netting support frame is ineffective in excluding small wildlife and birds unless covered by the smaller mesh netting.)
- Installation of the net must commence immediately after high activity operations cease. High activity operations include drilling operations and fracturing operations.
- Monitor and maintain the netting sufficiently to ensure the netting is functioning as intended, has not entrapped wildlife, and is free of holes and gaps greater than $1\frac{1}{2}$ inches.
- Flagging or tags must be installed on the net in the center of the pond.

i. Mineral Material from Excavation

Mineral materials extracted during construction of the frac pond will be stored onlocation and/or used for constructing the frac pond.

j. Topsoil Stockpile

The operator shall strip at least the top 6 inches of soil (root zone) from the entire frac pond area and stockpile the topsoil approximately 25 feet outside the bermed perimeter of the pond in a low profile manner, reasonably protected from wind and water erosion. Topsoil shall not be used for constructing the produced water pond. The topsoil will be used for final reclamation purposes only.

k. Frac Pond Fence

The operator will install and maintain exclosure fencing on all sides of the frac pond to prevent access to public, livestock, and large forms of wildlife. The fence shall be installed at the base of the berm and never on top of the berm. Construction of the fence shall consist of steel and/or wooden posts set firmly into natural ground. Hog panel or chain-link fencing must be used as the fence and tied securely to the fence posts. Barbedwire fencing or electric fences <u>shall not</u> be used. The fence height <u>shall not</u> be shorter than six (6) feet. The erected fence shall be maintained in adequate condition until the frac pond is reclaimed.

1. Erosion Prevention

Install earthen erosion-control structures as are suitable for the specific terrain and soil conditions.

m. Reclamation Start

- I. Reclamation efforts will commence immediately after the frac pond is no longer needed for the purpose of completing wells.
- II. Within 3 months of completion of frac operations on associated wells, all earthwork and final reclamation must be completed. This includes reclaiming and/or removal of:
 - i. Any roads approved for use with the pond
 - ii. Surface water lines
 - iii. Tanks, pumps, fencing etc.

Requirements for Operations and Final Reclamation:

4. If, during any phase of the construction, operation, maintenance, or termination of the frac pond, any pollutant should be released from the contaminated frac pond, the control and total removal, disposal, and cleaning up of such pollutant, wherever found, shall be the responsibility of holder, regardless of fault.

Upon failure of holder to control, dispose of, or clean up such discharge, or to repair all damages resulting there-from, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

6. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the

establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

7. After all disturbed areas have been satisfactorily contoured and prepared for seeding the location needs to be revegetated with the seed mixture provided. Seeding may need to be repeated until revegetation is successful. Operators shall contact Jim Amos, Supervisor, Environmental Protection – (575)234-5909, **prior** to beginning surface reclamation operations.

8. Seeding is required: Use the following seed mix.

() seed mixture 1	() seed mixture 3
() seed mixture 2	() seed mixture 4
(X) LPC mixture	() Aplomado Falcon mix

STANDARD STIPULATIONS FOR OIL AND GAS RELATED SITES

A copy of the application (Grant/Sundry Notice) and attachments, including stipulations and map, will be on location during construction. BLM personnel may request to view a copy of your permit during construction to ensure compliance with all stipulations.

The holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer, BLM.

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant and for all response costs, penalties, damages, claims, and other costs arising from the provisions of the Resource Conservation and Recovery Act (RCRA), 42 U.S.C. Chap. 82, Section 6901 et. seq., from the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA), 42 U.S.C. Chap. 109, Section 9601 et. seq., and from other applicable environmental statues.

2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976, as amended (15 U.S.C. 2601, et. seq.) with regard to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized by this grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation and Liability Act, Section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the Authorized Officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et. seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et. seq.) on the right-of-way (unless the release or threatened release is wholly unrelated to the right-of-way holder's activity on the right-of-way). This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the site or related pipeline(s), any oil or other pollutant should be discharged from site facilities, the pipeline(s) or from containers or vehicles impacting Federal lands, the control and total removal, disposal, and cleanup of such oil of other pollutant, wherever

found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages to Federal lands resulting therefrom, the Authorized Officer may take such measures as deemed necessary to control and cleanup the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any liability or responsibility.

5. Sites shall be maintained in an orderly, sanitary condition at all times. Waste materials, both liquid and solid, shall be disposed of promptly at an appropriate, authorized waste disposal facility in accordance with all applicable State and Federal laws. "Waste" means all discarded matter including, but not limited to, human waste, trash, garbage, refuse, petroleum products, brines, chemicals, oil drums, ashes, and equipment.

6. The operator will notify the Bureau of Land Management (BLM) authorized officer and nearest Fish and Wildlife Service (FWS) Law Enforcement office within 24 hours, if the operator discovers a dead or injured federally protected species (i.e., migratory bird species, bald or golden eagle, or species listed by the FWS as threatened or endangered) in or adjacent to a pit, trench, tank, exhaust stack, or fence. (If the operator is unable to contact the FWS Law Enforcement office, the operator must contact the nearest FWS Ecological Services office.)

7. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" designated by the Rocky Mountain Five-State Interagency Committee. The color selected for this project is Shale Green, Munsell Soil Color Chart Number 5Y 4/2.

8. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on the holder's behalf, on public or Federal land shall be immediately reported to the Authorized Officer. The holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to the proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

9. A sales contract for removal of mineral material (caliche, sand, gravel, fill dirt) from an authorized pit, site, or on location must be obtained from the BLM prior to commencing construction. There are several options available for purchasing mineral material: contact the BLM office (575-234-5972).

10. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

11. Once the site is no longer in service or use, the site must undergo final abandonment. At final abandonment, the site and access roads must undergo "final" reclamation so that the character and productivity of the land are restored. Earthwork for final reclamation must be completed within six (6) months of the abandonment of the site. All pads and facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact. After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

12. The holder shall stockpile an adequate amount of topsoil where blading occurs. The topsoil to be stripped is approximately 6_{--} inches in depth. The topsoil will be segregated from other spoil piles. The topsoil will be used for final reclamation.

13. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

() seed mixture 1	() seed mixture 3
() seed mixture 2	() seed mixture 4
(X) seed mixture 2/LPC	() Aplomado Falcon Mixture

14. In those areas where erosion control structures are required to stabilize soil conditions, the holder shall install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound management practices. Any earth work will require prior approval by the Authorized Officer.

15. Open-topped Tanks - The operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 $\frac{1}{2}$ inches. The netting must not be in contact with fluids and must not have holes or gaps

16. The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

17. Open-Vent Exhaust Stack Exclosures – The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

18. Containment Structures - Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.