State of New Mexico State of New S
District III - (55) 748-1283 NOV 1 PDC CONSERVATION DIVISION District III - (50) 334-6178 1220 South St. Francis Dr. 1220 South St. Francis Dr. STATE
District III - (505) 334-678 1220 South St. Francis Dr. 1200 Rio Brass 8td., 24ze., NM 8740 1220 S. St. Francis Dr. 513460 133460
1000 Rio Brazos Rd, Azace, NM 87410 120 Sufficial (**) (**) 476-340 120 S. S. Francis Dr., Santa Fermina
SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name Chicago 9/8 WOPM Fee
SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name Chicago 9/8 WOPM Fee
Rope of Well: Oil Well Gas Well Other 2H String of Operator Gas Well Other 2H String of Operator 9. OGRID Number 147444 147444 147444 147444 147444 147444 147444 147444 147444
2. Name of Operator Mewbourne Oil Company 3. Address of Operator PO Box 5270, Hobbs NM 88240 4. Well Location Unit Letter P : 1265
3. Address of Operator 10. Pool name or Wildcat Purple Sage; Wolfcamp (Gas) 98220
Purple Sage; Wolfcamp (Gas) 98220
4. Well Location Unit Letter P : 1265
Unit Letter P : 1265
Section 9 Township 24S Range 28E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3016' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK □ PLUG AND ABANDON □ REMEDIAL WORK □ ALTERING CASING □ COMMENCE DRILLING OPNS □ P AND A □ PULL OR ALTER CASING □ MULTIPLE COMPL □ CASING/CEMENT JOB □ CASING/CEMENT JOB □ CASING/CEMENT JOB □ CASING/CEMENT JOB □ OTHER: □ OT
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3016' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK □ PLUG AND ABANDON □ REMEDIAL WORK □ ALTERING CASING □ CHANGE PLANS □ COMMENCE DRILLING OPNS.□ P AND A□ PULL OR ALTER CASING □ MULTIPLE COMPL □ CASING/CEMENT JOB □ CHANGE PLANS □ OTHER: □ 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TDed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB CASING/CEMENT JOB DOWNHOLE COMMINGLE TOTHER: OTHER: TOTHER: T
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A DOWNHOLE CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE TO THER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A DOWNHOLE CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE TO THER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
TEMPORARILY ABANDON
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: DOWNHOLE Completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM OTHER: OTHER: OTHER: OTHER: OTHER: Is Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
CLOSED-LOOP SYSTEM OTHER: OTHER: OTHER: OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
proposed completion or recompletion. 10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
10/15/19 Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
Spud 17 1/2" hole @ 220'. Ran 205' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 250 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
w/1.34 yd. Displaced w/25 bbls FW. Plug down @ 9:15 PM 10/15/19. Circ 84 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 8:15 P.M. 10/16/19, tested csg to 1500# for 30 mins, held OK. FIT to 10.2 PPG EMW. Drilled out with 12 1/4" bit. 10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
10/18/19 TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
TD'ed 12 1/4" hole @ 2816'. Ran 2475' of 9 5/8" 40# HCL80 LT&C Csg. Cemented with 500 sks Lite Class C (35:65:6) w/additives.
Mixed @ 12.9#/g w/ 1.83 vd. Tail w/200 sks Class C Neat Mixed @ 14.8#/g w/1.32 vd. Plug down @ 12:15 PM 10/08/19. Circ. 141 sks
of cmt to the pits. Set Cameron mandrel hanger through BOP w/60k#. At 1:00 A.M. 10/19/19, tested csg to 1500# for 30 mins, held OK.
FIT test to EMW of 10.0 PPG. Drilled out with 8 3/4" bit.
Spud Date: 10/15/2019 Rig Release Date:
/ NB
I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE
Time or maint name Duby Caballara E mail address: rashallara@maybourna.com DUONE: 575 202 5005
Type or print name _Ruby Caballero E-mail address: rcaballero@mewbourne.com PHONE: _575-393-5905 For State Use Only
APPROVED BY: DATE 11/25/19 Conditions of Approval (if any):

. #