RECEMED	
Submit I Copy To Appropriate District State of New Mexico	Form C-103
Office <u>District 1</u> – (575) 393-6161 <u>1625 N. French Dr. Hobbs. NM 88240</u> <u>DEC TO ZUIS</u> <u>Alignetic and Natural Resources</u>	Revised July 18, 2013
District $H = (575)748,1283$	WELL API NO. 30-015-46275
District III – (505) 745-1265 811 S. First St., Artesia, NM 88210 District III – (505) 334-6178 1000 Bia Prance Bd. Actas NM 87410	5. Indicate Type of Lease STATE STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410       Santa Fe, NM 87505         District IV - (505) 476-3460       Santa Fe, NM 87505         1220 S. St. Francis Dr., Santa Fe, NM       Santa Fe, NM 87505	6. State Oil & Gas Lease No. 325165
87505 SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	QUAIL 2 STATE COM
PROPOSALS.)         1. Type of Well: Oil Well X         Gas Well         Other	8. Well Number #725H
2. Name of Operator EOG RESOURCES	9. OGRID Number 7377
3. Address of Operator	10. Pool name or Wildcat
P O BOX 2267, MIDLAND TX 79702	[98220] PURPLE SAGE; WOLFCAMP (GAS
4. Well Location Unit Letter D	
Unit Letter D 600 feet from the North line and 159 Section 02 Township 26E Range 30E	NMPM County EDDY CO
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	
27 S ▲ 7 S ★ 7 S ★ 7 S + S → S → S → S → S → S → S → S → S →	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING	
PULL OR ALTER CASING I MULTIPLE COMPL I CASING/CEMENT JOB I DOWNHOLE COMMINGLE	
OTHER: DRILL CSG Z 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of	
proposed completion or recompletion.	
11/07/19 20" Conductor @ 115' 11/17/19 12-1/4" HOLE Please Spearly Casing TD	
11/17/19 Surface Hole @ 1,187' MD, 1,186' TVD	
Casing shoe @ 1,172' MD Ran 9-5/8" 40# K-55 LTC	
Lead Cement w/ 610 sx Class C (1.76 yld, 13.5 ppg), Trail w/ 90 sx Class C(1.36 yld, 14.8 ppg) Test casing to 1,500 psi for 30 min - good Circ 287 sx cement to surface Resume Drilling 8-3/4" hole	
· · ·	· · · ·
Spud Date: Rig Release Date:	
Spud Date: 11/07/19	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE MULL TITLE Sr. Regulatory Administrator DATE 12/05/19	
Type or print name Emily Follis E-mail address: emily_follis@eogresources.comONE: 432-848-9163	
For State Use Only CC	
APPROVED BY:	DATE 12/12/19
Conditions of Approval (if any):	

-