## RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NMOCD NOV 2 242008sia FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS

5. Lease Serial No. NMNM93468

Do not use this form for proposals to drill or to the enter an abandoned well. Use form 3160-3 (APD) for the High Apple SIAO.C.D.					14/01/4/035400		
					6. If Indian, Allottee of	or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No. NMNM111792		
Type of Well     Oil Well					Well Name and No.     WARBIRD BEO FEDERAL COM 1		
2. Name of Operator Contact: ↑TINA HUERTA EOG Y RESOURCES INC E-Mail: tina_huerta@eogresources.com					9. API Well No. 30-005-63683-0	IO-S1	
3a. Address 105 SOUTH FOURTH STREI ARTESIA, NM 88210	3b. Phone No. (include area code) Ph: 575-748-4168			10. Field and Pool or Exploratory Area HAYSTACK-CISCO			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish,	State .	
Sec 8 T6S R27E NENE 660F				CHAVES COUNTY, NM			
12. CHECK THE A	PPROPRIATE BOX(ES)	TO INDICATE	NATURE O	F NOTICE,	REPORT, OR OTH	IER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
☑ Notice of Intent	☐ Acidize	☐ Deepen		☐ Production	on (Start/Resume)	■ Water Shut-Off	
	☐ Alter Casing	☐ Hydraulic Fracturi		☐ Reclama	•	☐ Well Integrity	
☐ Subsequent Report	□ Casing Repair	■ New Construction		☐ Recompl		Other	
☐ Final Abandonment Notice	☐ Change Plans ☑ Plu		ig and Abandon		rily Abandon		
	Convert to Injection Plu eration: Clearly state all pertinent details, inclu ally or recomplete horizontally, give subsurface		ig Back		sposal		
testing has been completed. Final Abdetermined that the site is ready for final Abdetermined that the site is ready for final EOG Resources, Inc. plans to  1. MIRU all safety equipment 2. Set a CIBP at 6244 ft with 3. Set a CIBP at 5748 ft with 3. Set a CIBP at 5748 ft with 3. Spot a 27 sx Class C ceme 5. Spot a 27 sx Class C ceme 6. Spot a 25 sx Class C ceme 7. Spot a 25 sx Class C ceme 8. Spot a 25 sx Class C ceme 9. Spot a 25 sx Class C ceme 1.	plug and abandon this we as needed. NU BOP. POO 35 ft Class H cement on to 35 ft Class C cement on to nt plug from 5498 ft - 534	ell as follows: OH with product op. op. 4 ft. WQC and to	on equipmen	t. Ac	cepted for record	NMOCD	
14. I hereby certify that the foregoing is true and/correct.					<del></del>		
γomn	utted to AFMS9 for proces	sing by JENNIFE	R SANCHEZ o	n 11/19/2019 (	(20JS0027SE)		
Name(Printed/Typed) TINA/HUERTA			e REGULA	TORY SPEC	CIALIST		
Signature (Electronic St	ubmission)	Dat	e <u>11/19/20</u>	19		;	
	THIS SPACE FOI	R FEDERAL C	R STATE O	FFICEPOY			
Approved By Conditions of approval, if any, are attached	Appropriate the second of the	Tit	le	NOV 2 0	2019	Date	
hich would entitle the applicant to conduc	t operations thereon.	ubject lease Of	fice	LOF LAND I	MANAGEMENT	•	
itle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent of	J.S.C. Section 1212, make it a cratements or representations as to	ine for any person	knowingly and w	SWELL MET	D OF ELD Ement or ag	gency of the United	

(Instructions on page 2)
\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\*

NO NO

## BUREAU OF LAND MANAGEMENT

Roswell Field Office 2909 West Second Street Roswell, New Mexico 88201 (575) 627-0272

## Permanent Abandonment of Production Zone Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from this approval.

If you are unable to plug back the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged back. Failure to do so will result in enforcement action.

- 2. Notification: Contact the BLM Roswell Field Office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, during office hours or after office hours call (575) 627-0205. Engineer on call during office hours phone (575) 627-0237 or phone (after hours) call (575) 626-5871.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Subsequent Plug back Reporting: Within 30 days after plug back work is completed, file one original and three copies of the Subsequent Report, Form 3160-5 to BLM. The report should give in detail the manner in which the plug back work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date work was completed.