Form 3160-5 (Juste 2019)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT DEC 0 3 2019

RECEIVED **OCD Artesia**

FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021

5. Lease Serial No.

NMNM04421

SUNDRY NOTICES AND REPORTS ON WELLS

	orm for proposals to di Use Form 3160-3 (APD)						
SUBMIT IN TRIPLICATE - Other instructions on page 2				I	7. If Unit of CA/Agreement, Name and/or No.		
1. Type of Well					NE Square Lake Unit		
Oil Well Gas Well Other				8.	8. Well Name and No. NE SQ LAKE Prem 21		
2. Name of Operator Trigg Oil and Gas				9.	9. API Well No. 30-015-04837		
			(include area code) 10. Field and Pool or Exploratory Area				
			72		NE Square Lake		
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)				11	11. Country or Parish. State		
1980' FNL 1980' FEL Section 10 T16S-R31E					Eddy, NM		
12. CHE	CK THE APPROPRIATE BOX(E	ES) TO INDICATE	NATURE	OF NOTICE	, REPORT OR OT	HER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
✓ Notice of Intent	Acidize	Deepen		Product	ion (Start/Resume)	Water Shut-Off	
- Notice of Mich	Alter Casing	Hydraulic Fr	acturing	Reclam	ation	Well Integrity	
Subsequent Report	Casing Repair	New Constru	ection	Recomp	olete	Other	
	Change Plans	Plug and Aba	and Abandon Temporarily Abandon				
Final Abandonment Notice	Convert to Injection	Plug Back		Water I	Disposal		
completion of the involved operatic completed. Final Abandonment No is ready for final inspection.) Trigg Oil & Gas proposed to pl Current Perforations: 3672-377 Remove tubing from hole Set CIBP @ 3760* 3 € 2 2 Circulate P&A mud from 9760, 25 sx cement plug 3000*-3760, 25 sx cement plug 1950*-2050, 25 sx cement plug 14400*-1500, 25 sx cement plug 100*-SURF, Install Dry Hole Marker	ons. If the operation results in a m tices must be filed only after all reugand abandon this well as follows. PBTD-3781 (Top fe-f 30 to surface 3 62 2 - (TAG) 3 62 2 - 3 (TAG) 1550 - 144 4 ACE	ultiple completion equirements, included to the second sec	or recompleting reclams	SEE A COND	w interval, a Form 3 cen completed and TTACHE	ust be filed within 30 days following 3160-4 must be filed once testing has been the operator has detennined that the site DFOR DFAPPROVAL From 1846-946 Tag.	
14. I hereby certify that the foregoing is true and correct. Name (<i>Printed/Typed</i>) JJ McGlasson			Agent				
JJ WCGIassori		Title			· · · · · · · · · · · · · · · · · · ·		
Signature	Date	Date 10/22/2019					
	THE SPACE FO	OR FEDERAL	OR STA	ATE OFIC	E USE		
Approved by	ra a. am		کے Title	SPET		Datc //-/6-19	
Conditions of approva, if any, are attac certify that the applicant holds legal or which would entitle the applicant to con	equitable title to those rights in the		Office	150			

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)



North East Square Lake Premier Unit 21 Field: North East Square Lake Lease: NMNM04421 API #30-015-04837 10-16S-31E, Eddy County, NM 1980' FNL & 1980' FEL Tripp Oil & Gas

Formation Tops:

Top Salt

Base Salt

Grayburg

San Andres

Premier

Yates

Queen

Wellbore Status as of:

10/21/19


Spud:

2/2/1961

TD: PBTD: 3/8/1961 3815' 3/8/1961 3781'

AFTER

DRAWING NOT TO SCALE.



Surface Casing:
212'
8-5/8 24# J-55
Cmtd w/ 135 sx
TOC-Unknown
Production Casing:
3815'
4-1/2", 11.6#, J-55, DVT @ 996'
Cmtd w/ STG 1-200sx

Prepared by J McGlasson 10/21/19

Cmtd w/ STG 2-225sx

TOC-SURF-Circ 5 sx

1500

2053

2127

2961

3346

3670

3727

Hole Circulated w/ 9# BW Salt Gel Mud

25sx cmt plug @ 1950-2050

TAGGED

25sx cmt plug @ 3660-3760 — TAGGED CIBP @ 3760

> Perf 3672'-3778' End of Casing @ 3815'

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

- 7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Tinting Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:</u>
From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted