Submit 1 Copy To Appropriate District Office State of New Mexico Office	Form C-103
District I – (575) 393-6161 Energy, Minerals and Natural Resource	ces Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240	WELL API NO.
DEC 57L269NSERVATION DIVISIO	N 30-015-46340
District III = (505) 334-6178	5. Indicate Type of Lease STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87/50RICTI-ARTESIAGARE Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	o. State on & Sus Dease No.
87505	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	Styr 17 WZITITOO ;
PROPOSALS.)	8. Well Number 1H
1. Type of Well: Oil Well Gas Well Other	O OCRUPAL 1 14744
2. Name of Operator Mewbourne Oil Company	9. OGRID Number 14744
3. Address of Operator	10. Pool name or Wildcat
PO Box 5270, Hobbs NM 88241	Purple Sage; Wolfcamp (gas)
	Turpie sage, wondamp (gas)
4. Well Location	
Unit Letter A : 316 feet from the North line and 367	
Section 20 Township 23S Range 2	
11. Elevation (Show whether DR, RKB, RT, C	GR, etc.)
3037' GL	
12. Check Appropriate Box to Indicate Nature of N	Notice, Report or Other Data
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIA	
	ICE DRILLING OPNS. P AND A
=	CEMENT JOB
	SEMENT JOB 🖂
DOWNHOLE COMMINGLE	
CLOSED-LOOP SYSTEM	П
13. Describe proposed or completed operations. (Clearly state all pertinent de	tails, and give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mult	
proposed completion or recompletion.	
11/30/19	·
Spud 17 1/2" hole @ 435'. Ran 420' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with	
w/1.34 yd. Displaced w/59 bbls FW. Plug down @ 1:15 PM 11/30/19. Circ 205 sks	
3500#. At 12:30 P.M. 12/01/19, tested csg to 1500# for 30 mins, held OK. FIT to 1	0.0 PPG EMW. Drilled out with 12 1/4" bit.
12/02/19	
TD'ed 12 1/4" hole @ 2460'. Ran 2443' of 9 5/8" 40# HCL80 LT&C Csg. Cement	ed with 350 sks Lite Class C (50:50:10) w/additives
Mixed @ 11.5#/g w/2.55 yd. Tail w/200 sks Class C Neat. Mixed @ 14.8#/g w/1.32	
cmt to the pits. Set Cameron mandrel hanger through BOP w/100k#. At 9:00 A.M.	
FIT test to EMW of 9.7 PPG. Drilled out with 8 3/4" bit.	
Spud Date: 11/30/19 Rig Release Date:	
I hereby certify that the information above is true and complete to the best of my kr	nowledge and belief.
\bigcirc \bigcirc	
SIGNATURE TITLE Regulatory	DATE12/12/2019
T - 1-11-0-1	ma com DHONE: 575 202 5005
Type or print name _Ruby Caballero E-mail address: _rojeda@mewbou	-
For State Use Only	cc , ,
APPROVED BY:	DATE 12/18/19
Conditions of Approval (if any):	1