

Submit to Appropriate District Office Two Copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised August 1, 2011						
1. WELL API NO. 30-015-45218		2. Type of Lease ☒ STATE ☐ FEE ☐ FED/INDIAN		3. State Oil & Gas Lease No.						
WELL COMPLETION OR RECOMPLETION REPORT AND LOG										
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)				5. Lease Name or Unit Agreement Name WHOMPING WILLOW CC 15-16 STATE COM 6. Well Number: 44H						
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER				9. OGRID 16696						
8. Name of Operator OXY USA Inc.				11. Pool name or Wildcat PURPLE SAGE; WOLFCAMP						
10. Address of Operator P.O. BOX 50250 MIDLAND, TX 79710				12. Location						
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	I	15	24S	29E		1365	SOUTH	420	EAST	EDDY
BH:	M	16	24S	29E		933	SOUTH	20	WEST	EDDY
13. Date Spudded 10/12/18		14. Date T.D. Reached 3/6/19		15. Date Rig Released 4/3/19		16. Date Completed (Ready to Produce) 6/26/19		17. Elevations (DF and RKB, RT, GR, etc.) 2943' GR		
18. Total Measured Depth of Well 21170'M 10844'V				19. Plug Back Measured Depth 20952'M 10843'V		20. Was Directional Survey Made? YES		21. Type Electric and Other Logs Run GR, CBL		
22. Producing Interval(s) of this completion - Top, Bottom, Name 10512-20714' - Purple Sage; Wolfcamp										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
10-3/4"		45.5# J55		455'		14-3/4"		600sx-surf circ.		
7-5/8"		26.4# L80		10445'		9-7/8"		1135sx-surf circ		
5-1/2"		23# P110		21068'		6-3/4"		1500sx-TOC@8150'		
24. LINER RECORD										
SIZE	TOP	BOTTOM		SACKS CEMENT	SCREEN		25. TUBING RECORD			
							SIZE	DEPTH SET	PACKER SET	
							2-7/8"	10464'	10464'	
26. Perforation record (interval, size, and number) 6 SPF @ 20592-20714, 20432-20552, 20272-20392, 20112-20234, 19952-20074, 19792-19912, 19632-19752, 19472-19592, 19312-19434, 19154-19274, 18832-18954, 18672-18792, 18512-18632, 18493-18352, 18192-18312, 18032-18152, 17872-17994, 17712-17832, 17552-17672, 17392-17514, 17232-17352, 17070-17192, 16912-17033, 16752-16872, 16592-16712, 16432-16554, 16272-16392, 16112-16232, 15950-16072, 15792-15912, 15632-15752, 15475-15592, 15313-15432, 15152-15272, 14992-15112, 14832-14952, 14672-14792, 14508-14632, 14352-14472, 14192-14312, 14034-14152, 13872-13992, 13796-13945, 13712-13832, 13550-13672, 13392-13514, 13232-13352, 13075-13192, 12912-13034, 12752-12874, 12592-12714, 12432-12556, 12272-12392, 12112-12232, 11952-12072, 11792-11912, 11634-11752, 11469-11592, 11312-11432, 11152-11272, 10992-11108, 10832-10952, 10672-10792, 10632-10512' Total 1536 holes						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 10512-20714' 940880g Slickwater + 15078798g linear gel + 63798g 7.5% HCl acid w/ 25235770# sand				
28. PRODUCTION										
Date First Production 6/26/19		Production Method (Flowing, gas lift, pumping - Size and type pump) GAS LIFT					Well Status (Prod. or Shut-in) PRODUCING			
Date of Test 7/3/19	Hours Tested 24	Choke Size 59/128	Prod'n For Test Period	Oil - Bbl 1614	Gas - MCF 6966	Water - Bbl. 4005	Gas - Oil Ratio 4316			
Flow Tubing Press:	Casing Pressure 1475	Calculated 24-Hour Rate	Oil - Bbl. 1614	Gas - MCF 6966	Water - Bbl. 4005	Oil Gravity - API - (Corr.)				
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD						30. Test Witnessed By 				
31. List Attachments C103, C104, C102, WBD, Directional Survey, Log										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.										
33. If an on-site burial was used at the well, report the exact location of the on-site burial:										
Latitude					Longitude			NAD 1927 1983		
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief										
Signature 			Printed Name Jana Mendiola			Title Regulatory Specialist			Date 9/23/2019	
E-mail Address janalyn_mendiola@oxy.com										

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE	
Southeastern New Mexico	

Southeastern New Mexico			Northwestern New Mexico	
T. Rustler 250'	T. Canyon		T. Ojo Alamo	T. Penn A"
T. Salado 645'	T. Strawn		T. Kirtland	T. Penn. "B"
T. Castile 1140'	T. Atoka		T. Fruitland	T. Penn. "C"
T. Lamar 3028'	T. Miss		T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian		T. Cliff House	T. Leadville
T. Queen	T. Silurian		T. Menefee	T. Madison
T. Grayburg	T. Montoya		T. Point Lookout	T. Elbert
T. San Andres	T. Simpson		T. Mancos	T. McCracken
T. Glorieta	T. McKee		T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger		Base Greenhorn	T. Granite
T. Blinbry	T. Gr. Wash		T. Dakota	
T. Tubb	T. Delaware Sand		T. Morrison	
T. Drinkard	T. Bone Springs 6723'		T. Todilto	
T. Abo	T. Bell Canyon 3078'		T. Entrada	
T. Wolfcamp 10067'	T. Cherry Canyon 4142'		T. Wingate	
T. Penn	T. Brushy Canyon 5117'		T. Chinle	
T. Cisco (Bough C)	T. 1 st Bone Springs 7765'		T. Permian	
	T. 2 nd Bone Springs 8617'			
	T. 3 rd Bone Springs 9654'			

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 3, from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

ATTACH ADDITIONAL SHEET IF NECESSARY

From	To	Thickness In Feet	Lithology