

300154676

RECEIVED

FEB 21 2020

Submit Original
to Appropriate
Office

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

EMNRD-OCD ARTESIA

GAS CAPTURE PLANDate: 02-26-2019☒ OriginalOperator & OGRID No.: OXY USA INC. - 16696☐ Amended - Reason for Amendment: _____

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below

| Well Name | API | Well Location (ULSTR) | Footages | Expected MCF/D | Flared or Vented | Comments |
|-------------------------------|---------|-----------------------|--------------|----------------|------------------|----------|
| Platinum MDP1 34-3 Fd Com 11H | Pending | C-34-23S-31E | 160 N 1755 W | 2500 | | |
| Platinum MDP1 34-3 Fd Com 12H | Pending | C-34-23S-31E | 160 N 1790 W | 2500 | | |
| Platinum MDP1 34-3 Fd Com 13H | Pending | B-34-23S-31E | 750 N 1480 E | 2500 | | |
| Platinum MDP1 34-3 Fd Com 14H | Pending | B-34-23S-31E | 750 N 1445 E | 2500 | | |
| Platinum MDP1 34-3 Fd Com 21H | Pending | D-34-23S-31E | 580 N 1027 W | 5500 | | |
| Platinum MDP1 34-3 Fd Com 22H | Pending | D-34-23S-31E | 580 N 1062 W | 5500 | | |
| Platinum MDP1 34-3 Fd Com 23H | Pending | C-34-23S-31E | 765 N 2565 W | 5500 | | |
| Platinum MDP1 34-3 Fd Com 24H | Pending | C-34-23S-31E | 765 N 2600 W | 5500 | | |
| Platinum MDP1 34-3 Fd Com 25H | Pending | A-34-23S-31E | 110 N 898 E | 5500 | | |
| Platinum MDP1 34-3 Fd Com 26H | Pending | A-34-23S-31E | 110 N 793 E | 5500 | | |
| Platinum MDP1 34-3 Fd Com 41H | Pending | C-34-23S-31E | 160 N 1530 W | 7200 | | |
| Platinum MDP1 34-3 Fd Com 42H | Pending | C-34-23S-31E | 160 N 1565 W | 7200 | | |
| Platinum MDP1 34-3 Fd Com 43H | Pending | B-34-23S-31E | 230 N 2320 E | 7200 | | |
| Platinum MDP1 34-3 Fd Com 44H | Pending | B-34-23S-31E | 195 N 2320 E | 7200 | | |
| Platinum MDP1 34-3 Fd Com 45H | Pending | A-34-23S-31E | 110 N 863 E | 7200 | | |
| Platinum MDP1 34-3 Fd Com 46H | Pending | A-34-23S-31E | 110 N 828 E | 7200 | | |

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, where a gas transporter system is in place. The gas produced from production facility is dedicated to Enterprise Field Services, LLC ("Enterprise") and is connected to Enterprise low/high pressure gathering system located in Eddy County, New Mexico. OXY USA INC. ("OXY") provides (periodically) to Enterprise a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, OXY and Enterprise have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Enterprise's Processing Plant located in Sec. 36, Twn. 24S, Rng. 30E, Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Enterprise system at that time. Based on current information, it is OXY's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines