Form 3160-5 (June 2015)

### ITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED

FEB 2 1 2020

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5. Lease Serial No. NMNM19186

### **SUNDRY NOTICES AND REPORTS ON WELLS** Do not use this form for proposals to drill or to recenter

abandoned we	II. Use form 3160-3 (APL	) for the North	ded did	AKIES MAI Indian, Allo	ottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No. NMNM113982	
Type of Well     Oil Well				8. Well Name an ARTEMIS FI	d No. EDERAL COM 1	
2. Name of Operator Contact: ADRIAN COVARRUBIAS MARATHON OIL PERMIAN LLC E-Mail: ADRIAN.COVARRUBIAS@ARCADIS.COM				9. API Well No. 30-015-340		
3a. Address 3b. Phone No. 5555 SAN FELIPE ST Ph: 806.75 HOUSTON, TX 77056			ude area code) 53		10. Field and Pool or Exploratory Area DUBLIN RANCH	
4. Location of Well (Footage, Sec., T.	, R., M., or Survey Description)			11. County or Pa	arish, State	
Sec 33 T22S R28E NWSW 1650FSL 660FWL				EDDY COL	JNTY, NM	
12. CHECK THE AF	PROPRIATE BOX(ES)	TO INDICATE 1	ATURE O	F NOTICE, REPORT, OR	OTHER DATA	
TYPE OF SUBMISSION			TYPE OF	ACTION		
■ Notice of Intent  Subsequent Report  Final Abandonment Notice  13. Describe Proposed or Completed Open If the proposal is to deepen directional	☐ Acidize ☐ Alter Casing ☐ Casing Repair ☐ Change Plans ☐ Convert to Injection ration: Clearly state all pertinen	☐ Deepen ☐ Hydrauli ☐ New Cor ☑ Plug and ☐ Plug Bac t details, including.es	struction Abandon k	☐ Production (Start/Resum ☐ Reclamation ☐ Recomplete ☐ Temporarily Abandon ☐ Water Disposal g date of any proposed work and a	☐ Well Integrity ☐ Other	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for file of the complete of th	operations. If the operation restandonment Notices must be file nal inspection.  H. Use Briler. Lear  7-9307 H 8'-7679' class M TAG 100 5x 6155'-5263 60 5x 3580'-3207'  rify. Install DHM.	ults in a multiple cond only after all require  K Test CIB  TAG C  TAG C	APP GEN SPE(	mpletion in a new interval, a Form	1 3160-4 must be filed once etcd and the operator has	
	Electronic Submission #5 For MARATHON mitted to AFMSS for proces	OIL PERMIAN LL ssing by PRISCILI	C, sent to th .A PEREZ on	e Carlsbad ı 02/11/2020 (20PP1199SE)		
Name (Printed/Typed) ADRIAN C	OVARRUBIAS	Title	ENVIRO	NMENTAL ENGINEER		
Signature (Electronic S	ubmission)	Date	02/11/20	020		
	THIS SPACE FO	R FEDERAL O	R STATE (	OFFICE USE		
Approved By Long Vo  Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conduct	. Approval of this notice does notable title to those rights in the s	ot warrant or	15	um Enginees	Date <b>3/14/30</b>	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.





3007 North County Road 1108 P.O Box 2439 Midland, Texas 79702 (432) 458-3780

December 30, 2019

Marathon Oil Permian LLC. 5555 San Felipe St. Houston, TX 77056

## Well Procedure

Artemis Fed Com #1 API: 30-015-34011

- 1. Prep location. Contact New Mexico regulatory
- 2. MIRM NDWH NU BOP POOH w/prod equipment
- 3. Run GR. Set CIBP @ 11,000' w/35'. Must Use Bailer Leak Test CIBP
- 4. TIH to CIBP. Circ w/P&A mud.
- 5. Spot 30 sx @ 9416. 9507' 9307' class H (Wolfcamp @ 9457')
- 6. Spot 30 sx @ 7858'. 7858'-7678' class H TAG (DV Tool @ 7807')
- 7. P&S 50 sx @ 6155-6055. 6155'- 5862' TAG Class ( (Shoe @ 6105' & Bone Sp. @ 5472)

  8. P&S 40 sx @ 2292-2192' TAC 2580'- 2207' TAG Class ( Base ScH@ 2082' & 404'

  9. P&S 120 sx @ 381 -surf & verify. Topof Satt @ 354' Class (
- 10. ND BOP. Remove WH. Install DHM.
- 11. RR. RDMU.

## Marathon Oil

## Wellbore Schematic Well Name: ARTEMIS FEDERAL 1

SIME/Province NEW MEXICO	UNITED STATES	Fied Name DUBLIN RANCH	Lattude (1). 32.34632980	Useg taxie (*) -104.09795150	North/South Distance (tt) 1,660.0	North South Reservate FSL
АЖ РО ИМ 3001534011	(5-Grand Distance (1)	KB-Mod time Distance (f)	Ground Sevation (E) 3,027.00	DriZing Ritg Spud Date	Wei Original Completion Da 8/6/2005	Wat First Production Date 5/3/2012
		ARTEMIS	EDERAL 1, 12/10/201	9 4:55:32 PM		
MD (fike)			Vertical scheit	iatic (actual)	· · · · · · · · · · · · · · · · · · ·	
0.0	*** *** * * * * * * * * * * * * * * *	aliante describe de par : de augus pue per es				
19.0		Maint Transport of Street Area Co.			Casing Joints; 13.375; Surface Casing Cemen	48.00; H40; 19.0-301:0 <sup></sup> t: 19.0-301:0
300.9 -						, , , , , , , , , , , , , , , , , , , ,
370.1				10 8 8.90	T. Salado	م
2,242.1				1	3, Salt Г. Delaware	
2,472:1		<b></b>			Casing Joints; 9.625; 4 ntermediate Casing Ce	0.00; N80; 19.0-8,105.0 ment; 19.0-6,105.0
5,318.9						7.00; P110; 19.0-7,807,0
6,105.0						?
6,290.0				] 	r. Bone Spring	
7,807,1					DV Tool; 5.500; 7,807.0	-7.808.0
7;808.1 -				7	7. 3rd Bone Spring	
8,972.1				(	Production Càsing Cen Casing Joints; 5.500; 1	
9,366.1					0,882.0 . Wolfcamp	
10,799.9				T	: Strawn	
10,881.9						
11,026.9					( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( )	
11,035.1				1	-2; Packer; 4,000; 11,0	27.0; 8.00
11,100.1					-3; Tubing; 2,875; 2,44 . Atoka	0; 11,035.0; 89.00
					. Alona	
11,124.0	11.162 <b>0</b> 41 4	178.0; Perf; Shot Dens:				
11,162:1	(1,102.0-11,10 C	Calculated Shot Total; 1 Phasing:				
11,178.1 -		Linked Zone				
11,294.9	F	Fish; 11,295:0-11,355:0-			,	
11,355.0	,			<b>.</b>	Cement Plug; 11,355.0-	11,390.0
11,390.1	Castlean Bilder	Oliver 14 200 0 44 204 0				
11,391.1	Castiron Bridge)	Plug; 11,390.0-11,391.0-				
11,396,0		12.0; Perf. Shot Dens: alculated Shot Total: 1				
11,412.1		Phasing: Linked Zone		- N	Morrow	
11,704.1				<u>C</u>	: Morrow Casing Joints; 5.500; 28 2,700.0	0.00; P110; 10,882.0-
12,700.1					-1- 2-1-	
www.marathonoi	l.com		Page 1/1		Repo	ort Printed: 12/10/2019

# Marathon Oil

## Post Plugging Wellbore Schematic Well Name: ARTEMIS FEDERAL 1

NEW MEXICO	UNITED STATES	Field Home DUBLIN RANCH	Latindo (*) 32.34632860	(27) -104.09795150	* * .	Kontrusouth Retarence FSL
APV (PO U.VII. 3001534011	19.00 ver han his	Summe deuxe cy	Gramo සිපන්න (ඛ 3,027,00	Dreamy Fig Spool Date	Neil Orginal Completion Date 8/6/2006	Wei Fost Productor:2012 5/3/2012

1001534011	19.000 3,027.00	8/6/2006 5/3/2012				
<del></del>	ARTEMIS FEDERAL 1, 12/10/20					
MD (ftKB).	Vertical schematic (actual)					
<b>6.0</b>	Top Satt @ 354 404'	Marker				
19.0		Casing Joints; 13.375; 48.00; H40; 19.0-301.0				
360.9	Perf. Sqz 120SX @351-Surface Visually Verify (lass C	Seriales classing centering 15.0-301.0				
370.1	Bons & 140 2383/ Polyage @ 352	T: Salado				
2,242.1	Base Salte 2282'/Oclaware @ 2530' Perf. Sqz 40SX @2282'-2192'	B. Sail T. Delaware				
2,472.1	TA G class ( 3580' - 2307'	Casing Joints; 9.625; 40,00; N80; 19.0-6,105.0 Intermediate Casing Cement; 19.0-6,105.0 Casing Joints; 5.500; 17,00; P110; 19.0-7,807.				
5,318.9	3/1//	//1 // 6 85@5472'				
6,105.0	Perf. Sqz. 598X @6155'-6055'	222				
6,290.0	1/14 61377 C	T. Bone Spring				
7,807.1		DV To o1; 6.500; 7,807.0-7,808.0				
7,809.1	c1445 H	T.3rd Bane Spring				
8,972.1	30SX @ 7858' - 7 6 78'	Production Casing Cement; 5,319.0-12,7000 Casing Joints; 5,500; 17.00; P110; 7,808.0-				
9,366,1	TA G	T.Wolfcamp.				
10,799.9 -		T. Strawn				
10,881.9	c lags H 305X @9416'	(wc@9497')				
.11,026.9 -	9507'-4307'	1-2; Packer; 4.000; 11,027.0; 8.00				
11,035.1	Must use Bailer, Leak Test (16P	1-3; Tubing; 2.875; 2.440; 11,036.0; 89.00				
11,100.1	II,II a	T. Aloka				
11,124.0	CIBP @ 11,000 w/35' of Class H					
11,162.1	11,162.0-11,178.0; Perf; Shot Dens: Calculated Shot Total: 1 Phasing:					
11,176,1 -	Linked Zone:					
11,294.9 -	Fish; 11,295.0-11,355,0					
11,355,0		Cement Plug; 11,355,0-11,390,0				
14 <b>,390</b> .1 -	Cast fron Bridge Plug; 11,390.0-11,391.0-					
1,1,391.1 -		<u>-</u> -₩				
11,396.0	11,396.0-11,417.0; Perf; Shot Dens: Calculated Shot Totak 1 Phasing:					
11,412:1	Linked Zone;	T:Norrow				
11,704.1 -		Casing Joints; 5,500; 20,00; P110; 10,882,0.				
12,700.1						

# BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 575-234-5972

## Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



## United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

### Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias
Environmental Protection Specialist
575-234-6230

Henryetta Price Environmental Protection Specialist 575-234-5951

Shelly Tucker Environmental Protection Specialist 575-234-5979

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612