Office District I	State of New Mexico		Form C-103	
1/05/17 77 17 17 17 17 17 17 17 17 17 17 17 1	Licizy, wind i tatalal resources		May 27, 2004	
1625 N. French Dr., Hobbs, NM 87240			WELL API NO. 30-015-34800	
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		5. Indicate Type of Lease	
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Fra Santa Fe, NM 8		STATE	FEE 🕱
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	•	7303	6. State Oil & Gas Le	ase No.
			7 7 1 11 11	. A
I (DO NOT USE THIS FORM FOR PROPO		OR PLUG BACK TO A	7. Lease Name or Uni	t Agreement Name:
DIFFERENT RESERVOIR. USE "APPLIC PROPOSALS.)	ATION FOR PERMIT" (FORM C-10	1) FOR SUCH	Seine C 6 Fee	
1. Type of Well:	18		8. Well Number	
Oil Well Gas Well	Other O		2H	
2. Name of Operator	10 CD CO	C. 2000	9. OGRID Number	
EOG Resources Inc.	Ag.	SES .	7377	
3. Address of Operator	· · · · · · · · · · · · · · · · · · ·	S/D	10. Pool name or Wil	
P.O. Box 2267 Midland, Text 4. Well Location	as 79702	7 3/	Cottonwood <u>. Creek</u>	: WC, West (Gas)
4. Well Location				
Unit Letter:	2440 feet from the So	line and	215 feet from the	ne <u>East</u> line
Section 6	Township 16S	Range 25E	NMPM (County Eddy
	11. Elevation (Show whether			
A Company		518 GR		estate in a second of the seco
Pit or Below-grade Tank Application	or Closure			
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water				
Pit Liner Thickness: mil	Below-Grade Tank: Volume	bbls; Construction	on Material	
12 Charle A	appropriate Box to Indicate	Noture of Notice	Donart or Other D	oto
			•	
NOTICE OF INTE		REMEDIAL WORK	SEQUENT REPO	
TEMPORARILY ABANDON				ALTERING CASING
TEINIFORANIET ABANDON	CHANGE PLANS	COMMENCE DRILL		PLUG AND
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB		
OTHER:				
	<u> </u>	OTHER: complet		X
Describe proposed or completed		rtinent details, and give		
of starting any proposed work).	SEE RULE 1103. For Multiple			
	SEE RULE 1103. For Multiple			
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls	s slick water, 193500 lbs	e Completions: Attach	wellbore diagram of pr	oposed completion
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66	s slick water, 193500 lbs 650' to 7300', 0.54", 36 b	30/70 Brown sand,	wellbore diagram of pr	oposed completion
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls	s slick water, 193500 lbs 650' to 7300', 0.54", 36 b s slick water, 169500 lbs	30/70 Brown sand, noles. 30/70 Brown sand,	wellbore diagram of pr	oposed completion
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 50	s slick water, 193500 lbs 650' to 7300', 0.54", 36 b s slick water, 169500 lbs 050' to 6000', 0.54", 36 b	30/70 Brown sand, coles. 30/70 Brown sand, coles.	wellbore diagram of pr 273200 lbs 20/40 wt 285500 lbs 20/40 wt	oposed completion ite sand.
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 50	s slick water, 193500 lbs 650' to 7300', 0.54", 36 b s slick water, 169500 lbs 050' to 6000', 0.54", 36 b s slick water, 253400 lbs	30/70 Brown sand, coles. 30/70 Brown sand, coles.	wellbore diagram of pr 273200 lbs 20/40 wt 285500 lbs 20/40 wt	oposed completion ite sand.
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 50 Frac w/ 8720 bbls	s slick water, 193500 lbs 650' to 7300', 0.54", 36 h s slick water, 169500 lbs 050' to 6000', 0.54", 36 h s slick water, 253400 lbs an up.	30/70 Brown sand, coles. 30/70 Brown sand, coles.	wellbore diagram of pr 273200 lbs 20/40 wt 285500 lbs 20/40 wt	oposed completion ite sand.
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 56 Frac w/ 8720 bbls 8/24/06 Flow back to clea	s slick water, 193500 lbs 650' to 7300', 0.54", 36 h s slick water, 169500 lbs 050' to 6000', 0.54", 36 h s slick water, 253400 lbs an up.	30/70 Brown sand, coles. 30/70 Brown sand, coles.	wellbore diagram of pr 273200 lbs 20/40 wt 285500 lbs 20/40 wt	oposed completion ite sand.
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 50 Frac w/ 8720 bbls 8/24/06 Flow back to cles 8/26/06 RIH to drill out	s slick water, 193500 lbs 650' to 7300', 0.54", 36 h s slick water, 169500 lbs 050' to 6000', 0.54", 36 h s slick water, 253400 lbs an up. frac plugs & clean cut.	30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand,	273200 lbs 20/40 Wh 285500 lbs 20/40 Wh 262500 lbs 20/40 Wh	oposed completion ite sand. ite sand. ite sand.
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 50 Frac w/ 8720 bbls 8/24/06 Flow back to clea 8/26/06 RIH to drill out I hereby certify that the information all grade tank has been/will be constructed or c	s slick water, 193500 lbs 650' to 7300', 0.54", 36 h s slick water, 169500 lbs 050' to 6000', 0.54", 36 h s slick water, 253400 lbs an up. frac plugs & clean cut. bove is true and complete to the	30/70 Brown sand, soles. 30/70 Brown sand, soles. 30/70 Brown sand, soles. 30/70 Brown sand,	wellbore diagram of pr 273200 lbs 20/40 Wh 285500 lbs 20/40 Wh 262500 lbs 20/40 Wh and belief. I further cert or an (attached) alternate	oposed completion ite sand. ite sand. ify that any pit or belowive OCD-approved plan
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 50 Frac w/ 8720 bbls 8/24/06 Flow back to cles 8/26/06 RIH to drill out	s slick water, 193500 lbs 650' to 7300', 0.54", 36 h s slick water, 169500 lbs 050' to 6000', 0.54", 36 h s slick water, 253400 lbs an up. frac plugs & clean cut. bove is true and complete to the losed according to NMOCD guideline	30/70 Brown sand, soles. 30/70 Brown sand, soles. 30/70 Brown sand, soles. 30/70 Brown sand,	273200 lbs 20/40 Wh 285500 lbs 20/40 Wh 262500 lbs 20/40 Wh	oposed completion ite sand. ite sand. ify that any pit or belowive OCD-approved plan
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 50 Frac w/ 8720 bbls 8/24/06 Flow back to clea 8/26/06 RIH to drill out I hereby certify that the information all grade tank has been/will be constructed or c	s slick water, 193500 lbs 650' to 7300', 0.54", 36 h s slick water, 169500 lbs 050' to 6000', 0.54", 36 h s slick water, 253400 lbs an up. frac plugs & clean cut. bove is true and complete to the losed according to NMOCD guideline	a Completions: Attach 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, Example 1 Brown sand, Example 2 Brown sand, Example 2 Brown sand, Example 3 Brown sand, Example 3 Brown sand, Example 4 Brown sand, Example 4 Brown sand, Example 5 Brown sand, Example 5 Brown sand, Example 6 Brown sand, Example 6 Brown sand, Example 7 Brown sand, Example 7 Brown sand, Example 8 Brow	273200 lbs 20/40 Who 285500 lbs 20/40 Who 262500 lbs 20/40 Who 262500 lbs 20/40 Who e and belief. I further cert or an (attached) alternately Analyst DA	oposed completion ite sand. ite sand. ify that any pit or belowive OCD-approved plan
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 56 Frac w/ 8720 bbls 8/24/06 Flow back to clee 8/26/06 RIH to drill cut I hereby certify that the information al grade tank has been/will be constructed or c SIGNATURE Type or print name Stan Wagner	s slick water, 193500 lbs 650' to 7300', 0.54", 36 h s slick water, 169500 lbs 050' to 6000', 0.54", 36 h s slick water, 253400 lbs an up. frac plugs & clean cut. bove is true and complete to the losed according to NMOCD guideline	a Completions: Attach 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, Example 1 Brown sand, Example 2 Brown sand, Example 2 Brown sand, Example 3 Brown sand, Example 3 Brown sand, Example 4 Brown sand, Example 4 Brown sand, Example 5 Brown sand, Example 5 Brown sand, Example 6 Brown sand, Example 6 Brown sand, Example 7 Brown sand, Example 7 Brown sand, Example 8 Brow	273200 lbs 20/40 Who 285500 lbs 20/40 Who 262500 lbs 20/40 Who 262500 lbs 20/40 Who e and belief. I further cert or an (attached) alternately Analyst DA	oposed completion Lite sand.
of starting any proposed work). or recompletion. 8/22/06 Frac w/ 5117 bbls Perforate from 66 8/23/06 Frac w/ 8709 bbls Perforate from 50 Frac w/ 8720 bbls 8/24/06 Flow back to cles 8/26/06 RIH to drill out I hereby certify that the information al grade tank has been/will be constructed or c SIGNATURE Type or print name Stan Wagner	s slick water, 193500 lbs 550' to 7300', 0.54", 36 h s slick water, 169500 lbs 050' to 6000', 0.54", 36 h s slick water, 253400 lbs an up. frac plugs & clean cut. bove is true and complete to the losed according to NMOCD guideline TIT E-I RECORDS ONLY	a Completions: Attach 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, coles. 30/70 Brown sand, Example 1 Brown sand, Example 2 Brown sand, Example 2 Brown sand, Example 3 Brown sand, Example 3 Brown sand, Example 4 Brown sand, Example 4 Brown sand, Example 5 Brown sand, Example 5 Brown sand, Example 6 Brown sand, Example 6 Brown sand, Example 7 Brown sand, Example 7 Brown sand, Example 8 Brow	wellbore diagram of pr 273200 lbs 20/40 Wr 285500 lbs 20/40 Wr 262500 lbs 20/40 Wr and belief. I further cert or an (attached) alternative Analyst Telephore	ite sand. ite sand. ite sand. ite sand. ify that any pit or belowive OCD-approved plan ATE 8/30/06 ae No. 432 686 3689

Conditions of Approval, if any: