

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.  
30-015-32813

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
B-8617-1

7. Lease Name or Unit Agreement Name:  
Spurck 16 State Cm

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:  
Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator  
Yates Drilling Company

3. Address of Operator  
105 South 4<sup>th</sup> St., Artesia, NM 88210

8. Well No.  
2

9. Pool name or Wildcat  
Morrow

4. Well Location

Unit Letter K : 1980 feet from the S line and 1980 feet from the W line

Section 16 Township 17S Range 28E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3559'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/14/2003 TD 10,081'. Ran 236 jts. 5 1/2" csg, set at 10,081', as follows:

49 jts. 5 1/2" 17# L-80 (2076.96')

41 jts. 5 1/2" 17# J-55 (1737.74')

110 jts. 5 1/2" 15.5# J-55 (4763.13')

25 jts. 5 1/2" 17# J-55 (118.69')

11 jts. 5 1/2" 17# L-80 (387.55')

Regular guide shoe set at 10,081'. Float collar set at 10,042.57'. Cemented w/ 1635 sxs 15:61:11 + 1% BA-10 + 5% salt + 2# LCM + 6% FL-52 + 3% SM with 250 bbls nitrified mud (yld 1.64, wt 13.2).

PD at 12:30 PM, 7/15/2003. Bumped plug to 3100 psi for 5 minutes. Float and casing held ok.

Rig released at 8:00 PM, 7/15/2003.

NOTE: Centralizers on jts. 1,9,18,27,36,45,54,63,72,81,90,108,117,126,135,144,153,162,171.

Waiting on completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Karen J. Leishman TITLE Engineering Tech. DATE 8/18/2003

Type or print name Karen J. Leishman Telephone No. 505-748-8463

(This space for State use)

APPROVED BY FOR RECORDS ONLY TITLE

DATE AUG 22 2003

Conditions of approval, if any: