3 Copies To Appropriate District State of New Mexico Form C-103 Energy, Minerals and Natural Resources May 27, 2004 WELL API NO. 25 N. French Dr., Hobbs, NM 88240 District II 30-015-35047 OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease 220 South St. Francis Dr. District III STATE 🛛 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. 1220 S. St. Francis Dr., Santa Fe, NM 87505 VO-6515 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH Draw BJL State PROPOSALS.) 8. Well Number 1. Type of Well: Oil Well Gas Well Month - Year 2. Name of Operator 9. OGRID Number MAR - 9 2007 Yates Petroleum Corporation 025575 OCD - ARTESIA, NM 3. Address of Operator 10. Pool name or Wildcat 105 S. 4th Street, Artesia, NM 88210 Brushy Draw; Delaware, North 4. Well Location Unit Letter 2310 feet from the South line and 2310 feet from the West line Section 36 Township 25S Range 29E **NMPM** Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3052'GR Pit or Below-grade Tank Application or Closure Depth to Groundwater _____ Distance from nearest fresh water well _ Distance from nearest surface water Pit Liner Thickness: Below-Grade Tank: Volume bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK □ PLUG AND ABANDON □ REMEDIAL WORK ALTERING CASING □ **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS.□ PLUG AND ABANDON □ PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB OTHER: Plugback and recomplete OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 2/16/07 - Set a composite bridge plug at 8994'. Perforate Delaware 6836'-6846' (11), 6858'-6864' (7), 7006'-7010' (5) and 7024'-7036' (13). Acidize Delaware 7006'-7036' with 750g 7-1/2% IC acid and 27 balls. Acidize Delaware 6836'-6864' with 750g 7-1/2% IC acid and 27 balls. 2/19/07 - Perforate Delaware 5602'-5606' (5), 5724'-5728' (5) and 5734'-5740' (7). Acidize Delaware 5724'-5740' with 1000g 7-1/2% IC acid. Acidize Delaware 5602'-5606' with 250g 7-1/2% IC acid. SN at 7131'. 2-7/8" tubing at 7170'. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines _, a general permit _ or an (attached) alternative OCD-approved plan _.