## Eom 3160-5 (April 2004)

## OCD-AKTESIA UNITED STATES DEPARTMENT OF THE INTERIOR PUREAL OF LAND MANAGEMENT

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007

`	DIDDLILOPT LND MAN	ACEMENT			Expires: 11M et 31, 2007	
. \	BUREAU OF LAND MAN NOTICES AND REF		LIC	5. Lease Seria NM-3846		
Do not use th	nis form for proposals t ell. Use Form 3160-3 (A			6. If Indian,	, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE- Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No.  8. Well Name and No. Pure Gold "A" Federal #8  9. API Well No.	
1. Type of Well Gas Well Other						
2. Name of Operator Pogo Producing Company						
3a Address 3b. Phone No. (include area code)				30-015-35296  10. Field and Pool, or Exploratory Area Sand Dunes De laware West		
P.O. Box 10340, Midland, TX 79702-7340 432-685-8100  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)						
1860' FNL & 1980' FWL			LE OF NOTICE, RI	Eddy Co	or Parish, State unty, NM OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent  Subsequent Report  Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Star Reclamation Recomplete Temporarily Abe		Water Shut-Off Well Integrity Spud	
Attach the Bond under which the following completion of the inv	ectionally or recomplete horizontally the work will be performed or provi- volved operations. If the operation that Abandonment Notices shall be	y, give subsurface locatio de the Bond No. on file v results in a multiple comp	ns and measured and true with BLM/BIA. Require eletion or recompletion in	vertical depth d subsequent re a new interval	s of all pertinent markers and zones. eports shall be filed within 30 days , a Form 3160-4 shall be filed once	

Spud & Set Surface Csg – MIRU Capstar #14. Spud well @ 06:00 hrs 02/10/07. Drld 17-1/2" hole to 687'. TD reached @ 06:00 hrs 02/12/07. Ran 16 jts 13-3/8" 48# H-40 ST&C csg. Cmt'd w/ 450 sks 35:65 Cl C + 2% CaCl2 @ 12.8 ppg followed by 200 sks Cl "C" + 2% CaCl2 @ 14.8 ppg. Circ 211 sks to surface. Plug down @ 20:30 hrs 02/12/07. WOC 24 hrs. Make cut-off. Weld on WH. NU BOP's & test to 800# for 30 mins ok.

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)					
Cathy Wright	Title Sr. Eng Tech				
Signature Coll Wellt	Date 02/21/07	ACCEPTED FOR RECOR			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by	Title	MAR 1 2 2007			
Conditions of approval, if any, are attached. Approval of this notice does not warran certify that the applicant holds legal or equitable title to those rights in the subject lea which would entitle the applicant to conduct operations thereon.	1	WESLEY W. INGRAM PETROLEUM ENGINEER			
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any States any false, fictitious or fraudulent statements or representations as to any matter	person knowingly and willfully to within its jurisdiction.				

(Instructions on page 2)