Submit 3 Copies Total List District State of New Mexico Office	Form C-103
District I Energy, Minerals and Natural Resources 1625 N. French Dr. 188240	May 27, 2004 WELL API NO.
District II	30-005-61862
District III 1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe NM 87505	STATE FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	o. State Off & Gas Lease No.
87505	V-134
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	Fox WG State
1. Type of Well: Oil Well Gas Well Other O	8. Well Number
2. Name of Operator Yates Petroleum Corporation	9. OGRID Number
Yates Petroleum Corporation	025575
3. Address of Operator 105 S. 4 th Street, Artesia, NM 88210	10. Pool name or Wildcat Pecos Slope; Abo
4. Well Location	
	660 feet from the West line
Section 17 Township 8S Range 27E 11. Elevation (Show whether DR, RKB, RT, GR, etc.)	NMPM Chaves County
4008' GR	
Pit or Below-grade Tank Application or Closure	
Pit type Depth to Groundwater Distance from nearest fresh water well Dis	tance from nearest surface water
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Co	nstruction Material
12. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Data
NOTICE OF INTENTION TO: SUBS	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ REMEDIAL WORK	
TEMPORARILY ABANDON	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT	JOB
OTHER: OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and	
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Att	ach wellbore diagram of proposed completion
or recompletion.	
Yates Petroleum Corporation plans to plug and abandon this well as follows:	
1. Rig up safety equipment as needed. No casing recovery will be attempted.	
2. Spot a 25 sx Class "C" cement plug from 4736'-4900'. This puts 164' plug across the A	bo perforations. WOC and tag plug.
3. Spot a 25 sx Class "C" cement plug from 2548'-2648'. This puts 100' plug across the to	p of the Glorieta. WOC and tag plug.
4. Spot a 25 sx Class "C" cement plug from 1150'-1250'. This puts 100' plug across the su 5. Perforate at 60' and circulate a 20 sx Class "C" cement plug from 60' up to the surface, i	
6. Remove all surface equipment, weld dry hole marker and clean location as per regulation	
NOTE: Yates Petroleum Corporation will use steel pits and no earth pits	
The 12. Three I consider the components with the control of the co	
I hereby certify that the information above is true and complete to the best of my knowledge	and helief I further certify that any nit or below.
grade tank has been/will be constructed or closed according to NMOCD guidelines [], a general permit []	
SIGNATURE (Line) TITLE Regulatory Compliance	Supervisor DATE March 27, 2007
Type or print name Tina Huerta E-mail address: tinah@ypcnm.co	om Telephone No505-748-1471
For State Use Only	200000000000000000000000000000000000000
APPROVED BY: Mittaken TITLE 4.	
ALERUVERIBY: / 'W /\ //W// IIILE '(M.	DATE M. 4. 1 19 A1
Conditions of Approval (if any):	DATH/Oceh 29 07

OCATION: 660' FNL				
GL: 4007.3' GR PUD DATE: 11/30/82			CASING PROGR	RAM
OMMENTS:			8-5/8" 40.5#	1,200
			4.4/0" 0.5#	5,578
			4-1/2 " 9.5#	3,070
12 1/4" Hole		TOC @ 880' 8-5/8" @ 1,200' w/ 700 sx cmt (circ)	Tops: San Andres 405' Glorieta 2598' Abo 4,786'	
7 7/8" Hole	\\	66'-2,378' (squeezed w	150 sxs)	
	4-1 Sta	o perfs: 4,941'-5,188' (2 1/2" @ 5,578' age 1: 500 sx (circ) age 2: 1000 sx	No. 1/3	ot to Scale 80/07 MFH

	haves Co., NM	
GL: 4007.3' GR ZERO: KB:	CASING PROGRAM	
SPUD DATE: 11/30/82 COMPLETION DATE: 2/11/83		
COMMENTS:	8-5/8" 40.5#	1,200
		5,578
	4-1/2" 9.5#	3,37
20 sx cmt plug 60' to surface, inside and outside		
casing		
	}	
12 1/4" Hole	A G	
	After	
) \ / \ \ (\ \ TOC @ 880'		
3" @ 1,200' \\ \\		
00 sx cmt (circ) 25 sx cmt plug 1,150'-1,250'	Tops:	7
	San Andres 405'	
	Glorieta 2598'	
	Abo 4,786'	
2,366'-2,378' (squeezed w 150 s	eve)	
() 2,000 2,070 (0qd0020d W 100 t	5,00	
DV tool @ 2,620' 25 sx cmt plug 2,548'-2,648'	—–––	
DV tool @ 2,620' 25 sx cmt plug 2,548'-2,648'		
7.700.44		
7 7/8" Hole		
25 sx cmt plug 4,736'-4900' (164	4')	
), // /		
Abo perfs: 4,941'-5,188' (20)		
// / /		
\\	Not to S	Scale
>/	1/30/07	- 3 51. 5
4-1/2" @ 5,578' Stage 1: 500 sx (circ)	MMFH	
Stane I built by force		