


District II
1301 W. Grand Ave., Artesia, NM 88210
Phone:(505) 748-1283 Fax:(505) 748-9720

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-101
Permit 53531



APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator Name and Address EOG RESOURCES INC P.O. Box 2267 Midland, TX 79702		2. OGRID Number 7377
		3. API Number 30-015-35611
4. Property Code 35612	5. Property Name SEINE B 6 FEE	6. Well No. 001H

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
H	6	16S	25E	16	2910	S	255	E	EDDY

8. Pool Information

COTTONWOOD CREEK;WC, WEST (GAS)	75260
---------------------------------	-------

Additional Well Information

9. Work Type New Well	10. Well Type GAS	11. Cable/Rotary	12. Lease Type Private	13. Ground Level Elevation 3521
14. Multiple N	15. Proposed Depth 5200	16. Formation Wolfcamp	17. Contractor	18. Spud Date
Depth to Ground water 50		Distance from nearest fresh water well 400		Distance to nearest surface water 400
Pit: Liner: Synthetic ☒ 12" mils thick Clay ☐ Pit Volume: 10000 bbls Drilling Method: Closed Loop System ☐ Fresh Water ☒ Brine ☐ Diesel/Oil-based ☐ Gas/Air ☐				

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	12.25	8.625	32	950	450	0
Prod	7.875	5.5	17	9263	820	0

Casing/Cement Program: Additional Comments

--

Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

I further certify that the drilling pit will be constructed according to NMOCD guidelines ☒, a general permit ☐, or an (attached) alternative OCD-approved plan ☐.

Printed Name: Donny G. Glanton

Title: SR. LEASE OPERATIONS REP

Email Address: donny.glanton@eogresources.com

Date: 5/14/07

Phone: 432-686-3642


OIL CONSERVATION DIVISION

Approved By: BRYAN G. ARANT
DISTRICT II GEOLOGIST

Approved Date: MAY 16 2007 Expiration Date: MAY 16 2008

See Conditions of Approval

NEW MEXICO SINGLE HORSESHOE RESERVE PIT DESIGN



Approximate Volume: 10,000 barrels

Scale: 1" = 20'

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised October 12, 2005
Submit to Appropriate District Office
State Lease- 4 Copies
Fee Lease- 3 Copies

☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 30-015- 3	Pool Code 75260	Pool Name Cottonwood Creek; WC West (Gas)
Property Code 35612	Property Name SEINE B 6 FEE	Well Number 1H
GRID No. 7377	Operator Name EOG RESOURCES, INC.	Elevation 3521'

Surface Location


UL or lot no.	Section	Township	Range	Lot Km	Feet from the	North/South line	Feet from the	East/West line	County
16	6	16 SOUTH	25 EAST, N.M.P.M.		2910	SOUTH	255	EAST	EDDY

Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Km	Feet from the	North/South line	Feet from the	East/West line	County
13	6	16 SOUTH	25 EAST, N.M.P.M.		3400	SOUTH	660	WEST	EDDY

Dedicated Acres 319.52	Joint or Infill	Consolidation Code	Order No.
---------------------------	-----------------	--------------------	-----------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Donny G. Glanton 6/8/06
Signature Date

Donny G. Glanton
Printed Name

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same are true and correct to the best of my belief.

Date of Survey 15079
Signature and Seal of Professional Surveyor:
Samuel J. Chalk
Certificate Number 15079

WO# 060330WL-C2 (LA)

Permit Information:

Well Name: Seine B 6 Fee #1H

Location:

SL 2,910' FSL & 235' FEL, Section 6, T-16-S, R-25-E, Eddy Co., N.M.

BHL 3,400' FSL & 660' FWL, Section 6, T-16-S, R-25-E, Eddy Co., N.M.

Casing Program:

Casing	Setting Depth	Hole Size	Casing Size	Casing Weight	Casing Grade	Desired TOC
Surface	950'	12-1/4"	8-5/8"	32#	J-55	Surface
Production	9,263'	7-7/8"	5-1/2"	17#	N-80	Surface

Cement Program:

Depth	No. Sacks	Slurries:
950'	200	Lead: Premium Plus + 2% CaCl ₂ + 3% Econolite + ¼ pps Flocele
	250	Tail: Premium Plus + 2% CaCl ₂ + ¼ pps Flocele
9,263'	460	Lead: Interfill C + ¼ pps Flocele
	360	Tail: Premium Cement + 100% Acid Soluble Additive + 0.6% Halad®-344 + 0.8% Econolite + 0.2% HR-55

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 – 950'	Fresh - Gel	8.6-8.8	28-34	N/c
950' – 4,400'	Cut Brine	8.8-9.2	28-34	N/c
4,400' – 5,100'	Cut Brine	8.8-9.2	28-34	10-15
4,342' – 9,263'	Polymer (Lateral)	9.0-9.4	40-45	10-25

EOG - Midland (3)

Thames

Seine B 6 Fee #1H

Seine B 6 Fee #1H

Seine B 6 Fee #1H

Plan: Plan #1 041706

Standard Planning Report

17 April, 2006

Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well Seine B 6 Fee #1H
Company:	EOG - Midland (3)	TVD Reference:	WELL @ 3539.0ft (Original Well Elev)
Project:	Thames	MD Reference:	WELL @ 3539.0ft (Original Well Elev)
Site:	Seine B 6 Fee #1H	North Reference:	Grid
Well:	Seine B 6 Fee #1H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Seine B 6 Fee #1H		
Design:	Plan #1 041706		

Project:	Thames		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site:	Seine B 6 Fee #1H				
Site Position:		Northing:	710,403.10 ft	Latitude:	32° 57' 10.213 N
From:	Map	Easting:	443,827.70 ft	Longitude:	104° 30' 59.242 W
Position Uncertainty:	0.0 ft	Slot Radius:	"	Grid Convergence:	-0.10 °

Well:	Seine B 6 Fee #1H					
Well Position	+N/-S	0.0 ft	Northing:	710,403.10 ft	Latitude:	32° 57' 10.213 N
	+E/-W	0.0 ft	Easting:	443,827.70 ft	Longitude:	104° 30' 59.242 W
Position Uncertainty		0.0 ft	Wellhead Elevation:	ft	Ground Level:	3,521.0 ft

Wellbore:	Seine B 6 Fee #1H				
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength
	IGRF2005	4/17/2006	(°)	(°)	(nT)
			8.66	60.80	49,448

Design:	Plan #1 041706			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction
	(ft)	(ft)	(ft)	(°)
	0.0	0.0	0.0	277.00

Plan Sections										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Bulk Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	--
4,342.2	0.00	0.00	4,342.2	0.0	0.0	0.00	0.00	0.00	0.00	
4,800.7	68.78	343.38	4,698.3	233.5	-69.7	15.00	15.00	0.00	343.38	
4,800.8	68.78	343.38	4,698.3	233.6	-69.7	0.00	0.00	0.00	0.00	
5,285.3	90.00	272.00	4,800.0	494.4	-425.5	15.00	4.38	-14.73	-83.05	Entry Point B1
5,330.0	90.00	270.66	4,800.0	495.4	-470.2	3.00	0.00	-3.00	-90.00	
9,263.2	90.00	270.66	4,800.0	540.7	-4,403.1	0.00	0.00	0.00	0.00	PBHL Seine B 6 Fee :

Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well Seine B 6 Fee #1H
Company:	EOG - Midland (3)	TVD Reference:	WELL @ 3539.0ft (Original Well Elev)
Project:	Thames	MD Reference:	WELL @ 3539.0ft (Original Well Elev)
Site:	Seine B 6 Fee #1H	North Reference:	Grid
Well:	Seine B 6 Fee #1H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Seine B 6 Fee #1H		
Design:	Plan #1 041706		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	0.00	0.00	2,100.0	0.0	0.0	0.0	0.00	0.00	0.00
2,200.0	0.00	0.00	2,200.0	0.0	0.0	0.0	0.00	0.00	0.00
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.0	0.00	0.00	0.00
2,400.0	0.00	0.00	2,400.0	0.0	0.0	0.0	0.00	0.00	0.00
2,500.0	0.00	0.00	2,500.0	0.0	0.0	0.0	0.00	0.00	0.00
2,600.0	0.00	0.00	2,600.0	0.0	0.0	0.0	0.00	0.00	0.00
2,700.0	0.00	0.00	2,700.0	0.0	0.0	0.0	0.00	0.00	0.00
2,800.0	0.00	0.00	2,800.0	0.0	0.0	0.0	0.00	0.00	0.00
2,900.0	0.00	0.00	2,900.0	0.0	0.0	0.0	0.00	0.00	0.00
3,000.0	0.00	0.00	3,000.0	0.0	0.0	0.0	0.00	0.00	0.00
3,100.0	0.00	0.00	3,100.0	0.0	0.0	0.0	0.00	0.00	0.00
3,200.0	0.00	0.00	3,200.0	0.0	0.0	0.0	0.00	0.00	0.00
3,300.0	0.00	0.00	3,300.0	0.0	0.0	0.0	0.00	0.00	0.00
3,400.0	0.00	0.00	3,400.0	0.0	0.0	0.0	0.00	0.00	0.00
3,500.0	0.00	0.00	3,500.0	0.0	0.0	0.0	0.00	0.00	0.00
3,600.0	0.00	0.00	3,600.0	0.0	0.0	0.0	0.00	0.00	0.00
3,700.0	0.00	0.00	3,700.0	0.0	0.0	0.0	0.00	0.00	0.00
3,800.0	0.00	0.00	3,800.0	0.0	0.0	0.0	0.00	0.00	0.00
3,900.0	0.00	0.00	3,900.0	0.0	0.0	0.0	0.00	0.00	0.00
4,000.0	0.00	0.00	4,000.0	0.0	0.0	0.0	0.00	0.00	0.00
4,100.0	0.00	0.00	4,100.0	0.0	0.0	0.0	0.00	0.00	0.00
4,200.0	0.00	0.00	4,200.0	0.0	0.0	0.0	0.00	0.00	0.00
4,300.0	0.00	0.00	4,300.0	0.0	0.0	0.0	0.00	0.00	0.00
4,342.2	0.00	0.00	4,342.2	0.0	0.0	0.0	0.00	0.00	0.00
4,350.0	1.17	343.38	4,350.0	0.1	0.0	0.0	15.00	15.00	0.00
4,375.0	4.92	343.38	4,375.0	1.3	-0.4	0.6	15.00	15.00	0.00
4,400.0	8.67	343.38	4,399.8	4.2	-1.2	1.7	15.00	15.00	0.00
4,425.0	12.42	343.38	4,424.4	8.6	-2.6	3.6	15.00	15.00	0.00
4,450.0	16.17	343.38	4,448.6	14.5	-4.3	6.1	15.00	15.00	0.00
4,475.0	19.92	343.38	4,472.3	21.9	-6.5	9.2	15.00	15.00	0.00
4,500.0	23.67	343.38	4,495.5	30.8	-9.2	12.9	15.00	15.00	0.00
4,525.0	27.42	343.38	4,518.1	41.1	-12.3	17.2	15.00	15.00	0.00
4,550.0	31.17	343.38	4,539.9	52.8	-15.8	22.1	15.00	15.00	0.00

Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well Seine B 6 Fee #1H
Company:	EOG - Midland (3)	TVD Reference:	WELL @ 3539.0ft (Original Well Elev)
Project:	Thames	MD Reference:	WELL @ 3539.0ft (Original Well Elev)
Site:	Seine B 6 Fee #1H	North Reference:	Grid
Well:	Seine B 6 Fee #1H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Seine B 6 Fee #1H		
Design:	Plan #1 041706		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	N-S (ft)	E-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
4,575.0	34.92	343.38	4,560.9	65.9	-19.7	27.6	15.00	15.00	0.00
4,600.0	38.67	343.38	4,580.9	80.2	-24.0	33.6	15.00	15.00	0.00
4,625.0	42.42	343.38	4,599.9	95.8	-28.6	40.1	15.00	15.00	0.00
4,650.0	46.17	343.38	4,617.8	112.5	-33.6	47.1	15.00	15.00	0.00
4,675.0	49.92	343.38	4,634.5	130.4	-38.9	54.5	15.00	15.00	0.00
4,700.0	53.67	343.38	4,649.9	149.2	-44.5	62.4	15.00	15.00	0.00
4,725.0	57.42	343.38	4,664.1	168.9	-50.4	70.6	15.00	15.00	0.00
4,750.0	61.17	343.38	4,676.8	189.5	-56.6	79.2	15.00	15.00	0.00
4,775.0	64.92	343.38	4,688.2	210.9	-62.9	88.2	15.00	15.00	0.00
4,800.8	68.78	343.38	4,698.3	233.6	-69.7	97.7	14.97	14.97	0.00
4,800.8	68.78	343.38	4,698.3	233.6	-69.7	97.7	0.00	0.00	0.00
4,825.0	69.26	339.52	4,707.0	255.0	-76.9	107.4	15.00	2.00	-15.92
4,850.0	69.85	335.57	4,715.7	276.7	-85.9	118.9	15.00	2.35	-15.81
4,875.0	70.53	331.65	4,724.2	297.7	-96.3	131.9	15.00	2.70	-15.68
4,900.0	71.29	327.76	4,732.4	318.1	-108.2	146.2	15.00	3.04	-15.54
4,925.0	72.13	323.91	4,740.2	337.7	-121.6	161.8	15.00	3.36	-15.40
4,950.0	73.04	320.10	4,747.7	356.5	-136.2	178.7	15.00	3.65	-15.25
4,975.0	74.02	316.33	4,754.8	374.4	-152.2	196.7	15.00	3.93	-15.09
5,000.0	75.07	312.59	4,761.4	391.3	-169.4	215.8	15.00	4.19	-14.94
5,025.0	76.18	308.89	4,767.6	407.1	-187.8	236.0	15.00	4.43	-14.79
5,050.0	77.34	305.23	4,773.4	421.7	-207.2	257.0	15.00	4.65	-14.65
5,075.0	78.56	301.60	4,778.6	435.2	-227.6	278.9	15.00	4.85	-14.51
5,100.0	79.82	298.01	4,783.3	447.4	-248.9	301.6	15.00	5.03	-14.39
5,125.0	81.11	294.44	4,787.4	458.3	-271.0	324.8	15.00	5.19	-14.27
5,150.0	82.44	290.90	4,791.0	467.8	-293.8	348.6	15.00	5.32	-14.17
5,175.0	83.80	287.38	4,794.0	476.0	-317.3	372.9	15.00	5.43	-14.08
5,200.0	85.18	283.87	4,796.4	482.7	-341.2	397.5	15.00	5.53	-14.01
5,225.0	86.58	280.38	4,798.2	487.9	-365.6	422.3	15.00	5.60	-13.95
5,250.0	87.99	276.91	4,799.4	491.7	-390.3	447.3	15.00	5.65	-13.91
5,275.0	89.41	273.43	4,799.9	493.9	-415.2	472.3	15.00	5.68	-13.89
5,285.3	90.00	272.00	4,800.0	494.4	-425.5	482.6	15.00	5.69	-13.88
Entry Point B1									
5,300.0	90.00	271.56	4,800.0	494.9	-440.2	497.2	3.00	0.00	-3.00
5,330.0	90.00	270.66	4,800.0	495.4	-470.2	527.0	3.00	0.00	-3.00
5,400.0	90.00	270.66	4,800.0	496.2	-540.1	596.6	0.00	0.00	0.00
5,500.0	90.00	270.66	4,800.0	497.4	-640.1	696.0	0.00	0.00	0.00
5,600.0	90.00	270.66	4,800.0	498.5	-740.1	795.4	0.00	0.00	0.00
5,700.0	90.00	270.66	4,800.0	499.7	-840.1	894.8	0.00	0.00	0.00
5,800.0	90.00	270.66	4,800.0	500.8	-940.1	994.1	0.00	0.00	0.00
5,900.0	90.00	270.66	4,800.0	502.0	-1,040.1	1,093.5	0.00	0.00	0.00
6,000.0	90.00	270.66	4,800.0	503.1	-1,140.1	1,192.9	0.00	0.00	0.00
6,100.0	90.00	270.66	4,800.0	504.3	-1,240.1	1,292.3	0.00	0.00	0.00
6,200.0	90.00	270.66	4,800.0	505.4	-1,340.1	1,391.7	0.00	0.00	0.00
6,300.0	90.00	270.66	4,800.0	506.6	-1,440.1	1,491.1	0.00	0.00	0.00
6,400.0	90.00	270.66	4,800.0	507.8	-1,540.1	1,590.5	0.00	0.00	0.00
6,500.0	90.00	270.66	4,800.0	508.9	-1,640.1	1,689.9	0.00	0.00	0.00
6,600.0	90.00	270.66	4,800.0	510.1	-1,740.1	1,789.3	0.00	0.00	0.00
6,700.0	90.00	270.66	4,800.0	511.2	-1,840.1	1,888.6	0.00	0.00	0.00
6,800.0	90.00	270.66	4,800.0	512.4	-1,940.1	1,988.0	0.00	0.00	0.00
6,900.0	90.00	270.66	4,800.0	513.5	-2,040.0	2,087.4	0.00	0.00	0.00
7,000.0	90.00	270.66	4,800.0	514.7	-2,140.0	2,186.8	0.00	0.00	0.00
7,100.0	90.00	270.66	4,800.0	515.8	-2,240.0	2,286.2	0.00	0.00	0.00
7,200.0	90.00	270.66	4,800.0	517.0	-2,340.0	2,385.6	0.00	0.00	0.00

Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well Seine B 6 Fee #1H
Company:	EOG - Midland (3)	TVD Reference:	WELL @ 3539.0ft (Original Well Elev)
Project:	Thames	MD Reference:	WELL @ 3539.0ft (Original Well Elev)
Site:	Seine B 6 Fee #1H	North Reference:	Grid
Well:	Seine B 6 Fee #1H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Seine B 6 Fee #1H		
Design:	Plan #1 041706		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
7,300.0	90.00	270.66	4,800.0	518.1	-2,440.0	2,485.0	0.00	0.00	0.00
7,400.0	90.00	270.66	4,800.0	519.3	-2,540.0	2,584.4	0.00	0.00	0.00
7,500.0	90.00	270.66	4,800.0	520.4	-2,640.0	2,683.8	0.00	0.00	0.00
7,600.0	90.00	270.66	4,800.0	521.6	-2,740.0	2,783.1	0.00	0.00	0.00
7,700.0	90.00	270.66	4,800.0	522.7	-2,840.0	2,882.5	0.00	0.00	0.00
7,800.0	90.00	270.66	4,800.0	523.9	-2,940.0	2,981.9	0.00	0.00	0.00
7,900.0	90.00	270.66	4,800.0	525.0	-3,040.0	3,081.3	0.00	0.00	0.00
8,000.0	90.00	270.66	4,800.0	526.2	-3,140.0	3,180.7	0.00	0.00	0.00
8,100.0	90.00	270.66	4,800.0	527.3	-3,240.0	3,280.1	0.00	0.00	0.00
8,200.0	90.00	270.66	4,800.0	528.5	-3,340.0	3,379.5	0.00	0.00	0.00
8,300.0	90.00	270.66	4,800.0	529.6	-3,440.0	3,478.9	0.00	0.00	0.00
8,400.0	90.00	270.66	4,800.0	530.8	-3,539.9	3,578.2	0.00	0.00	0.00
8,500.0	90.00	270.66	4,800.0	531.9	-3,639.9	3,677.6	0.00	0.00	0.00
8,600.0	90.00	270.66	4,800.0	533.1	-3,739.9	3,777.0	0.00	0.00	0.00
8,700.0	90.00	270.66	4,800.0	534.2	-3,839.9	3,876.4	0.00	0.00	0.00
8,800.0	90.00	270.66	4,800.0	535.4	-3,939.9	3,975.8	0.00	0.00	0.00
8,900.0	90.00	270.66	4,800.0	536.5	-4,039.9	4,075.2	0.00	0.00	0.00
9,000.0	90.00	270.66	4,800.0	537.7	-4,139.9	4,174.6	0.00	0.00	0.00
9,100.0	90.00	270.66	4,800.0	538.8	-4,239.9	4,274.0	0.00	0.00	0.00
9,200.0	90.00	270.66	4,800.0	540.0	-4,339.9	4,373.4	0.00	0.00	0.00
9,263.2	90.00	270.66	4,800.0	540.7	-4,403.1	4,436.2	0.00	0.00	0.00

PBHL Seine B 6 Fee #1H

Targets

Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (ft)	Easting (ft)	Latitude	Longitude
- Hit/miss target									
- Shape									
PBHL Seine B 6 Fee #1H	0.00	0.00	4,800.0	540.7	-4,403.1	710,943.80	439,424.60	32° 57' 15.485 N	104° 31' 50.929 W
- plan misses by 63.2ft at 9200.0ft MD (4800.0 TVD, 540.0 N, -4339.9 E)									
- Point									
Entry Point B1	0.00	0.00	4,800.0	494.4	-425.5	710,897.50	443,402.20	32° 57' 15.098 N	104° 31' 4.246 W
- plan hits target									
- Point									

SITE DETAILS: Seine B 6 Fee #1H

Site Centre Northing: 710403.10
Easting: 443827.70

Positional Uncertainty: 0.0
Convergence: -0.10
Local North: Grid



PROJECT DETAILS: Thames

Geodetic System: US State Plane 1927 (Exact solution)
Datum: NAD 1927 (NADCON CONUS)
Ellipsoid: Clarke 1866
Zone: New Mexico East 3001

System Datum: Mean Sea Level

SECTION DETAILS

MD	Inc	Azi	TVD	+N/-S	+E/-W	DLeg	TFace	VSec	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
4342.2	0.00	0.00	4342.2	0.0	0.0	0.00	0.00	0.0	
4800.7	68.78	343.38	4698.3	233.5	-69.7	15.00	343.38	97.7	
4800.8	68.78	343.38	4698.3	233.6	-69.7	0.00	0.00	97.7	
5285.3	90.00	272.00	4800.0	494.4	-425.5	15.00	-83.05	482.6	Entry Point B1
5330.0	90.00	270.66	4800.0	495.4	-470.2	3.00	-90.00	527.0	
9263.2	90.00	270.66	4800.0	540.7	-4403.1	0.00	0.00	4436.2	PBHL Seine B 6 Fee #1H





EOG Resources, Inc.
P.O. Box 2267
Midland, TX 79702
(432) 686-3600

April 17, 2006

State of New Mexico Energy, Minerals and Natural Resources
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

To Whom It May Concern:

I am writing to request a waiver for the inclusion of an H₂S Contingency Plan for the Seine B 6 Fee #1H. The current plan is to complete this well in the Wolfcamp, which is sweet, and I do not anticipate encountering any H₂S bearing formations during drilling operations.

Sincerely,

A handwritten signature in cursive script that reads "Ron McIntyre".

Ron McIntyre
Drilling Engineer

Permit Conditions of Approval

Operator: EOG RESOURCES INC , 7377

Well: SEINE B 6 FEE #001H

API: 30-015-34798

OCD Reviewer	Condition
BArrant	Pit construction and closure must satisfy all requirements of your approved plan, O.C.D. Rule 19.15.2.50, and the Pit and Below-Grade Tank Guidelines
BArrant	Will require a directional survey with the C-104
BArrant	Please notify time of spud and time to witness the cementing to surface of all casing strings.
BArrant	As noted, operator to drill surface hole with 'fresh water' mud.
BArrant	Providing another well is drill in the same proration unit to produce from the same formation, an approval from Santa Fe is required.


EOG Resources, Inc.

Legals:
Seine B 6 Fee
Well # 1H
2910' FSL & 235' FEL
Section 6
16 South Township Survey
Eddy County, New Mexico
30 - 015 - 356.11

RECEIVED
JUN 06 2006
COUNTY CLERK

H₂S

“Contingency Plan”



CALLAWAY SAFETY EQUIPMENT CO., INC.
1020 W. Hwy. 80 East
Odessa, Texas 79765
(432) 561-5049
3229 Industrial Drive
Hobbs, New Mexico 88240
(505) 392-2973
(877) 422-6345

TABLE OF CONTENTS

I. H2S Contingency Plan

- A. Scope
- B. Objective
- C. Discussion of Plan

II. Emergency Procedures

- A. Emergency Procedures
- B. Emergency Reaction Steps
- C. Simulated Blowout Control Drills

III. Ignition Procedures

- A. Responsibility
- B. Instructions

IV. Training Requirements

V. Emergency Equipment

VI. Check Lists

- A. Status Check List
- B. Procedural Check List

VII. Briefing Procedures

VIII. Evacuation Plan

- A. General Plan
- B. Emergency Phone Lists

IX. Maps and Plats

- A. Location Plat
- B. Map to Location
- C. Radius of Exposure

X. General Information

- A. Drilling/Re-entry Permits
- B. H-9 Permit
- C. H₂s Permissible Limits

- D. Toxicity Table
- E. Physical Properties
- F. Respirator Use
- G. Emergency Rescue

H₂S CONTINGENCY PLAN SECTION

Scope:

This contingency plan provides an organized plan of action for alerting and protecting the public within an area of exposure prior to an intentional release, or following the accidental release of a potentially hazardous volume of hydrogen sulfide. The plan establishes guidelines for all personnel whose work activity may involve exposure to Hydrogen Sulfide Gas (H₂S).

Objective:

Prevent any and all accidents, and prevent the uncontrolled release of H₂S into the atmosphere.

Provide proper evacuation procedures to cope with emergencies.

Provide immediate and adequate medical attention should an injury occur.

Discussion of Plan:

Suspected Problem Zones:

Implementation: This plan, with all details, is to be fully implemented 1000' before drilling into the first sour zone.

Emergency Response Procedure: This section outlines the conditions and denotes steps to be taken in the event of an emergency.

Emergency Equipment and Procedure: This section outlines the safety and emergency equipment that will be required for the drilling of this well.

Training Provisions: This section outlines the training provisions that must be adhered to 1000' before drilling into the first sour zone.

Emergency call lists: Included are the telephone numbers of all persons that would need to be contacted, should an H₂S emergency occur.

Briefing: This section deals with the briefing of all persons involved with the drilling of this well.

Public Safety: Public Safety Personnel will be made aware of the drilling of this well.

Check Lists: Status check lists and procedural check lists have been included to ensure adherence to the plan.

General Information: A general information section has been included to supply support information.

EMERGENCY PROCEDURES SECTION

- I. In the event of any evidence of H₂S level above 10 ppm, take the following steps immediately:
 - A. Secure breathing apparatus.
 - B. Order non-essential personnel out of the danger zone.
 - C. Take steps to determine if the H₂S level can be corrected or suppressed, and if so, proceed with normal operations.
- II. If uncontrollable conditions occur, proceed with the following:
 - A. Take steps to protect and/or remove any public downwind of the rig, including partial evacuation or isolation. Notify necessary public safety personnel and the Texas Railroad Commission of the situation.
 - B. Remove all personnel to the Safe Briefing Area.
 - C. Notify public safety personnel for help with maintaining roadblocks and implementing evacuation.
 - D. Determine and proceed with the best possible plan to regain control of the well. Maintain tight security and safety measures.
- III. Responsibility:
 - A. The Company Approved Supervisor shall be responsible for the total implementation of the plan.
 - B. The Company Approved Supervisor shall be in complete command during any emergency.
 - C. The Company Approved Supervisor shall designate a back up Supervisor in the event that he/she is not available.

EMERGENCY PROCEDURE IMPLEMENTATION

I. Drilling or Tripping

A. All Personnel

1. When alarm sounds, don escape unit and report to upwind Safe Briefing Area.
2. Check status of other personnel (buddy system).
3. Secure breathing apparatus.
4. Wait for orders from supervisor.

B. Drilling Foreman

1. Report to the upwind Safe Briefing Area.
2. Don Breathing Apparatus and return to the point of release with the Tool Pusher or Driller (buddy system).
3. Determine the concentration of H₂S.
4. Assess the situation and take appropriate control measures.

C. Tool Pusher

1. Report to the upwind Safe Briefing Area.
2. Don breathing apparatus and return to the point of release with the Drilling Foreman or the Driller (buddy system).
3. Determine the concentration.
4. Assess the situation and take appropriate control measures.

D. Driller

1. Check the status of other personnel (in a rescue attempt, always use the buddy system).
2. Assign the least essential person to notify the Drilling Foreman and Tool Pusher, in the event of their absence.

3. Assume the responsibility of the Drilling Foreman and the Tool Pusher until they arrive, in the event of their absence.

E. Derrick Man and Floor Hands

1. Remain in the upwind Safe Briefing Area until otherwise instructed by a supervisor.

F. Mud Engineer

1. Report to the upwind Safe Briefing Area.
2. When instructed, begin check of mud for pH level and H₂S level.

G. Safety Personnel

1. Don Breathing Apparatus.
2. Check status of all personnel.
3. Wait for instructions from Drilling Foreman or Tool Pusher.

II. Taking a Kick

- A. All personnel report to the upwind Safe Briefing Area.
- B. Follow standard BOP procedures.

III. Open Hole Logging

- A. All unnecessary personnel should leave the rig floor.
- B. Drilling Foreman and Safety Personnel should monitor the conditions and make necessary safety equipment recommendations.

IV. Running Casing or Plugging

- A. Follow "Drilling or Tripping" procedures.
- B. Assure that all personnel have access to protective equipment.

SIMULATED BLOWOUT CONTROL DRILLS

All drills will be initiated by activating alarm devices (air horn). One long blast, on the air horn, for ACTUAL and SIMULATED Blowout Control Drills. This operation will be performed by the Drilling Foreman or Tool Pusher at least one time per week for each of the following conditions, with each crew:

Drill # 1 Bottom Drilling

Drill # 2 Tripping Drill Pipe

In each of these drills, the initial reaction time to shutting in the well shall be timed as well as the total time for the crew to complete its entire pit drill assignment. The times must be recorded on the IADC Driller's Log as "Blowout Control Drill".

Drill No.:

Reaction Time to Shut-In: minutes, seconds.

Total Time to Complete Assignment: minutes, seconds.

I. Drill Overviews

A. Drill No. 1- Bottom Drilling

1. Sound the alarm immediately.
2. Stop the rotary and hoist kelly joint above the rotary table.
3. Stop the circulatory pump.
4. Close the drill pipe rams.
5. Record casing and drill pipe shut-in pressures and pit volume increases.

B. Drill No. 2 – Tripping Drill Pipe

1. Sound the alarm immediately.
2. Position the upper tool joint just above the rotary table and set the slips.

3. Install a full opening valve or inside blowout preventor tool in order to close the drill pipe.
4. Close the drill pipe rams.
5. Record the shut-in annular pressure.

II. Crew Assignments

A. Drill No. 1 – Bottom Drilling

1. Driller

- a) Stop the rotary and hoist kelly joint above the rotary table.
- b) Stop the circulatory pump.
- c) Check flow.
- d) If flowing, sound the alarm immediately.
- e) Record the shut-in drill pipe pressure.
- f) Determine the mud weight increase needed or other courses of action.

2. Derrickman

- a) Open choke line valve at BOP.
- b) Signal Floor Man # 1 at accumulator that choke line is open.
- c) Close choke and upstream valve after pipe tams have been closed.
- d) Read the shut-in annular pressure and report readings to Driller.

3. Floor Man # 1

- a) Close the pipe rams after receiving the signal from the Derrickman.
- b) Report to Driller for further instructions.

4. Floor Man # 2

- a) Notify the Tool Pusher and Operator Representative of the H₂S alarms.
- b) Check for open fires and, if safe to do so, extinguish them.
- c) Stop all welding operations.
- d) Turn-off all non-explosion proof lights and instruments.
- e) Report to Driller for further instructions.

5. Tool Pusher

- a) Report to the rig floor.
- b) Have a meeting with all crews.
- c) Compile and summarize all information.
- d) Calculate the proper kill weight.
- e) Ensure that proper well procedures are put into action.

6. Operator Representative

- a) Notify the Drilling Superintendent.
- b) Determine if an emergency exists and if so, activate the contingency plan.

B. Drill No. 2 – Tripping Pipe

1. Driller

- a) Sound the alarm immediately when mud volume increase has been detected.
- b) Position the upper tool joint just above the rotary table and set slips.
- c) Install a full opening valve or inside blowout preventor tool to close the drill pipe.
- d) Check flow.
- e) Record all data reported by the crew.

f) Determine the course of action.

2. Derrickman

- a) Come down out of derrick.
- b) Notify Tool Pusher and Operator Representative.
- c) Check for open fires and, if safe to do so, extinguish them.
- d) Stop all welding operations.
- e) Report to Driller for further instructions.

3. Floor Man # 1

- a) Pick up full opening valve or inside blowout preventor tool and stab into tool joint above rotary table (with Floor Man # 2).
- b) Tighten valve with back-up tongs.
- c) Close pipe rams after signal from Floor Man # 2.
- d) Read accumulator pressure and check for possible high pressure fluid leaks in valves or piping.
- e) Report to Driller for further instructions.

4. Floor Man # 2

- a) Pick-up full opening valve or inside blowout preventor tool and stab into tool joint above rotary table (with Floor Man # 1).
- b) Position back-up tongs on drill pipe.
- c) Open choke line valve at BOP.
- d) Signal Floor Man # 1 at accumulator that choke line is open.
- e) Close choke and upstream valve after pipe rams have been closed.
- f) Check for leaks on BOP stack and choke manifold.
- g) Read annular pressure.

h) Report readings to the Driller.

5. Tool Pusher

- a) Report to the rig floor.
- b) Have a meeting with all of the crews.
- c) Compile and summarize all information.
- d) See that proper well kill procedures are put into action.

6. Operator Representative

- a) Notify Drilling Superintendent
- b) Determine if an emergency exists, and if so, activate the contingency plan.

IGNITION PROCEDURES

Responsibility:

The decision to ignite the well is the responsibility of the DRILLING FOREMAN in concurrence with the STATE POLICE. In the event the Drilling Foreman is incapacitated, it becomes the responsibility of the RIG TOOL PUSHER. This decision should be made only as a last resort and in a situation where it is clear that:

1. Human life and property are endangered.
2. There is no hope of controlling the blowout under the prevailing conditions.

If time permits, notify the main office, but do not delay if human life is in danger. Initiate the first phase of the evacuation plan.

Instructions for Igniting the Well:

1. Two people are required for the actual igniting operation. Both men must wear self-contained breathing apparatus and must use a full body harness and attach a retrievable safety line to the D-Ring in the back. One man must monitor the atmosphere for explosive gases with the LEL monitor, while the Drilling Foreman is responsible for igniting the well.
2. The primary method to ignite is a 25mm flare gun with a range of approximately 500 feet.
3. Ignite from upwind and do not approach any closer than is warranted.
4. Select the ignition site best suited for protection and which offers an easy escape route.
5. Before igniting, check for the presence of combustible gases.
6. After igniting, continue emergency actions and procedures as before.
7. All unassigned personnel will limit their actions to those directed by the Drilling Foreman.

NOTE: After the well is ignited, burning Hydrogen Sulfide will convert to Sulfur Dioxide, which is also highly toxic. Do not assume the area is safe after the well is ignited.

TRAINING PROGRAM

When working in an area where Hydrogen Sulfide (H_2S) might be encountered, definite training requirements must be carried out. The Company Supervisor will ensure that all personnel, at the well site, have had adequate training in the following:

1. Hazards and Characteristics of Hydrogen Sulfide.
2. Physicals effects of Hydrogen Sulfide on the human body.
3. Toxicity of Hydrogen Sulfide and Sulfur Dioxide.
4. H_2S detection, emergency alarm and sensor location.
5. Emergency rescue.
6. Resuscitators.
7. First aid and artificial resuscitation.
8. The effects of Hydrogen Sulfide on metals.
9. Location safety.

Service company personnel and visiting personnel must be notified if the zone contains H_2S , and each service company must provide adequate training and equipment for their employees before they arrive at the well site.

EMERGENCY EQUIPMENT REQUIREMENTS

Lease Entrance Sign:

Should be located at the lease entrance with the following information:

CAUTION-POTENTIAL POISON GAS
HYDROGEN SULFIDE
NO ADMITTANCE WITHOUT AUTHORIZATION

Respiratory Equipment:

- Fresh air breathing equipment should be placed at the safe briefing areas and should include the following:
- Two SCBA's at each briefing area.
- Enough air line units to operate safely, anytime the H₂S concentration reaches the IDLH level (100 PPM).
- Cascade system with enough breathing air hose and manifolds to reach the rig floor, the derrickman and the other operation areas.

Windsocks or Wind Streamers:

- A minimum of two 10" windsocks located at strategic locations so that they may be seen from any point on location.
- Wind streamers (if preferred) should be placed at various locations on the well site to ensure wind consciousness at all times. (Corners of location).

Hydrogen Sulfide Detector and Alarms:

- 1-Four channel H₂S monitor with alarms.
- Four (4) sensors located as follows: # 1 – Rig Floor, # 2 – Bell Nipple, # 3 – Shale Shaker, # 4 – Mud Pits.
- Gastec or Draeger pump with tubes.
- Sensor test gas.

Well Condition Sign and Flags:

The Well Condition Sign w/flags should be placed a minimum of 150' before you enter the location. It should have three (3) color coded flags (green, yellow and red) that will be used to denote the following location conditions:

GREEN – Normal Operating Conditions

YELLOW – Potential Danger

RED – Danger, H₂S Gas Present

Auxiliary Rescue Equipment:

- Stretcher
- 2 – 100' Rescue lines
- First Aid Kit properly stocked.

Mud Inspection Equipment:

Garret Gas Train or Hach Tester for inspection of Hydrogen Sulfide in the drilling mud system.

Fire Extinguishers:

Adequate fire extinguishers shall be located at strategic locations.

Blowout Preventor:

- The well shall have hydraulic BOP equipment for the anticipated BHP.
- The BOP should be tested upon installation.
- BOP, Choke Line and Kill Line will be tested as specified by Operator.

Confined Space Monitor:

There should be a portable multi-gas monitor with at least 3 sensors (O₂, LEL & H₂S). This instrument should be used to test the atmosphere of any confined space before entering. It should also be used for atmospheric testing for LEL gas before beginning any type of Hot Work. Proper calibration documentation will need to be provided.

Communication Equipment:

- Proper communication equipment such as cell phones or 2 – way radios should be available at the rig.

- Radio communication shall be available for communication between the company man's trailer, rig floor and the tool pusher's trailer.
- Communication equipment shall be available on the vehicles.

Special Control Equipment:

- Hydraulic BOP equipment with remote control on the ground.
- Rotating head at the surface casing point.

Evacuation Plan:

- Evacuation routes should be established prior to spudding the well.
- Should be discussed with all rig personnel.

Designated Areas:

Parking and Visitor area:

- All vehicles are to be parked at a pre-determined safe distance from the wellhead.
- Designated smoking area.

Safe Briefing Areas:

- Two Safe Briefing Areas shall be designated on either side of the location at the maximum allowable distance from the well bore so they offset prevailing winds or they are at a 180 degree angle if wind directions tend to shift in the area.
- Personal protective equipment should be stored at both briefing areas or if a moveable cascade trailer is used, it should be kept upwind of existing winds. When wind is from the prevailing direction, both briefing areas should be accessible.

NOTE:

- Additional equipment will be available at the nearest Callaway Safety Office.
- Additional personal H₂S monitors are available for all employees on location.

- Automatic Flare Igniters are recommended for installation on the rig

CHECK LISTS

Status Check List

Note: Date each item as they are implemented.

1. Sign at location entrance. _____
2. Two (2) wind socks (in required locations). _____
3. Wind Streamers (if required). _____
4. SCBA's on location for all rig personnel and mud loggers. _____
5. Air packs, inspected and ready for use. _____
6. Spare bottles for each air pack (if required). _____
7. Cascade system for refilling air bottles. _____
8. Cascade system and hose line hook up. _____
9. Choke manifold hooked-up and tested.
(Before drilling out surface casing.) _____
10. Remote Hydraulic BOP control (hooked-up and
tested before drilling out surface casing). _____
11. BOP tested (before drilling out surface casing). _____
12. Mud engineer on location with equipment to test
mud for H₂S. _____
13. Safe Briefing Areas set-up. _____
14. Well Condition sign and flags on location and ready. _____
15. Hydrogen Sulfide detection system hooked-up & tested. _____
16. Hydrogen Sulfide alarm system hooked-up & tested. _____
17. Stretcher on location at Safe Briefing Area. _____
18. 2-100' Life Lines on location. _____

- [illegible]

Procedural Check List

Perform the following on each tour:

1. Check fire extinguishers to see that they have the proper charge.
2. Check Breathing equipment to insure that they have not been tampered with.
3. Check pressure on the supply air bottles to make sure they are capable of recharging.
4. Make sure all of the Hydrogen Sulfide detection systems are operative.

Perform the following each week:

1. Check each piece of breathing equipment to make sure that they are fully charged and operational. This requires that the air cylinder be opened and the mask assembly be put on and tested to make sure that the regulators and masks are properly working. Negative and Positive pressure should be conducted on all masks.
2. BOP skills.
3. Check supply pressure on BOP accumulator stand-by source.
4. Check all breathing air mask assemblies to see that straps are loosened and turned back, ready to use.
5. Check pressure on cascade air cylinders to make sure they are fully charged and ready to use for refill purposes if necessary.
6. Check all cascade system regulators to make sure they work properly.
7. Perform breathing drills with on-site personnel.
8. Check the following supplies for availability:
 - Stretcher
 - Safety Belts and ropes.
 - Spare air bottles.
 - Spare oxygen bottles (if resuscitator required).
 - Gas Detector Pump and tubes.
 - Emergency telephone lists.

9. Test the Confined Space Monitor to verify the batteries are good.

BRIEFING PROCEDURES

The following scheduled briefings will be held to ensure the effective drilling and operation of this project:

Pre-Spud Meeting

Date: Prior to spudding the well.

Attendance: Drilling Supervisor

Drilling Engineer

Drilling Foreman

Rig Tool Pushers

Rig Drillers

Mud Engineer

All Safety Personnel

Key Service Company Personnel

Purpose: Review and discuss the well program, step-by-step, to insure complete understanding of assignments and responsibilities.

EVACUATION PLAN

General Plan

The direct lines of action prepared by CALLAWAY SAFETY EQUIPMENT CO., INC., to protect the public from hazardous gas situations are as follows:

1. When the company approved supervisor (Drilling Foremen, Tool Pusher or Driller) determine that Hydrogen Sulfide gas cannot be limited to the well location, and the public will be involved, he will activate the evacuation plan. Escape routes are noted on the Area Map.
2. Company safety personnel or designee will notify the appropriate local government agency that a hazardous condition exists and evacuation need to be implemented.
3. Company approved safety personnel that have been trained in the use of the proper emergency equipment will be utilized.
4. Law enforcement personnel (State Police, Local Police Department, Fire Department, and the Sheriff's Department) will be called to aid in setting up and maintaining road blocks. Also, they will aid in evacuation of the public if necessary.

NOTE: Law enforcement personnel will not be asked to come into a contaminated area. Their assistance will be limited to uncontaminated areas. Constant radio contact will be maintained with them.

5. After the discharge of gas has been controlled, "Company" safety personnel will determine when the area is safe for re-entry.

See Emergency Action Plan

Emergency Assistance Telephone List

PUBLIC SAFETY:

911 or

Eddy County Sheriff's Department	(505) 558-3571
Fire Department	(505) 746-5050
Artesia General Hospital	(505) 748-3333
Life Flight:	
Arrow Care-Lubbock	(806) 744-5055
Southwest Air-Med E Vac.	(806) 242-6199

Surface	Lat. N. 32.9528372
Location	Long. W. 104.5164563

Bottom Hole	Lat. N. 32.9543013
Location	Long. W. 104.5308136

New Mexico D.O.T.	(505) 827-5100
New Mexico State Police	(505) 888-3137
Bureau of Land Management	(505) 393-3612
U.S. Dept. of Labor	(505) 248-5302
New Mexico OCD	(505) 393-6161
New Mexico OCD/After Hours	(505) 370-7106

EOG Resources, Inc.

EOG / Midland	Office (432) 686-3600
---------------	-----------------------

Company Drilling Consultants:

Dwain Davis	Cell (432) 889-6788
Dan Atnipp	Cell (432) 557-4599

Drilling Engineer:

Ron McLntyre	Office (432) 686-3640
	Cell (432) 664-8113

Drilling Superintendent

Boyd Holmes	Office (432) 686-3695
	Cell (432) 935-2393

JW Drilling Rig #3

JW Drilling/Artesia, NM	Office (505) 748-8704
-------------------------	-----------------------

JW Drilling Rig #3	Rig (432) 894-0398
--------------------	--------------------

Drilling Supervisor Kevin Wilbanks	Office (505) 748-8704
---------------------------------------	-----------------------

Tool Pusher:

Johnny Woods	Rig (432) 894-0398
--------------	--------------------

Callaway Safety Equipment

Odessa (432) 561-5049

Hobbs (505) 392-2973

Artesia (505) 746-2847

MAPS AND PLATS
(Maps & Plats Attached)

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised October 12, 2005
Submit to Appropriate District Office
State Lease-4 Copies
Fee Lease-3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	Pool Code	Pool Name
Property Code	Property Name SEINE B 6 FEE	Well Number 1H
OGRD No.	Operator Name EOG RESOURCES, INC.	Elevation 3521'

Surface Location


UL or lot no.	Section	Township	Range	Lot 1/4	Feet from the	North/South line	Feet from the	East/West line	County
16	6	16 SOUTH	25 EAST, N.M.P.M.		2910	SOUTH	235	EAST	EDDY

Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot 1/4	Feet from the	North/South line	Feet from the	East/West line	County
13	6	16 SOUTH	25 EAST, N.M.P.M.		3400	SOUTH	660	WEST	EDDY

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
-----------------	-----------------	--------------------	-----------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Signature _____ Date _____

Printed Name _____

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of a survey made by me or under my supervision, and that the same is true and correct to the best of my knowledge.

Date of Survey _____

Signature of _____
Professional Surveyor

Terry J. Paul
Certificate Number 15079

WOF 000330ML-c (200)

Affected Notification List

(within a 65' radius of exposure @100ppm)

The geologic zones that will be encountered during drilling are known to contain hazardous quantities of H₂S. The accompanying map illustrates the affected areas of the community. The residents within this radius will be notified via a hand delivered written notice describing the activities, potential hazards, conditions of evacuation, evacuation drill siren alarms and other precautionary measures.

Evacuee Description:

Residents: **THERE ARE NO RESIDENTS WITHIN 3000' ROE.**

Notification Process:

A continuous siren audible to all residence will be activated, signaling evacuation of previously notified and informed residents.

Evacuation Plan:

All evacuees will migrate lateral to the wind direction.

The Oil Company will identify all home bound or highly susceptible individuals and make special evacuation preparations, interfacing with the local and emergency medical service as necessary.

GENERAL INFORMATION

District II

1301 W. Grand Ave., Artesia, NM 88210
Phone:(505) 748-1283 Fax:(505) 748-9720

State of New Mexico

Energy, Minerals and Natural
Resources

Oil Conservation Division

1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-101

Permit 27674

**APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A
ZONE**

1. Operator Name and Address EOG RESOURCES INC PO BOX 2267 MIDLAND, TX 79702		2. OGRID Number 7377
		3. API Number 30-015-34798
4. Property Code 35612	5. Property Name SEINE B 6 FEE	6. Well No. 001H

7. Surface Location

UL - Lot H	Section 6	Township 16S	Range 25E	Lot Idn 16	Feet From 2910	N/S Line S	Feet From 235	E/W Line E	County EDDY
------------------	--------------	-----------------	--------------	------------------	----------------------	------------------	---------------------	------------------	----------------

8. Pool Information

COTTONWOOD CREEK;WC, WEST (GAS)	75260
---------------------------------	-------

Additional Well Information

9. Work Type New Well	10. Well Type GAS	11. Cable/Rotary	12. Lease Type Private	13. Ground Level Elevation 3521
14. Multiple N	15. Proposed Depth 5200	16. Formation Wolfcamp	17. Contractor	18. Spud Date
Depth to Ground water 50		Distance from nearest fresh water well 400		Distance to nearest surface water 400
Pit: Liner: ☐ 12 mils thick Clay: ☐ Pit Volume: 10300 bbls Drilling Method: Synthetic ☐ Closed Loop System ☐ Fresh Water ☐ Brine ☐ Diesel/Oil-based ☐ Gas/Air ☐				

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	12.25	8.625	32	950	450	0
Prod	7.875	5.5	17	9263	820	0

Casing/Cement Program: Additional Comments

--

Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.		OIL CONSERVATION DIVISION	
I further certify that the drilling pit will be constructed according to NMOCD guidelines ☐ , a general permit ☐ , or an (attached) alternative OCD-approved plan ☐ .		Approved By: Bryan Arrant	
Printed Name: Electronically filed by Mike Francis		Title: Geologist	
Title: ROW Agent		Approved Date: 4/21/2006	Expiration Date: 4/21/2007
Email Address: mike_francis@eogresources.com			
Date: 4/18/2006	Phone: 4326863714	Conditions of Approval Attached	

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural
Resources

Oil Conservation Division

1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102

Permit 27674

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-015-34798	2. Pool Code 75260	3. Pool Name COTTONWOOD CREEK;WC, WEST (GAS)
4. Property Code 35612	5. Property Name SEINE B 6 FEE	6. Well No. 001H
7. OGRID No. 7377	8. Operator Name EOG RESOURCES INC	9. Elevation 3521

10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
16	6	16S	25E	16	2910	S	235	E	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
13	6	16S	25E	13	3400	S	660	W	EDDY
12. Dedicated Acres 319.52	13. Joint or Infill	14. Consolidation Code	15. Order No.						

**NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL
INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN
APPROVED BY THE DIVISION**

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Mike Francis

Title: ROW Agent

Date: 4/18/2006

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Terry Asel

Date of Survey: 3/30/2006

Certificate Number: 15079

Permit Conditions of Approval

Operator: EOG RESOURCES INC , 7377

Well: SEINE B 6 FEE #001H

API: 30-015-34798

OCD Reviewer	Condition
Barrant	Pit construction and closure must satisfy all requirements of your approved plan, O.C.D. Rule 19.15.2.50, and the Pit and Below-Grade Tank Guidelines
Barrant	Will require a directional survey with the C-104
Barrant	Please notify time of spud and time to witness the cementing to surface of all casing strings.
Barrant	As noted. operator to drill surface hole with 'fresh water' mud.
Barrant	Providing another well is drill in the same proration unit to produce from the same formation, an apporval from Santa Fe is required.

Permit Comments

Operator: EOG RESOURCES INC , 7377

Well: SEINE B 6 FEE #001H

API:

Created By	Comment	Comment Date
dglanton	Plat, Detailed Casing, Mud, Cement, Drilling Plan and H2S letter will be forwarded via regular mail.	4/17/2006

Toxic Effects of H₂S Poisoning

Hydrogen Sulfide is extremely toxic. The acceptable ceiling concentration for eight-hour exposure is 10 PPM, which is .001% by volume. Hydrogen Sulfide is heavier than air (specific gravity-1.192) and is colorless and transparent. Hydrogen Sulfide is almost as toxic as Hydrogen Cyanide and is 5-6 times more toxic than Carbon Monoxide. Occupational exposure limits for Hydrogen sulfide and other gasses are compared below in Table I. Toxicity table for H₂S and physical effects are shown in Table II.

Table 1
Permissible Exposure Limits of Various Gasses

Common Name	Symbol	Sp. Gravity	TLV	STEL	IDLH
Hydrogen Cyanide	HCN	.94	4.7 ppm	C	
Hydrogen Sulfide	H ₂ S	1.192	10 ppm	15 ppm	100 ppm
Sulfide Dioxide	SO ₂	2.21	2 ppm	5 ppm	
Chlorine	CL	2.45	.5 ppm	1 ppm	
Carbon Monoxide	CO	0.97	25 ppm	200 ppm	
Carbon Dioxide	CO ₂	1.52	5000 ppm	30,000 ppm	
Methane	CH ₄	0.55	4.7% LEL	14% UEL	

Definitions

- A. TLV – Threshold Limit Value is the concentration employees may be exposed to based on a TWA (time weighted average) for eight (8) hours in one day for 40 hours in one (1) week. This is set by ACGIH (American Conference of Governmental Hygienists and regulated by OSHA.
- B. STEL – Short Term Exposure Limit is the 15 minute average concentration an employee may be exposed to providing that the highest exposure never exceeds the OEL (Occupational Exposure Limit). The OEL for H₂S is 19 PPM.
- C. IDLH – Immediately Dangerous to Life and Health is the concentration that has been determined by the ACGIH to cause serious health problems or death if exposed to this level. The IDLH for H₂S is 100 PPM.

- D. TWA – Time Weighted Average is the average concentration of any chemical or gas for an eight (8) hour period. This is the concentration that any employee may be exposed to based on an TWA.

TABLE II
Toxicity Table of H₂S

Percent %	PPM	Physical Effects
.0001	1	Can smell less than 1 ppm.
.001	10	TLV for 8 hours of exposure
.0015	15	STEL for 15 minutes of exposure
.01	100	Immediately Dangerous to Life & Health. Kills sense of smell in 3 to 5 minutes.
.02	200	Kills sense of smell quickly, may burn eyes and throat.
.05	500	Dizziness, cessation of breathing begins in a few minutes.
.07	700	Unconscious quickly, death will result if not rescued promptly.
.10	1000	Death will result unless rescued promptly. Artificial resuscitation may be necessary.

PHYSICAL PROPERTIES OF H₂S

The properties of all gasses are usually described in the context of seven major categories:

COLOR
ODOR
VAPOR DENSITY
EXPLOSIVE LIMITS
FLAMMABILITY
SOLUBILITY (IN WATER)
BOILING POINT

Hydrogen Sulfide is no exception. Information from these categories should be considered in order to provide a fairly complete picture of the properties of the gas.

COLOR – TRANSPARENT

Hydrogen Sulfide is colorless so it is invisible. This fact simply means that you can't rely on your eyes to detect its presence. a fact that makes the gas extremely dangerous to be around.

ODOR – ROTTEN EGGS

Hydrogen Sulfide has a distinctive offensive smell, similar to "rotten eggs". For this reason it earned its common name "sour gas". However, H₂S, even in low concentrations, is so toxic that it attacks and quickly impairs a victim's sense of smell, so it could be fatal to rely on your nose as a detection device.

VAPOR DENSITY – SPECIFIC GRAVITY OF 1.192

Hydrogen Sulfide is heavier than air so it tends to settle in low-lying areas like pits, cellars or tanks. If you find yourself in a location where H₂S is known to exist, protect yourself. Whenever possible, work in an area upwind and keep to higher ground.

EXPLOSIVE LIMITS – 4.3% TO 46%

Mixed with the right proportion of air or oxygen, H₂S will ignite and burn or explode, producing another alarming element of danger besides poisoning.

FLAMMABILITY

Hydrogen Sulfide will burn readily with a distinctive clear blue flame, producing Sulfur Dioxide (SO₂), another hazardous gas that irritates the eyes and lungs.

SOLUBILITY – 4 TO 1 RATIO WITH WATER

Hydrogen Sulfide can be dissolved in liquids, which means that it can be present in any container or vessel used to carry or hold well fluids including oil, water, emulsion and sludge. The solubility of H₂S is dependent on temperature and pressure, but if conditions are right, simply agitating a fluid containing H₂S may release the gas into the air.

BOILING POINT – (-76 degrees Fahrenheit)

Liquefied Hydrogen Sulfide boils at a very low temperature, so it is usually found as a gas.

RESPIRATOR USE

The Occupational Safety and Health Administration (OSHA) regulates the use of respiratory protection to protect the health of employees. OSHA's requirements are written in the Code of Federal Regulations, Title 29, Part 1910, Section 134, Respiratory Protection. This regulation requires that all employees who might be required to wear respirators, shall complete a OSHA mandated medical evaluation questionnaire. The employee then should be fit tested prior to wearing any respirator while being exposed to hazardous gasses.

Written procedures shall be prepared covering safe use of respirators in dangerous atmospheric situations, which might be encountered in normal operations or in emergencies. Personnel shall be familiar with these procedures and the available respirators.

Respirators shall be inspected prior to and after each use to make sure that the respirator has been properly cleaned, disinfected and that the respirator works properly. The unit should be fully charged prior to being used.

Anyone who may use respirators shall be properly trained in how to properly seal the face piece. They shall wear respirators in normal air and then in a test atmosphere. (Note: Such items as facial hair (beard or sideburns) and eyeglass temple pieces will not allow a proper seal.) Anyone that may be expected to wear respirators should have these items removed before entering a toxic atmosphere. A special mask must be obtained for anyone who must wear eyeglasses. Contact lenses should not be allowed.

Respirators shall be worn during the following conditions:

- A. Any employee who works near the top or on the top of any tank unless tests reveal less than 20 ppm of H₂S.
- B. When breaking out any line where H₂S can reasonably be expected.
- C. When sampling air in areas where H₂S may be present.
- D. When working in areas where the concentration of H₂S exceeds the Threshold Limit Value for H₂S (10 ppm).
- E. At any time where there is a doubt as to the H₂S level in the area to be entered.

EMERGENCY RESCUE PROCEDURES

DO NOT PANIC!!!

Remain Calm - THINK

1. Before attempting any rescue you must first get out of the hazardous area yourself. Go to a safe briefing area.
2. Sound an alarm and activate the 911 system.
3. Put on breathing apparatus. At least two persons should do this, when available use the buddy system.
4. Rescue the victim and return them to a safe briefing area.
5. Perform an initial assessment and begin proper First Aid/CPR procedures.
6. Keep the victim lying down with a blanket or coat, etc..., under the shoulders to keep airway open. Conserve body heat and do not leave unattended.
7. If the eyes are affected by H₂S, wash them thoroughly with potable water. For slight irritation, cold compresses are helpful.
8. In case a person has only minor exposure and does not lose consciousness totally, it's best if he doesn't return to work until the following day.
9. Any personnel overcome by H₂S should always be examined by medical personnel. They should always be transported to a hospital or doctor.