

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

REVISED

Form C-103
May 27, 2004

CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30 - 015 - 02553

13. Indicate Type of Lease

STATE ☒ FEE ☐

13. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Empire Abo Unit "I"

8. Well Number

30

9. OGRID Number

00778

10. Pool name or Wildcat

Empire Abo

13. Well Location

Unit Letter C : 330 feet from the North line and 1675' feet from the West line
Section 4 Township 18S Range 28E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3671' RKB

Pit or Below-grade Tank Application ☒ or Closure ☐

Pit type Workover Depth to Groundwater >100' Distance from nearest fresh water well >1000' Distance from nearest surface water >200'

Pit Liner Thickness: 20 mil Below-Grade Tank: Volume 200 bbls; Construction Material

13. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

This is a revision to original C-103 for P&A dated 2/28/07 and approved by NMOCD on 3/1/07:

1. MIRU PU. Install BOP and test 4½" csg to 500 psi.
2. TIH w/ tubing to 6128' and spot 25 sx cement onto existing CIBP @ 6128'.
3. Circulate and load hole w/ 9.5 ppg mud laden fluid & POH w/ tubing.
4. Perf 4 squeeze holes @ 3725' = 50' below top of Glorieta @ 3675'. Run packer on tubing, set @ 3400' & squeeze perfs w/ 40 sx - displace 30 sx of cement outside of perfs and leave 10 sx inside csg. **WOC & TAG - top must not be lower than 3625'.**
5. Spot 25 sx cement from 3040' - 2678' across old squeeze holes @ 2987'. **NOT NECESSARY TO TAG THIS PLUG.**
6. Spot 25 sk plug from 2300' - 1938' across 8 5/8" surface casing shoe @ 2239'. **WOC & tag plug; top of plug must not be lower than 2189'.**
7. Spot 25 sx cement from 1450' - 1088' across top of Queen @ 1348'. **WOC & TAG - top of plug must not be lower than 1292'.**
8. POH w/ tubing to 550' = 50' below top of the Yates. Circulate cement to surface (estimated 38 sx). RD PU. Cut off casings and wellheads to 3' below ground level and install regulation Dry Hole Marker. Cut anchors to 3' below ground level, clean location and notify NMOCD when site is ready for final inspection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE [Signature] TITLE Agent for BP America Production Company DATE 5 / 22 / 07

Type or print name D. C. Dodd E-mail address: ddodd@sierra-engineering.net Telephone No. 432 / 683-8000

For State Use Only

APPROVED BY: [Signature] TITLE St DATE 5/24/07
Conditions of Approval (if any):

Empire Abo Unit "I" #30
Empire Abo Field
API No. 30-015-02553

330' FNL & 1675' FWL
Sec 4 - T18S - R28E
Eddy County, New Mexico

P&A Plan

TA'd 06/17/91
RKB 3671'
GL 3660'

