Form 3160-5 (April2004)

## UNITEDSTATES DEPARTMENT OF THE INTERIOR D-ARTESIA

FORMAPPROVED

## OM B No. 1004-0137 Expires: March 31, 2007 BUREAU OF LAND MANAGEMENT 5. Legase Serial No. NMNM04228 SUNDAY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name bt use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on reverse side. NMNM682294 1. Type of Well Oil Well X Gas Well Other 8. Well Name and No. **BIG EDDY UNIT #153** 2. Name of Operator 9. API Well No. BEPCO, L.P. 30-015-34012 3a. Address 3b. PhoneNo. (include area code) P.O. BOX 2760 MIDLAND TX 79702-2760 (432)683-2277 10. Field and Pool, or Exploratory Area QUAHADA RIDGE (ATOKA) 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State SWSE, 660 FSL, 1980' FEL, SEC 20, T21S, R29E EDDY NM 12. CHECK APPROPRIATE BOX(ES)TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Acidize Deepen Production (Start/Resume) Water Shut-Off Notice of Intent Alter Casing Reclamation Well Integrity OtherRECOMPLETE TO Casing Repair New Construction X Recomplete X Subsequent Report Change Plans Temporarily Abandon THE ATOKA Plug and Abandon ☐ Final Abandonment Notice Convert to Injection PlugBack Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) ON 12-11-2006 THE MORROW WAS TEMPORARILY ABANDONED WITH THE PLACEMENT OF A HORNET PACKER WITH 10K GLASS DISC (PLUG IN PLACE) WITH THE FULL ASSEMBLY AT A TOTAL DEPTH OF 12,189'. IT IS BEPCO'S INTENTION TO COMMINGLE THE MORROW AND ATOKA AT SOME TIME IN THE FUTURE. PLEASE FIND A SUBSURFACE EQUIPMENT REPORT AS A COMPLETE DESCRIPTION OF THE EQUIPMENT IN THIS WELLBORE. THE QUAHADA RIDGE (ATOKA) WAS PERFORATED AT 11,534 - 544' 48 HOLES, 11,690' - 706' 48 HOLES, 11, 11,460'. WELL WAS 746' - 760' 42 HOLES. A BAKER 2-3/8" X 7" HORNET MECHANICAL PACKER WA RETURNED TO PRODUCTION ON 12/21/2006. 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) PRODUCTION CLERK OF LAND MANAGEMENT

Signature 03/30/2007 Date THIS SPACE FOR FEDERAL OR STATE OFFICE USE Title Date Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ANN MOORE

## SUBSURFACE EQUIPMENT INSTALLATION REPORT

OPERATOR: BASS ENTERPRISES PRODUCTION COMPANY FIELD: GOLDEN LANE MORROW COUNTY: EDDY, NM LEASE: BIG EDDY UNIT WELL: 153 TOTAL DEPTH: PBTD: 12763' TOF: DATE OF INSTALLATION: 12/20/2006 REASON FOR INSTALLATION: RECOMPLETE IN ATOKA

PERFS: 11534' - 44', 11690' - 706', 11746' - 760' (ATOKA) DEPTHS ARE SHOWN FROM: GL - KB = 26.60'

	BELOW PLUG 12538' - 546' & 12625' - 638' (MIDDLE MORROW)								
NO. OF JOINTS	DESCRIPTION	THDS OFF LENGTH	FROM	то					
	PAGE 2			0.00					
	BAKER 5 1/2" X 2 3/8" MODEL L - 10 INVERTED ON/OFF TOOL W/ 1.875" ID	1.54	12164.71	12166.25					
	2 7/8" X 2' L-80 TUBING SUB	1.75	12166.25	12168.00					
1	BAKER 7" RELIANT HORNET PACKER	8.63	12168.00	12176.63					
1	2 3/8" X 6' N-80 TUBING SUB	6.05	12176.63	12182.68					
1	2 3/8" BAKER "F" PROFILE NIPPLE W/ 1.875" ID	0.98	12182.68	12183.66					
1	2 3/8" X 4' N-80 TUBING SUB	4.05	12183.66	12187.71					
1	2 3/8" BAKER MAGNUM BLAST DISK (DISK IN PLACE)	1.34	12187.71	12189.05					
1	2 3/8" WIRELINE RE-ENTRY GUIDE	0,33	12189.05	12189.38					
			12189.38						
	PERMANENT PACKER ASSEMBLY								
	BAKER 7" MODEL DB PERMANENT PACKER W/ BOX DOWN	3,88	12458.00	42464.69					
	2 7/8" EUE 8RD 6.5# L - 80 TUBING W/ AB MODIFIED COUPLINGS	30,71	12458.00	12461.88 12492.59					
	2 7/8" BAKER "F" PROFILE NIPPLE W/ 2,250 ID	1.03	12492.59	12492.59					
	SCHLUMBERGER MECHANICAL GUN RELEASE ( GUNS RELEASED & DROPPED 12/22/05 )	1.60	12492.59	12493.02					
	SCHLUMBERGER MECHANICAL GUN RELEASE (GUNS RELEASED & DROFFED 12/22/05)	1.00	12495.02	12495.22					
	DROPPED GUN ASSEMBLY (JUNK IN HOLE)	2.15							
1	SCHLUMBERGER DEBRIS / CIRCULATION SUB	31,45							
1	2 7/8" EUE 8RD 6,5# L - 80 TUBING W/ AB MODIFIED COUPLINGS	0,45							
1	2 7/8" X 2 3/8" X - OVER	4.73							
1	SCHLUMBERER FIRING HEAD	5.04							
1	SAFETY SPACER	100.00							
1	4 1/2" SHCLUMBERGER GUNS & SPACERS	0.30							
1	BULL NOSE								
·····		144.12							
	TOTAL LENGTH OF JUNK	12618.88							
	ESTIMATED TO TOP OF FISH	<u> </u>	1						

REMARKS:

REPORTED BY: DEAN CLEMMER DATE: 12/20/2006

## SUBSURFACE EQUIPMENT INSTALLATION REPORT

OPERATOR:	BASS ENTERPRISES	PRODUCTION COMPANY	FIELD: GOLDEN L	ANE M	ORROW		COUNTY:	EDDY, NM
LEASE: BIG EDDY U	NIT	WELL: 153	TOTAL DEPTH:		PBTD: 12763'	TOF:	DATE OF INSTALLATION:	12/20/2006

REASON FOR INSTALLATION: RECOMPLETE IN ATOKA

DEPTHS ARE SHOWN FROM: GL - KB = 26.60' PERFS: 11534' - 44', 11690' - 706', 11746' - 760' (ATOKA)

PERFS: 11534' - 44', 11690' - 706', 11746' - 760' (ATOKA)

BELOW PLUG 12538' - 546' & 12625' - 638' (MIDDLE MORROW)

	BELOW PLUG 12538' - 546' & 12625' - 638' (MIDDLE MORROW)								
NO. OF JOINTS	DESCRIPTION	THDS OFF LENGTH	FROM	то					
	PAGE 1			0.00					
	TUBING INSTALLATION								
	ROTARY CORRECTION	27.80	0.00	27.80					
1	2 3/8" X 8' N-80 TUBING SUB	8.20	27.80	36.00					
349	2 3/8" EUE 8RD 4.7# L-80 TUBING W/ AB MODIFIED COUPLINGS	11385.20	36.00	11421.20					
1	2 3/8" BAKER "F" PROFILE NIPPLE W/ 1.875" ID	0.98	11421.20	11422.18					
1	2 3/8" EUE 8RD 4.7# L-80 TUBING W/ AB MODIFIED COUPLINGS	32.60	11422.18	11454.78					
1	2 3/8" BOX X 2 7/8" PIN X-OVER	0.66	11454.78	11455.44					
1	2 7/8" BAKER MODEL L-10 ON / OFF TOOL W/ 1.875" ID	1.82	11455,44	11457.26					
1	BAKER 7" RELIANT HORNET PACKER	7.96	11457.26	11465.22					
1	2 7/8" BOX X 2 3/8" PIN X-OVER	0.68	11465.22	11465.90					
1	2 3/8" X 6' N-80 TUBING SUB	6.16	11465.90	11472.06					
1	2 3/8" BAKER "F" PROFILE NIPPLE W/ 1.875" ID	0.98	11472.06	11473.04					
1	2 3/8" X 4' N-80 TUBING SUB	4.10	11473.04	11477.14					
1	2 3/8" MAGNUM BLAST DISK	1.35	11477.14	11478.49					
1	2 3/8" WIRELINE RE-ENTRY GUIDE	0.33	11478.49	11478.82					
<del>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</del>			11478.82						
····									
				·					
	CONTINUED ON PAGE 2								
		<del>                                     </del>							
			- <del></del>						
		<u> </u>							

REMARKS:

REPORTED BY:DEAN CLEMMER

DATE: 12/20/2006