<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 1000 Rio Person Road, Artec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

Surface Owner: Polic

Lines 🔯 Unificed 🔲

high water elevation of ground water.)

Dopin to ground water (vertical distance from bottom of pit to sent

Wellhood protection area: (Less than 200 feet from a private de

water neuros, or loss than 1000 feet from all other unior sources.)

Distance to surface water: (horizontal distance to all wetlands, playes,

imigation canals, disches, and postunial and ephonomic watercourses.)

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Long them 40 first

100 fort or more

1980 fact or more

Yes

No

50 feet or sneet, but less than 100 feet

200 fact or more, but has than 1000 fact

175

For drilling ng and production facilities, submit to to NMOCD Deader Office. Intrema facilities, submit to Santa Po

Form C-144

June 1, 2004

office Month

(20 points)

(10 points)

(O points)

(20 points)

(Opoints)

(20 points)

(10 points)

(Opeints)

0

ර

0

Pit or Below-Grade Tank Registration or Closure OCD - WILLIA , Is pit or below-grade tank covered by a "general plan"? Yes \ No \(\times\) No cities: Registration of a pit or below-grade tank \(\times\) Course of a pit or below-grade tank Type of se Men bourne 88241 NM P.O. Box 5270 R25E T205 AFT # 30-015-34343 stong DrAW 9 Fed Poon # 1 ₩N32'35'36.1" Length WIO4'29'003" NAD: 1927 1983 [] ral 🔀 Stato 🔲 Privato 🔲 Indiae 🔲 er-exacto to Wi Type of Suit True: Drilling M Production [] Disposel [] Workswer | Bracegorey | d, with lack detection? You [[Knet, explain vely not Liner type: Synthetic 🖄 Thickness 🖊 💆 mil Chy 🔲

Ranking Score (Total Points) 0 If this is a nit clusure: (1) Attack a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the canite box if your are burying in place) omite 🛱 officie 🔲 If offices, same of facility ... (3) Attack a general description of remodial action taken including remediation start date and end date. (4) Groundwater encountered: No 🖸 Yes 🔲 If yes, show depth below ground surface ft. and stiach sample results. (5) Altrich soil encycle results and a dip Keter IAN Additional Comments:

has been/will be constructed or closed according to MMOCD guidelines 🔀 a general permit 🗋 or an (attached) alternative OCD-approved plan 📋 Your certification and NMOCD a Approvat: Printed Name/Title Extracural

I hereby certify that the information above in true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade (ank

Notify OCD 24 hours prior to beginning pit closure.

- Samples are to be obtained from pit area and analysis submitted to NMOCD prior to back-filling



P.O. Box 310 Hobbs, NM 88241-0310

New Mexic Environmental Services

Hobbs. New Mexico 505.392.8584 Cell 505.631.2442 Fax 505.392.3085

Hobbs, New Mexico

Reserve Pit Remediation

SURFACE PIT CLOSURE PLAN

PIT PARAMETERS

COMPANY: Mewbourne Oil Co.

WELL SITE: Long Draw 9 Fed Com #1

LEGAL DESCRIPTION: Unit A Sec 9 T20s R25e, 660

FNL 660 FEL, Eddy co.

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 150' X 150' X 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1800 yards. The burial cell is to be excavated and lined with a minimum 12 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cuttings will be loaded as to allow for > 36" freeboard to ground level. After the cuttings are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the

edge of the burial cell. This cap will be constructed as to slope and allow for water runoff from burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.