District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Eio Benzos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87565

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For descriptions facilities, submit to Santa Fo

Form C-144 June 1, 2004

Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure

| Is pit or below-grade tank covered by a "general plant"? Yes No No No No No No No N | | | |
|---|--|--|--|
| A | (5 R) 623-5500 | | |
| Address: 401 Congress Are, ste 2700, | Auctia TX 78701 | | |
| Pacific or well suppor FAST Millman Unit # 232 AFT # | 35-015-34860 BMCONDE + | See 15 T 195 R28E | |
| County: Edd y Latin | N32: 39' 39. 2" | "A7"33.5" NAD- 1927 [7] 1913 [7] | |
| | | | |
| Surface Owner: Federal State Private Indian | | | |
| | Rhannshink | | |
| Type: Drilling X Production Disposal C | Volume:bhi Type of fluid: | | |
| Wedower Benegency | Construction material: | | |
| Lines of Unified | Double-walled, with lask detection? Yes [If not, explain why not. | | |
| Liner type: Synthetic Thickness 12 mil Clay [| | | |
| Pit Valumot&l | | | |
| Doub to ground water (vertical distance from bottom of pit to sonsonal | Loss them 50 first | (29 points) | |
| high water elevation of ground water.) | 50 fout or more, but less than 100 fout | (10 points) | |
| | 150' | (O points) | |
| | Yes | (20 points) | |
| Wellhard protection area: (Less than 200 fact from a private demostic | No | (O points) | |
| water source, or less than 1600 feet from all other water sources.) | | | |
| Distance to surface water: (horizontal distance to all wetlands, player, | Loss them 200 first | (20 points) | |
| inigation canals, ditches, and percential and ophomeral watercommon.) | 200 feet or mose, but less than 1000 feet | (10 points) | |
| | 1000 fact or mage. | (Opeints) | |
| | Ranking Store (Total Points) | 0 | |
| modistion start date and end date. (4) Groundwater encountered: No jù b) Attach soil example results and a fingurar of mangle locations and excess Additional Comments: Relief to AHA CLed | | ft. and strach sample results. | |
| | | | |
| I bereby certify that the information above is true and complete to the brings been will be constructed or closed according to MMOCD guidelf | ed of my knowledge and bolick. I further certify the | at the above-described pit or below-grade tank | |
| Date: 5/24/67 Printed NamorTillo Dusky L. Wilson/Feld Hage. | + sold y | | |
| Your cordification and NMOCD approval of this application/olsoure does otherwise endanger public health or the environment. Nor does it willow regulations. | as not referre the operator of Estado should be control to operate of its responsibility for compliance with | rate of the pit or track conteminate ground water or it any other folicial, state, or local laws and/or | |
| Approval: | | -11 | |
| Printed Nume/Title | Same WALCK SUNAM | Date: 6/5/07 | |
| tomy of the state | amples are to be obtained from it area and analysis submitted to | | |

NMOCD prior to back-filling



P.O. Box 310 Hobbs, NM 88241-0310

New Mexic Environmental Services

Hobbs. New Mexico

Hobbs, New Mexico

Reserve Pit Remediation

505.392.8584

Cell 505.631.2442 Fax 505.392.3085

SURFACE PIT CLOSURE PLAN

PIT PARAMETERS

COMPANY: Ameristate Exploration

WELL SITE: East Millman Unit #232

LEGAL DESCRIPTION: Unit H Sec 15 T19s R28e, 2610

FNL 1090 FEL, Eddy co.

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 120' X 120' X 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1400 yards. The burial cell is to be excavated and lined with a minimum 12 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cuttings will be loaded as to allow for > 36" freeboard to ground level. After the cuttings are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the

edge of the burial cell. This cap will be constructed as to slope and allow for water runoff from burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.

AMERISTATE EXPLORATION L.L.C. EAST MILLMAN UNIT #232 API#30-015-34860 V-DOOR NORTH

