Form 3160-5 (April 2004)

UNITED STATES

Oil Cons. N.M. DIV-Dist. 2 DEPARTMENT OF THE INTERIOR 1301 W Grand Avenue

FORM APPROVED OMB No 1004-0135

BUREAU OF LAND MANAGI	Artesia, NM 88210				
SUNDRY NOTICES AND REPOR	5. Lease Serial No.				
Do not use this form for proposals to di	NM-22614				
abandoned well. Use Form 3160-3 (APD) f	6. If Indian, Allottee or Tribe Name				
SUBMIT IN TRIPLICATE - Other instr	ructions on reverse side	7. If Unit or CA/Agreement, Name and/or No			
Type of Well Oil Well A Gas Well Other		8 Well Name and No			
A Sec 11st	11111 0 0 000				
2 Name of Operator	JUN 29 2007	Mike Harvey TR Federal #4			
Yates Petroleum Corporation	OCD 4 PT	9. API Well No			
3a. Address	3b Phone No (include area code),	30-005-61878			
105 S. 4th Str., Artesia, NM 88210	505-748-1471	10 Field and Pool, or Exploratory Area			
4 Location of Well (Footage, Sec ,T.,R.,M , OR Survey Description)		Pecos Slope; Abo			
		11 County or Parish, State			
1780'FNL & 2480'FWL of Section 3-T5S-R24E (Ur	nit F, SENW)	Chaves County, New Mexico			
12. CHECK APPROPRIATE BOX(ES) TO	INDICATE NATURE OF NOTICE, RI	EPORT, OR OTHER DATA			
TYPE OF SUBMISSION	TYPE OF ACTION				
Acidize	Deepen Production	(Start/Resume) Water Shut-Off			
X Notice of Intent Alter Casing	Fracture Treat Reclamation	n Well Integrity			
Casing Repair	New Construction Recomplete				
Subsequent Report Change Plans	X Plug and Abandon Temporani				
Change Trails	Tag and Abandon Temporating	y Nowington			
Final Abandonment Notice Convert to Injection	n Plug Back Water Disp	ater Disposal			
13 Describe Proposed of Completed Operation (clearly state all pertinent details, if the proposal is to deepen directionally or recomplete horizontally, give subsurvatanthe Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a matesting has been completed. Final Abandonment Notices shall be filed only a determined that the site is ready for final inspection.) Yates Petroleum Corporation plans to plug and ab	urface locations and measured and true vertical depths of all p No on file with BLM/BIA. Required subsequent reports sh multiple completion or recompletion in a new interval, a Form after all requirements, including reclamation, have been com-	pertinent markers and zones nall be filed within 30 days n3160-4 shall be filed once pleted, and the operator has			
1: Rig up all safety equipment as needed. No casi Spot a 25 sx Class "C" cement plug from 1385'-WOC and tag plug. (No LEMENT BEHING. 3. Spot a 25 sx Class "C" cement plug from 840'-9 WOC and tag plug.	1485'. This puts 100' cement plug or CASINE.)	ver the top of the Glorieta.			

- 4. Spot a 15 sx Class "C" cement plug from 60' up to the surface.
- 5. Remove all surface equipment, weld dry hole marker and clean location as per regulations.

SEE ATTACHED FOR NOTE: Yates Petroleum Acceptation will use steed pits and no earth pits CONDITIONS OF APPROVAL

14 I hereby certify that the foregoing is true and correct		
Name (Printed/Typed) Tina Huetta 2 2007	itle Regulatory Compliance Supervis	sor
Signature Gerry Guye, Deput Field Inspector	Date June 25, 2007	
THIS SPACE FOR FEI	RAL OR STATE OFFICE USE	
Approved by /S/ ALEXIS C. SWOBODA	PRITROLEUM ENGINEERDate	JUN 27 2007
Conditions of approval, if any, are attached. Approval of this notice does not watcerfully that the applicant holds legal or equitable title to those rights in the subjective which would entitle the applicant to conduct operations thereon.	nt or	
Title 18 U S C Section 1001 and Title 43 U S C Section 1212, make it a crime for	person knowingly and willbully to make to any department	or agency of the United

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

		/ TR Federal #4	Chaves County				
LOCATION	1780 FNL 8	& 2480'FWL Sec 3-					
GL: 3964'	8964' ZERO: KB: 3973.2' ATE. 12-21-82 COMPLETION DATE: 2-5-83			CASING PROGRA	CASING PROGRAM		
				10 3¼"40.5# J-55	890"		
COMMENTS				4 ½" 9 5# J-55	4099'		
			1 15 ave surface plus				
		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	', 15 sxs surface plug				
14 3/4"	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\						
hole	> / / /	1/ \ \ \					
	/ / \						
				After			
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	1 1/3					
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\						
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		10 ¾" @ 890'				
			w/700 sx(circ 50 sx)				
			100', 840'-940', 25 sxs	plug across surface casing shoe			
	\\\	~~\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\					
	1,1	~~ / / /	100' 1 385'-1 485' 25	sxs plug over top Glorieta			
1" from 1500' to su	rface	~~	7,000 7,400 720	one plag ever top chorieta			
	7						
	}						
	()	/					
7 7/8"	}						
hole	}						
	2) TOC 6) 2970', CBL				
	57	100 @	, 2970 , OBL				
	$\langle \langle $						
		\\ \					
CIBP @ 3500 w/35' cmt) ~	//					
	\\		3506'-3558',14 les, shot on				
	5/1	1/28/8:					
	>\		0000# 20/40 Sd				
	}/						
	<u> </u>	1//		San Andres 525'			
)/	1\(Glorieta 1485' Abo 3471'			
		// 4 ½ @					
	()	w/650					
	\\	BTD 4034'					
	T	D 4100'					