Form 3 160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT OCD-ARTESIA

FORM APPROVED OMB No. 1004-0135 Expires Jnovember 30, 2000

Lease Serial No. 5

NM-88136 6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS											
Do	not	use	this	form	for	proposals	to	drill	or	reenter	an
abandoned well. Use Form 3160-3 (APD) for such proposals.											

SUBMIT IN TRIPLIC	CATE - Other instructions	on reverse side	7. If Unit or CA/Agreement, Name and/o					
1. Type of Well	П.,		8. Well Name and No.					
2. Name of Operator	Other		Corral Draw AQH Federal #7 20474					
Yates Petroleum Corporati	on 25575		9 API Well No.					
3a. Address	3b.	Phone No. (include area code)	30-015-35058					
105 South Fourth Street, A	rtesia, NM 88210 (50	5) 748-1471	10. Field and Pool, or Exploratory Area					
4. Location of Well (Footage, Sec.,		- 0007	Pierce Crossing, Bone Spring, East 96473					
330' FSL and 990' FWL		JUL 2 6 2007	11. County or Parish, State					
Section 13, T24S-R29E		OCD-ARTESIA	Eddy County, New Mexico					
12. CHECK APPRO	PRIATE BOX(ES) TO INDICA	TE NATURE OF NOTICE, REP	ORT, OR OTHER DATA					
TYPE OF SUBMISSION		TYPE OF ACTION						
Notice of Intent	Acidize Alter Casing	Deepen Production Fracture Treat Reclamatio	(Start/Resume) Water Shut-Off Well Integrity					
X Subsequent Report	Casing Repair	New Construction Recomplete Plug and Abandon Temporaril						
Final Abandonment Notice	Convert to Injection	Plug Back Water Disp	osal					
Describe Proposed or Completed Operations (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days Following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once Testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Yates Petroleum Corporation wishes to extend the captioned well's APD expiration date for two (2) years to July 28, 2009. (C-144 attached)								
Sources at Yates Petroleum Co	orporation have relayed inform	nation to me that they believe t	here will not be enough H2S					
anticipated from the surface to	, -	meet the OCD's minimum requ	uirements for the submission					
of a contingency plan per rule 1	118.	App	POVED - 94					
Thank you.		END	ROVED FOR 24 MONTH PLAGOR					
		Email cy@ypcnm.com Title: Regulatory Agent / L	and Department					
Signature Signature		Date June 28, 2007						
	THIS SPACE FOR F	EDERAL OR STATE USE						
Approved by /s/ Don	Peterson FOR	PIELD MANAGE	R Date JUL 2 4 2007					
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent which would entitle the applicant to conductive to the conductive terms of t	table title to those rights in the subject l							
Title 18 U.S.C. Section 1001, make states fictitious or fraudulent state	e it a crime for any person know ments or representations as to an	ringly and willfully to make to any matter within its jurisdiction.	department or agency of the United					

/District I

4625 N. French Dr., Hobbs, NM 88240

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

State of New Mexico

Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION 1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-102 Revised October 12, 2005 Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

27.01.107.0										
1220 S. St. Francis Dr., Santa Fe, NM 87505									DED REPORT	
		V	VELL LO	CATION	I AND ACRE	EAGE DEDICA	ATION PLAT			
i	API Numbe	r		² Pool Code ³ Pool Name						
3	0-015-3505	8		96473	ring, East					
⁴ Property		k		6 Wel	⁶ Well Number					
20474				COL	7					
7 OGRID	No.		· · · · · · · · · · · · · · · · · · ·		, E	⁹ Elevation				
02557	5			YATES	3056'					
			•		¹⁰ Surface L	ocation				
UL or lot no.	Section	Township Range Lot Idn Feet from the North/South line Feet from the				East/West line	County			
M	13	248	29E		330	SOUTH	990	WEST	EDDY	
	•		11 Bo	ttom Hol	e Location If	Different From	Surface			
UL or lot no. Sec		Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County	
12 Dedicated Acre 40 SWSW	es ¹³ Joint o	or Infill 14 (Consolidation C	Code 15 Ord	ler No.		<u>_</u>			

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

16			17 OPERATOR CERTIFICATION
			I hereby certify that the information contained herein is true and complete
			to the best of my knowledge and belief, and that this organization either
1			owns a working interest or unleased mineral interest in the land including
(the proposed bottom hole location or has a right to drill this well at this
			location pursuant to a contract with an owner of such a mineral or working
			interest, or to a voluntary pooling agreement or a compulsory pooling
			ordermeretofare entered by the division
			6/28/07
1			Signature Date
			Signature
			Cy Cowan
		 	Printed Name
			Regulatory Agent Title
			T8SURVEYOR CERTIFICATION
			I hereby certify that the well location shown on this
			it and the second secon
			plat was plotted from field notes of actual surveys
			made by me or under my supervision, and that the
			same is true and correct to the best of my belief.
			Day 60
			Date of Survey
NM-88136			Signature and Seal of Professional Surveyor
			REFER TO ORIGINAL PLAT
	Shire		
	F.		
990'			
330			Certificate Number
	4	1	

DISTRICT I 1626 M. Franch Br., Hobbs, 191 86240 DISTRICT II 811 South First, Artesia, NM 88210 bistrict III · 1006 Rio Brazos Rd., Astec, NM 87410

DISTRICT IV 2040 South Pacheco, Santa Fe, NM 87605

N.440774.4 E.661921.1 (NAD-83)

1650' 1980' 2310'

2310' 1980'

1650

990'

860'

330'

660'

890'

990

330'

State of New Mexico Energy, Minerale and Natural Resources Department

Form C-102 Revised March 17, 1999 Instruction on back Submit to Appropriate District Office

CORPAN DRAW 7 100 ENERAL STREETH STREE

GENERAL

State Lease - 4 Copies Foe Lease - 3 Copies


OIL CONSERVATION DIVISION P.O. Box 2088

Santa Fe, New Mexico 87504-2088

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number			Pool Code Pool Name							
			<u> </u>				ldcat Bone Sj			
Property (Code			01	Property N ORRAL DRAW "A			Well No	ımber	
OGRID No	<u> </u>		· · · · · · · · · · · · · · · · · · ·		Operator N				Kievation.	
025575				YAT	ES PETROLEUM			3056		
<u> </u>		<u></u>			Surface L	ocation		 		
UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County	
м	13	245	29E	1	330	SOUTH	990	WEST	EDDY	
			Bottom	Hole L	ocation If Di	ferent From Su	rface	1	<u> </u>	
UL or lot No.	Section	Township	Range	Lot Ma		····	Foet from the	East/West line	County	
				1						
Dedicated Acres	Joint o	or Infill Co	molidation	Code	Order No.					
40				1						
NO ALLO	WABLE 1	WILL BE A	SSIGNED	TO THIS	COMPLETION	UNTIL ALL INTE	RESTS HAVE B	EEN CONSOLIDA	ATED	
		OR A 1	iate-non	NDARD U	JNIT HAS BEE	N APPROVED BY	THE DIVISION			
				1			7			
							OPERATO	OR CERTIFICAT	TON	
				ľ				y certify the the in		
					}		11	n to true and compl viodes and batter.	ece to the	
:				1	j					
	ļ			1				71 may		
				 			Signature			
				}			/	Cy Cowan		
	1				1		Printed Nam			
							<u> </u>	egulatory Ag	ent	
				1	ļ		Title	ine 13, 2006		
							Date	ine 13, 2000	<u></u>	
					ļ		CHIDADA	OR CERTIFICAT	TON	
				 				A CERTIFICAT	1014	
	Ī							y that the well locate		
					İ		on this plat w	as plotted from field	notes of	
							supervison, or	of that the same is	true and	
	I			ı			correct to th	e best of my belief	2.	
					ı		11			
	ľ			1	ĺ	<u>.</u>		5/25/2006		
·•							Date Surveye	a e		
No Po	21			1		***************************************	Signature & Professional	Secretary L.		
NW-881	<i>>></i> 0 ▮			1	ł		1 1/4	SEW MEY ON		
		N.32°12 W.103°5	40.2	Į	ł			N. John	<i>[3</i>	
3051	30	- W.103°5	8'38.4"	1	ŀ		11 ~43/		_	



State of New Mexico Energy Minerals and Natural Resources

Form C-144 March 12, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

	de Tank Registration or Clos k covered by a "general plan"? Yes \(\) N r below-grade tank \(\) Closure of a pit or below-g	
Operator: YATES PETROLEUM CORPORATION Telephone: (505) 748-14 Address: 105 South Fourth Street, Artesia, NM 88210 Facility or well name: Corral Draw AOH Federal #7 API #: 30-0/5-3 County: Eddy Latitude N.32'12'40.2" Longitude W.103'56'36.4"	71 e-mail address:	S R 29E
Pit	Below-grade tank	
Type: Drilling X Production Disposal	Volume:bbl Type of fluid:	
Workover Emergency	Construction material:	
Lined X Unlined	Double-walled, with leak detection? Yes [] If	
Liner type: Synthetic X Thickness 12 mil Clay Volume 20,000 bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points) 0
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points) 0
Pietros to surface nutters (horizontal distance to all untlands planes	Less than 200 feet	(20 points)
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
ingagon catalo, orones, and percential and epitement watercomses.)	1000 feet or more	(0 points) 0
	Ranking Score (Total Points)	0
If this is a pit closure: (1) attach a diagram of the facility showing the pit's onsite offsite If offsite, name of facility date. (4) Groundwater encountered: No Yes If yes, show depth belo diagram of sample locations and excavations.	(3) Attach a general description of remedial a	action taken including remediation start date and end
I hereby certify that the information above is true and complete to the best of a been/will be constructed or closed according to NMOCD guidelines [], a Date: June 20, 2005 Printed Name/Title Cy Cowan, Regulatory Agent Your certification and NMOCD approval of this application/closure does not a otherwise endanger public health or the environment. Nor does it relieve the or regulations.	general permit X or ap (attached) alternative O Signature Signature relieve the operator of hability should the contents	CD-approved plan
Approval: Date: Printed Name/Title Semi W. Sterre Visited II Semesore	Signature Bh /a	2

CONDITIONS OF APPROVAL - DRILLING

Operator's Name: Well Name & No.

YATES PETROLEUM CORPORATION
7 – CORRAL DRAW AQH FEDERAL

Location:

330' FSL & 990' FWL – SEC 13 – T24S – R29E - EDDY

Lease:

NM-88136

I. DRILLING OPERATIONS REQUIREMENTS:

- **A.** The Bureau of Land Management (BLM) is to be notified a minimum of 4 hours in advance for a representative to witness:
 - 1. Spudding well
 - 2. Setting and/or Cementing of all casing strings
 - 3. BOPE tests
 - Eddy County call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (505) 361-2822
- **B.** Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.

II. CASING:

- A. The 13-3/8 inch surface casing shall be set at 500 feet and cemented to the surface.
 - 1. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with a surface log readout will be used or a cement bond log shall be run to verify the top of the cement.
 - 2. Wait on cement (WOC) time for a primary cement job will be a minimum of 12 hours for a non-water basin, 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compression strength, whichever is greater. (This is to include the lead cement)
 - 3. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compression strength, whichever is greater.
 - 4. If cement falls back, remedial action will be done prior to drilling out that string.
- **B.** The minimum required fill of cement behind the <u>8-5/8</u> inch intermediate casing is <u>circulate</u> cement to the surface. If cement does not circulate see A.1 thru 4.
- C. The minimum required fill of cement behind the <u>5-1/2</u> inch production casing is <u>tie back 200 feet</u> into the 8-5/8 inch casing.
- **D.** If hardband drill pipe is rotated inside casing; returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool I joints of the drill pipe will be installed prior to continuing drilling operations.

III. PRESSURE CONTROL:

- A. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Section 17.
- **B.** The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - 1. The tests shall be done by an independent service company.
 - 2. The results of the test shall be reported to the appropriate BLM office.
 - 3. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
 - 4. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug.
 - 5. A variance to test the surface casing and BOP/BOPE to the reduced pressure of <u>1000</u> psi with the rig pumps is approved.

LBabyak 7/20/07