

District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM 87505



State of New Mexico
Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144
June 1, 2004

For drilling and production facilities, submit to
appropriate NMOCD District Office
For downstream facilities, submit to Santa Fe
office

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐

Type of action Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator Yates Petroleum Corporation Telephone 505-748-4500 e-mail address mikes@yepcnm.com

Address 105 South 4th Street, Artesia, NM 88210

Facility or well name Jumper BIP Federal #5 API # 30-015-28577 U/L or Qtr/Qtr E Sec 4 T 24S R 29E

County Eddy Latitude 32 24898 Longitude 103 99232 NAD 1927 ☒ 1983 ☐

Surface Owner Federal ☒ State ☐ Private ☐ Indian ☐

AUG 17 2007
OCD-ARTESIA

Pit

Type Drilling ☒ Production ☐ Disposal ☐

Work over ☐ Emergency ☐

Lined ☒ Unlined ☐

Liner type Synthetic ☒ Thickness 12 mil Clay ☐

Pit Volume 20,000 bbl

Below-grade tank

Volume _____ bbl Type of fluid _____

Construction material _____

Double-walled, with leak detection? Yes ☐ If not, explain why not _____

Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water)

Less than 50 feet

50 feet or more, but less than 100 feet

100 feet or more

(20 points) XXXX

(10 points)

(0 points)

Wellhead protection area (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources)

Yes

No

(20 points)

(0 points) XXXX

Distance to surface water (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses)

Less than 200 feet

200 feet or more, but less than 1000 feet

1000 feet or more

(20 points)

(10 points)

(0 points) XXXX

Ranking Score (Total Points)

20 points

If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks (2) Indicate disposal location (check the onsite box if you are burying in place)

onsite ☒ offsite ☐ If offsite, name of facility NA (3) Attach a general description of remedial action taken including remediation start date and end date (4) Groundwater

encountered No ☐ Yes ☐ If yes, show depth below ground surface _____ ft and attach sample results

(5) Attach soil sample results and a diagram of sample locations and excavations

Additional Comments Closure work plan for drilling pit An encapsulation trench will be constructed and lined with 12 mil synthetic liner next to existing drilling pit The drilling pit contents will be excavated and emplaced into the encapsulation trench using a mixture of eight to one pit material and Class H bulk cement or CKD The emulsion of pit material and cement will be mixed using a track hoe and water added if needed After completion of solidifying pit material in cement and pit contents have set in place for a minimum of 24 hours, the encapsulation trench will then be capped using a 20 mil synthetic liner placed over the pit contents with a minimum of a 3' over lap of the underlying trench areas The trench will then be backfilled to grade using a minimum of 3' of clean soil or like material A one call and 48 hour notification to OCD will be made before pit closure action begins Beginning pit closure date N/A Ending pit closure date N/A

(previously submitted 7/23/07 approved 8/6/07)

I hereby certify that the information above is true and complete to the best of my knowledge and belief I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☒, or an (attached) alternative OCD-approved plan ☐.

Date 08/15/2007

Printed Name/Title Mike Stubblefield / Environmental Regulatory Agent

Signature Mike Stubblefield

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations

If burial trench is to be constructed in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench.

Approval _____

Signed By Mike Stubblefield

AUG 17 2007

Signature _____

Date _____

NOTIFY OCD 24 HOURS PRIOR to beginning closure and 24 HOURS PRIOR to obtaining samples. Samples are to be obtained from pit area and analyses submitted to OCD prior to back-filling.

- As a condition of approval if during pit construction water is encountered or if water seeps into pits after construction the OCD MUST BE CONTACTED IMMEDIATELY.

(2)

District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144
June 1, 2004

For drilling and production facilities, submit to appropriate NMOC District Office
For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐
Type of action Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator Yates Petroleum Corporation Telephone 505-748-4500 e-mail address mikes@ypenn.com
Address 105 South 4th Street, Artesia, N M 88210
Facility or well name Juniper BIP Federal #5 API # 30-015-28577 U/L or Qtr/Qtr E Sec 4 T 24S R 29E
County Eddy Latitude 32 24898 Longitude 103 99232 NAD 1927 ☒ 1983 ☐
Surface Owner Federal ☒ State ☐ Private ☐ Indian ☐

AUG 17 2007
OCD-ARTESIA

Pit

Type Drilling ☒ Production ☐ Disposal ☐
Work over ☐ Emergency ☐
Lined ☒ Unlined ☐
Liner type Synthetic ☒ Thickness 12 mil Clay ☐
Pit Volume 20,000 bbl

Below-grade tank

Volume _____ bbl Type of fluid _____
Construction material _____
Double-walled, with leak detection? Yes ☐ If not, explain why not _____

Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water)

Less than 50 feet	(20 points) XXXX
50 feet or more, but less than 100 feet	(10 points)
100 feet or more	(0 points)

Wellhead protection area (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources)

Yes	(20 points)
No	(0 points) XXXX

Distance to surface water (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses)

Less than 200 feet	(20 points)
200 feet or more, but less than 1000 feet	(10 points)
1000 feet or more	(0 points) XXXX

Ranking Score (Total Points)

20 points

If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks (2) Indicate disposal location (check the onsite box if you are burying in place)

onsite ☒ offsite ☐ If offsite, name of facility NA (3) Attach a general description of remedial action taken including remediation start date and end date (4) Groundwater encountered No ☐ Yes ☐ If yes, show depth below ground surface _____ ft and attach sample results

(5) Attach soil sample results and a diagram of sample locations and excavations

Additional Comments Registration work plan for encapsulation trench An encapsulation trench will be constructed and lined with 12 mil synthetic liner next to existing drilling pit The drilling pit contents will be excavated and emplaced into the encapsulation trench using a mixture of eight to one pit material and Class H bulk cement or CKD The emulsion of pit material and cement will be mixed using a track hoe and water added if needed After completion of solidifying pit material in cement and pit contents have set in place for a minimum of 24 hours, the encapsulation trench will then be capped using a 20 mil synthetic liner placed over the pit contents with a minimum of a 3' over lap of the underlying trench areas The trench will then be backfilled to grade using a minimum of 3' of clean soil or like material A one call and 48 hour notification to OCD will be made before pit closure action begins Beginning pit closure date N/A Ending pit closure date N/A

(previously submitted 7/23/07 approved 8/6/07)

I hereby certify that the information above is true and complete to the best of my knowledge and belief I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☒, or an (attached) alternative OCD-approved plan ☐.

Date 08/15/2007

Printed Name/Title Mike Stubblefield / Environmental Regulatory Agent

Signature *Mike Stubblefield*

Your certification and NMOC approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations

If burial trench is to be constructed in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench.

Approval

Signed By *Mike Stubblefield*

AUG 17 2007

Signature


Date

NOTIFY OCD 24 HOURS PRIOR to beginning closure and 24 HOURS PRIOR to obtaining samples. Samples are to be obtained from pit area and analyses submitted to OCD prior to back-filling.

As a condition of approval if during pit construction water is encountered or if water seeps into pits after construction the OCD MUST BE CONTACTED IMMEDIATELY.

Reserve Pit Solidification Procedure

1. Diagram of deep burial trench(s) is provided with application for closure (form C-144)



Reserve pit 150' x 150'

2. **Solidification of Cuttings:**
 - (A) The cuttings will be mixed with a track hoe. Contents will be lifted and dropped so as to create a stirring process. This process will continue until CKD and pit contents are thoroughly bonded.
 - (B) The solidification material will be Cement Kiln Dust (CKD).
 - (C) CKD to pit contents ratio will be 1 yard of pit contents to 250 lbs. of CKD or 1,000 cubic yards of pit contents to 120 tons of CKD. Pit contents will be measure to determine actual volume (length' x width' x depth') /27. CKD is weighed and delivered to the site in 40,000 lb increments.

A 1,000 cubic yard work pit is constructed inside the original reserve pit beside the encapsulation/solidification trench. One thousand cubic yards of pit contents will be placed in the work trench along with six 20 ton loads of CKD to begin the mixing process.

 - (D) Water may be introduced to initiate the bonding process of CKD and pit Contents.
 - (E) In order to assure proper mixing, all CKD is precisely weighed before delivery and pit construction is measure to a predetermined need depending on exact volume of pit contents.
3. A minimum of three representative samples will be taken from pit contents Prior to any work. These samples will be stored in a closed container.
4. Each stage being mixed will be sampled prior to transferring the slurry to the deep trench as follows:
 - (A) One sample of the slurry will be taken at the beginning of the transference and stored in a closed container.

- (B) One sample of the slurry will be taken at the beginning of the transference and stored in an open container.
 - (C) One sample of the slurry will be taken at the end of the transference and stored in a closed container.
 - (D) One sample of the slurry will be taken at the end of the transference and stored in an open container.
5. All samples will be stored in environmentally approved containers.
 6. All samples and associated paperwork will be delivered to the OCD office within 3 working days of closure.

New Mexico Office of the State Engineer
POD Reports and DownloadsJUNIPER BIP FEDERAL #5
30-015-28577

Township: 24S Range: 29E Sections:

NAD27 X: Y: Zone: Search Radius:

County: Basin: Number: Suffix:

Owner Name: (First) (Last) ☐ Non-Domestic ☐ Domestic ☒ All

POD / Surface Data Report

Avg Depth to Water Report

Water Column Report

Clear Form

iWATERS Menu

Help

AVERAGE DEPTH OF WATER REPORT 07/23/2007

Bsn	Tws	Rng	Sec	Zone	X	Y	Wells	(Depth Water in Feet)		
								Min	Max	Avg
C	24S	29E	16				1	18	18	18

Record Count: 1

This topographic map depicts the Malaga Bend area in New Mexico. The Pecos River flows through the center, with the Harroun Canal branching off to the north. The map features numerous contour lines indicating elevation, with labels such as 2900, 2950, 3000, 3050, and 3100. Key locations include Malaga Bend, Harroun, and Malaga. A well and a water tank are marked near the river. The map is overlaid with a grid showing coordinates: 104° 00' to 104° 57' 30" West and 35° 57' 30" to 36° 00' North. A scale bar at the bottom indicates distances in miles (0 to 5) and centimeters (0 to 2400).

'Pierce Canyon; NM' Scale: 1" = 0.379Mi, 610Mt, 2,000Ft, 1 Mi = 2.640", 1 cm = 240Mt