Form C-144 June 1, 2004

District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fc, NM 87505

## State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe office

Allstate Services

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes \( \subseteq \text{No} \subseteq X \)

Type of action: Registration of a pit or	r below-grade tank U Closure of a pit or below-gre	THE CHIEK LIV
0		
	e-mail address:	
	i U/LarOtr/Otr 1 Sec 20 T2	4S R 28E
Facility or well name: New Man Fed Com #1 API #: 30-015-34903 County: Eddy Latitude 32-12-03.10N		7 🖸 1983 🗖
	ongitude 104-06-13.60W NAD: 192	, C 1963 C
Surface Owner: Federal X State Private Indian		
Pit	Below-grade tank	
Type: Drilling X Production Disposal	Volume:bbl Type of fluid:	
Workover D Emergency D	Construction material:	
Lined X Ualined	Double-walled, with leak detection? Yes  hf not, explain why not.	
Liner type: Synthetic X Thickness 20/12mil Clay		
Pit Volumebbl		
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)XXX
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	( 0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
•	No	( 0 points)XXX
water source, or less than 1000 feet from all other water sources.)		
Distance to surface water: (horizontal distance to all wetlands, playes,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	( 0 points)XXX
	Ranking Score (Total Points)	20 points
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's	relationship to other equipment and tooks (2) India	ete ditmosti location: (check the oneite how if
		• •
your are burying in place) onsite X 🔲 offsite 🔲 If offsite, name of facility	(3) Attach a general description of remedial ac	tion taken including remediation start date and
end date. (4) Groundwater encountered: No 🗌 Yes 🔲 If yes, show depth t	below ground surfaceft. and attach s	ample results.
		ample results.
	ions.	
(5) Attach soil sample results and a diagram of sample locations and excavati	ions. In trench will be constructed and lined with a 12 mile	synthetic liner next to existing drilling pit.
(5) Attach soil sample results and a diagram of sample locations and excavate Additional Comments: Closure work plan for drilling pit. An encapsulation	ions.  In trench will be constructed and lined with a 12 mile at the constructed and lined with a 12 mile at t	synthetic liner next to existing drilling pit.
(5) Attach soil sample results and a diagram of sample locations and excavational Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsular emulsion of pit material and cement will be mixed using a trackhoe and water.	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying	synthetic liner next to existing drilling pit.  al and Class H bulk cement or CKD. The pit material in cement and pit contents have
(5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: Closure work plan for drilling pit. An encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation of pit material and cement will be mixed using a trackthoe and was set in place for a minimum of 24 hours, the encapsulation trench will then.	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfill	synthetic liner next to existing drilling pit.  al and Class H bulk cement or CKD. The pit material in cement and pit contents have
(5) Attach soil sample results and a diagram of sample locations and excavational Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsular emulsion of pit material and cement will be mixed using a trackhoe and water.	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfill	synthetic liner next to existing drilling pit.  al and Class H bulk cement or CKD. The pit material in cement and pit contents have
(5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: Closure work plan for drilling pit. An encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation of pit material and cement will be mixed using a trackfloe and was set in place for a minimum of 24 hours, the encapsulation trench will then.	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfill	synthetic liner next to existing drilling pit.  al and Class H bulk cement or CKD. The pit material in cement and pit contents have
(5) Attach soil sample results and a diagram of sample locations and excavation Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation will be mixed using a tracking and was set in place for a minimum of 24 hours, the encapsulation trench will then material and clean soil. A one call and 48 hour notification to OCD will be I hereby certify that the information above is true and complete to the best of the personnel.	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  of my knowledge and belief. I further carfify that a	nymthetic liner next to existing drilling pit.  al and Class H bulk cement or CKD. The pit meterial in cement and pit contents have ad to grade using a minimum of 3° of like  the above-described pit or below-grade tank
(5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: Closure work plan for drilling pit. An encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation of pit material and cement will be mixed using a trackhoe and was set in place for a minimum of 24 hours, the encapsulation trench will then the material and clean soil. A one call and 48 hour notification to OCD will be	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  of my knowledge and belief. I further cartify that a  X , a general permit , or an (attached) altern	and Class H bulk cement or CKD. The pit meterial in cement and pit contents have be to grade using a minimum of 3' of like the above described pit or below-grade task native OCD-approved plan .
The drilling pit contents will be excavated and emplaced into the encapsular emulsion of pit material and cement will be mixed using a tracking and was set in place for a minimum of 24 hours, the encapsulation trench will then material and clean soil. A one call and 48 hour notification to OCD will be I hereby certify that the information above is true and complete to the best of	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  of my knowledge and belief. I further cartify that a  X , a general permit , or an (attached) altern	and Class H bulk cement or CKD. The pit meterial in cement and pit contents have be to grade using a minimum of 3' of like the above described pit or below-grade task native OCD-approved plan .
(5) Attach soil sample results and a diagram of sample locations and excavation Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation of pit material and cement will be mixed using a tracking and was set in place for a minimum of 24 hours, the encapsulation trench will then a material and clean soil. A one call and 48 hour notification to OCD will be inhereby certify that the information above is true and complete to the best of has been/will be constructed or closed according to NMOCD guidelines.	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  of my knowledge and belief. I further cartify that a  X , a general permit , or an (attached) altern	nymthetic liner next to existing drilling pit.  al and Class H bulk cement or CKD. The pit meterial in cement and pit contents have ad to grade using a minimum of 3° of like  the above-described pit or below-grade tank
(5) Attach soil sample results and a diagram of sample locations and excavation Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be escavated and emplaced into the encapsulation the drilling pit contents will be escavated and emplaced into the encapsulation of pit material and cement will be mixed using a tracking and was set in place for a minimum of 24 hours, the encapsulation trench will then I material and clean soil. A one call and 48 hour notification to OCD will be I hereby certify that the information above is true and complete to the best of this been/will be constructed or closed according to NMOCD guidelines.  Date: 10/10/07	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  of my knowledge and belief. I further cartify that a  IX , a general permit , or an (attached) altern	nymthetic liner next to existing drilling pit.  al and Class H bulk cement or CKD. The pit meterial in cement and pit contents have be to grade using a minimum of 3' of like  the above described pit or below-grade tank native OCD-approved plan .
(5) Attach soil sample results and a diagram of sample locations and excavation Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contests will be escavated and emplaced into the encapsulation. The drilling pit contests will be escavated and emplaced into the encapsulation the drilling pit material and cement will be mixed using a trackthoe and was set in place for a minimum of 24 hours, the encapsulation trench will then the material and clean soil. A one call and 48 hour notification to OCD will be a likely certify that the information above is true and complete to the best of has been/will be constructed or closed according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title i Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  of my knowledge and belief. If further cartify that a  X , a general perint , or an interched) altern  of relieve the operator of liability should the contents	al and Class H bulk cement or CKD. The pit material in cement and pit contents have not to grade using a minimum of 3° of like the above-described pit or below-grade tank tantive Of D-approved plan
(5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: Closure work plan for drilling pit. An encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation for pit material and cement will be mixed using a tracking and was set in place for a minimum of 24 hours, the encapsulation trench will then a material and clean soil. A one call and 48 hour notification to OCD will be material and clean soil. A one call and 48 hour notification to OCD will be a hereby certify that the information above is true and complete to the best class been/will be constructed or closed according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not the certification and NMOCD approval of this application/closure does not the certification and NMOCD approval of this application/closure does not the certification and NMOCD approval of this application/closure does not certificate the certification and NMOCD approval of this application/closure does not certificate the certification and NMOCD approval of this application/closure does not certificate the certification and NMOCD approval of this application/closure does not certificate the certification and the	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  of my knowledge and belief. If further cartify that a  X , a general perint , or an interched) altern  of relieve the operator of liability should the contents	al and Class H bulk cement or CKD. The pit material in cement and pit contents have not to grade using a minimum of 3° of like the above-described pit or below-grade tank tantive Of D-approved plan
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation of pit material and cement will be mixed using a trackthoe and was set in place for a minimum of 24 hours, the encapsulation trench will then be material and clean soil. A one call and 48 hour notification to OCD will be material and clean soil. A one call and 48 hour notification to OCD will be a largely be constructed or clusted seconding to NMOCD guidelines.  I hereby certify that the information above is true and complete to the best of has been/will be constructed or clusted seconding to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title \(^1\) Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  of my knowledge and belief. If further cartify that a  X , a general perint , or an interched) altern  of relieve the operator of liability should the contents	al and Class H bulk cement or CKD. The pit meterial in cement and pit contents have ed to grade using a minimum of 3° of like the above described pit or below-grade tank native OCD-approved plan.
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation that the encapsulation of pit material and cement will be mixed using a trackflore and was set in place for a minimum of 24 hours, the encapsulation trench will then I material and clean soil. A one call and 48 hour notification to OCD will be interested and clean soil. A one call and 48 hour notification to OCD will be been will be constructed or clusted according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title Toan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Getty Guyo	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  If my knowledge and belief. I further cartify that a  IX , a general personal , or an (astoched) altern  Signature  At relieve the operator of liability should the contents a operator of its responsibility for compliance with a	al and Class H bulk cement or CKD. The pit meterial in cement and pit contents have bed to grade using a minimum of 3' of like the above described pit or below-grade tank native OCD-approved plan
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation of pit material and cement will be mixed using a trackthoe and was set in place for a minimum of 24 hours, the encapsulation trench will then be material and clean soil. A one call and 48 hour notification to OCD will be material and clean soil. A one call and 48 hour notification to OCD will be a largely be constructed or clusted seconding to NMOCD guidelines.  I hereby certify that the information above is true and complete to the best of has been/will be constructed or clusted seconding to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title \(^1\) Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit materi ter added if needed. After completion of solidifying be capped using a 20 mil synthetic liner and backfille made before action begins.  of my knowledge and belief. If further cartify that a  X , a general perint , or an interched) altern  of relieve the operator of liability should the contents	al and Class H bulk cement or CKD. The pit meterial in cement and pit contents have ed to grade using a minimum of 3° of like the above described pit or below-grade tank native OCD-approved plan.
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation that the encapsulation of pit material and cement will be mixed using a trackflore and was set in place for a minimum of 24 hours, the encapsulation trench will then I material and clean soil. A one call and 48 hour notification to OCD will be interested and clean soil. A one call and 48 hour notification to OCD will be been will be constructed or clusted according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title Toan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Getty Guyo	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk coment or CKD. The pit material in coment and pit contents have ad to grade using a minimum of 3° of like  the above described pit or below-grade tank tative OCD-approved plan .  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation that the encapsulation of pit material and cement will be mixed using a trackflore and was set in place for a minimum of 24 hours, the encapsulation trench will then I material and clean soil. A one call and 48 hour notification to OCD will be interested and clean soil. A one call and 48 hour notification to OCD will be been will be constructed or clusted according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title Toan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Getty Guyo	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	al and Class H bulk cement or CKD. The pit meterial in cement and pit contents have bed to grade using a minimum of 3' of like the above described pit or below-grade tank native OCD-approved plan
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation that the encapsulation of pit material and cement will be mixed using a trackflore and was set in place for a minimum of 24 hours, the encapsulation trench will then I material and clean soil. A one call and 48 hour notification to OCD will be interested and clean soil. A one call and 48 hour notification to OCD will be been will be constructed or clusted according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title Toan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Getty Guyo	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk coment or CKD. The pit moterial in coment and pit contents have ad to grade using a minimum of 3' of like  the above described pit or below-grade tank tative OCD-approved plan.  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation that the encapsulation of pit material and cement will be mixed using a trackflore and was set in place for a minimum of 24 hours, the encapsulation trench will then I material and clean soil. A one call and 48 hour notification to OCD will be interested and clean soil. A one call and 48 hour notification to OCD will be been will be constructed or clusted according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title Toan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Getty Guyo	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk coment or CKD. The pit moterial in coment and pit contents have ad to grade using a minimum of 3' of like  the above described pit or below-grade tank tative OCD-approved plan.  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
(5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: Closure work plan for drilling pit. An encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation trends of pit material and cement will be mixed using a trackflore and was set in place for a minimum of 24 hours, the encapsulation trench will then I material and clean soil. A one call and 48 hour notification to OCD will be interested and clean soil. A one call and 48 hour notification to OCD will be been been will be constructed or closed according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title i Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Approval.  Getty Guyo	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk coment or CKD. The pit material in coment and pit contents have ad to grade using a minimum of 3° of like  the above described pit or below-grade tank tative OCD-approved plan .  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
(5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: Closure work plan for drilling pit. An encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation trends of pit material and cement will be mixed using a trackflore and was set in place for a minimum of 24 hours, the encapsulation trench will then I material and clean soil. A one call and 48 hour notification to OCD will be interested and clean soil. A one call and 48 hour notification to OCD will be been been will be constructed or closed according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title i Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Approval.  Getty Guyo	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk coment or CKD. The pit material in coment and pit contents have ad to grade using a minimum of 3° of like  the above described pit or below-grade tank tative OCD-approved plan .  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
(5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: Closure work plan for drilling pit. An encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation trends of pit material and cement will be mixed using a trackflore and was set in place for a minimum of 24 hours, the encapsulation trench will then I material and clean soil. A one call and 48 hour notification to OCD will be interested and clean soil. A one call and 48 hour notification to OCD will be been been will be constructed or closed according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title i Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Approval.  Getty Guyo	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk coment or CKD. The pit material in coment and pit contents have ad to grade using a minimum of 3° of like  the above described pit or below-grade tank tative OCD-approved plan .  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation set in place for a minimum of 24 hours, the encapsulation trench will then it material and clean soil. A one call and 48 hour notification to OCD will be material and clean soil. A one call and 48 hour notification to OCD will be the been/will be constructed or clusted according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title  Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Approval.  Getty Guye  Compliance Officer	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk cement or CKD. The pit meterial in cement and pit contents have ad to grade using a minimum of 3' of like  the above described pit or below-grade tank tative OCD-approved plan.  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation. The drilling pit contents will be excavated and emplaced into the encapsulation trends of pit material and cement will be mixed using a tracking and was set in place for a minimum of 24 hours, the encapsulation trench will then it material and clean soil. A one call and 48 hour notification to OCD will be interested to the best of the been/will be constructed or clusted according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Approval.  Getty Guye  Compliance Officer	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk coment or CKD. The pit moterial in coment and pit contents have ad to grade using a minimum of 3' of like  the above described pit or below-grade tank tative OCD-approved plan.  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
Additional Comments: Cleasure work plan for drilling pit. An encapsulation The drilling pit contests will be escavated and emplaced into the encapsulation. The drilling pit contests will be escavated and emplaced into the encapsulation trends of pit material and cement will be mixed using a trackhoe and was set in place for a minimum of 24 hours, the encapsulation trench will then the material and clean soil. A one call and 48 hour notification to OCD will be as been/will be constructed or clusted according to NMOCD guidelines.  I hereby certify that the information above is true and complete to the best of has been/will be constructed or clusted according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Getty Guye  Frinted Name/Title Getty Guye  Frinted Name/Title Compliance Officer	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk coment or CKD. The pit moterial in coment and pit contents have ad to grade using a minimum of 3' of like  the above described pit or below-grade tank tative OCD-approved plan.  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
Additional Comments: Closure work plan for drilling pit. An encapsulation The drilling pit contents will be excavated and emplaced into the encapsulation the drilling pit contents will be excavated and emplaced into the encapsulation set in place for a minimum of 24 hours, the encapsulation trench will then it material and clean soil. A one call and 48 hour notification to OCD will be material and clean soil. A one call and 48 hour notification to OCD will be the been/will be constructed or clusted according to NMOCD guidelines.  Date: 10/10/07  Printed Name/Title  Dan Dolan/Agent  Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.  Approval.  Getty Guye  Compliance Officer	ions.  In trench will be constructed and lined with a 12 mile tion trench using a mixture of three to one pit material ter added if needed. After completion of solidifying the capped using a 20 mile synthetic liner and backfills anade before action begins.  If my knowledge and belief. I further cartify that is the contents of my knowledge and belief. I further cartify that is the contents of the	pynthetic liner next to existing drilling pit.  al and Class H bulk coment or CKD. The pit material in coment and pit contents have ad to grade using a minimum of 3° of like  the above described pit or below-grade tank tative OCD-approved plan .  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or



## ALLSTATE ENVIRONMENTAL SERVICES, LLC



P.O BOX 11322 MIDLAND, TEXAS 79702 OFFICE: (432) 682-3547 FAX: (432) 682-4182 Contractors License #94195

DEC 5 2007 OCD-ARTESIA

December 4, 2007

New Mexico Oil Conservation Division District 2 1301 Grand Avenue Artesia, New Mexico 88210

Dear Sir/Ma'am

Included in this mailing is the closure report for OGX Resources, New Man Fed #1 in Eddy County, New Mexico. As indicated in the summary the pit closure work began October 19, 2007 and was completed on November 14, 2007.

Any concern or questions regarding this site may be addressed to Paula Guell, Office Supervisor, Allstate Environmental Services, at 432-682-3547, or e-mail <a href="mailto:paula@basinbroadband.com">paula@basinbroadband.com</a> or the company e-mail address at allstate@basinbroadband.com

Sincerely,

Paula Guell Office Supervisor Allstate Environmental Services, LLC

Cc: OGX Resources, T.X.
Allstate Environmental Services - file

## Stipulations for closing Of Pit

Samples are to be obtained from pit area and analysis submitted to NMOCD prior to back filling. Notify NMOCD 24 hours prior to obtaining samples.

**DATA INDICATES THIS AREA TO BE WATER SENSITIVE.** As a condition of approval, if during pit construction, water is encountered or if water seeps into pits after construction the **OCD MUST BE CONTACTED IMMEDIATELY** 

If pit is situated in an agricultural area pit contents must be hauled to an NMOCD approved disposal area.

Pits must be closed within 6 months of the date production casing is set.

OGX Resources New Man Fed #1 Eddy County, New Mexico Begin Date 10/19/2007 End 11/14/2007





