

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised June 10, 2003

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-015-00300

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Atoka San Andres Unit

8. Well Number

101

DEC 4 2007

9. OGRID Number

6137

OCD-ARTESIA

10. Pool name or Wildcat

Atoka San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other—Water Injection Well

2. Name of Operator

Devon Energy Production Company, LP

3. Address of Operator

20 North Broadway, Suite 1500, Oklahoma City, Oklahoma 73102

4. Well Location

Unit Letter C : 990' feet from the North line and 2310' feet from the West line

Section 11

Township 18S Range 26E

Eddy

County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3311' GL; 3321' KB

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MIRU. Release packer @ 1630'. TOH w/2-3/8" Fiberglass tubing and packer.
2. Circulate wellbore with 10 ppg salt gelled mud.
3. Set CIBP at 1,670'. Dump 35' cement on top. (Open San Andres perms @ 1696'-1706')
4. Spot 25 Sx cement @ 1,282'. WOC & Tag. Calc. PBD @ 1,042'. (7-5/8" casing shoe @ 1,232')
5. Perf sqz holes at 100' through 5-1/2" casing and 7-5/8" casing. Pump 35 Sx cement, circulating cement to surf on 5-1/2" annulus and 7-5/8" annulus, leaving 100' plug in 5-1/2 casing to surface.
6. Cut wellhead off 3' below ground level. Set P&A marker.
7. Clean & restore location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie Slack

TITLE: Engineering Technician

DATE 11/29/07

Type or print name Ronnie Slack

E-mail address: Ronnie.Slack@dvni.com

Telephone No. 405-552-4615

(This space for State use)

APPROVED BY PhD Hanken

TITLE Comptroller

DATE 12/10/07

Conditions of approval, if any:

Notify OCD 24 hrs. prior
To any work done.

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: ASAU #101		Field: ATOKA SAN ANDRES	
Location: 990' FNL & 2310' FWL; SEC 11-T18S-R26E		County: EDDY	State: NM
Elevation: 3311' GL; 3321' KB		Spud Date: 1/21/57	Compl Date: 2/3/57
API#: 30-015-00300	Prepared by: Ronnie Slack	Date: 11/29/07	Rev:

PROPOSED PLUG & ABANDONMENT

Proposed:

1. Perf Sqz holes at 100' in 5-1/2" & 7-5/8" casing.
2. Pump 35 Sx cement to surface on 5-1/2" & 7-5/8" annulus, leaving 100' plug in 5-1/2" casing.
3. Cut wellhead off 3' below ground, set dry hole marker.
4. Clean & restore location.

10 ppg mud

9-7/8" Hole
7-5/8", 24#, J55, @ 1,232'
 Cmt'd w/450 Sx TOC @ 290' (Temp Survey-1/25/57)

Proposed:

1. Spot 25 Sx plug @ 1,282'
2. WOC & Tag. Calc PBD @ 1,042'

10 ppg mud

Proposed:

1. Circulate wellbore w/10# salt gelled mud

SAN ANDRES
1,696' - 1,706'

4/1/67 Converted to water injection

6-3/4" Hole
5-1/2", 14#, J55, @ 1,782'
 Cmt'd w/150 Sx. TOC @ 130' (Temp survey-1/30/57)

Proposed:

1. Set CIBP @ +/- 1,670'.
2. Dump 35' cement on top. Calc PBD @ 1635'

1,776' PBD

1,783' TD

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: ASAU #101		Field: ATOKA SAN ANDRES	
Location: 990' FNL & 2310' FWL; SEC 11-T18S-R26E		County: EDDY	State: NM
Elevation: 3311' GL; 3321' KB		Spud Date: 1/21/57	Compl Date: 2/3/57
API#: 30-015-00300	Prepared by: Ronnie Slack	Date: 11/27/07	Rev:

CURRENT SCHEMATIC

9-7/8" Hole
7-5/8", 24#, J55, @ 1,232'
 Cmt'd w/450 Sx. TOC @ 290' (Temp Survey-1/25/57)

2-3/8", EUE, 8RD, Med. Hvy. Fiber Glass Tubing (3/29/67)

Baker On/Off tool
 Baker Lok Set Packer @ 1,630' (3/25/67)

SAN ANDRES
1,696' - 1,706'

4/1/67 Converted to water injection

6-3/4" Hole
5-1/2", 14#, J55, @ 1,782'
 Cmt'd w/150 Sx. TOC @ 130' (Temp survey-1/30/57)

1,776' PBD

1,783' TD

