

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised June 10, 2003

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

FEB 28 2008

OCD-ARTESIA



WELL API NO.

30-015-00207

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Atoka San Andres Unit

8. Well Number

135

9. OGRID Number

6137

10. Pool name or Wildcat

Atoka San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other—Water Injection Well

2. Name of Operator

Devon Energy Production Company, LP

3. Address of Operator

20 North Broadway, Suite 1500, Oklahoma City, Oklahoma 73102

4. Well Location

Unit Letter F: 1650' feet from the North line and 2980' feet from the East line

Section 14

Township 18S

Range 26E

Eddy

County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3314' GL; 3324' KB

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. 2/13/08--MIRU. Circulated wellbore w/10 ppg mud. Spot 25 sx cement on CIBP @ 1,575'.

2. Spot 25 sx cement at 1,145' in 5-1/2" casing. Tagged TOC at 951'.

3. Circulated 25 Sx cement from 240' to surface.

4. 2/14/08--Wellbore plugged out.

5. 2/25/08--Cut wellhead off 3' below ground level & set dry hole marker. Wellbore plugged & abandoned.

Approved for plugging of well bore only.  
Bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under <http://www.emnrd.state.nm.us/oed>.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie Slack

TITLE: Engineering Technician

DATE 2/25/08

Type or print name Ronnie Slack

E-mail address: Ronnie.Slack@dvn.com

Telephone No. 405-552-4615

(This space for State use)

APPROVED BY Phyllis Hahn

TITLE Comptroller

DATE 2/28/08

Conditions of approval, if any:

**DEVON ENERGY PRODUCTION COMPANY LP**

|   |                           |                         |                     |
|---|---------------------------|-------------------------|---------------------|
| Well Name: ATOKA SAN ANDRES UNIT #135             |                           | Field: ATOKA SAN ANDRES |                     |
| Location: 1650' FNL & 2980' FEL; SEC 14-T18S-R26E |                           | County: EDDY            | State: NM           |
| Elevation: 3324' KB; 3314' GL                     |                           | Spud Date: 9/6/57       | Compl Date: 9/23/57 |
| API#: 30-015-00207                                | Prepared by: Ronnie Slack | Date: 2/25/08           | Rev:                |

**PLUGGED & ABANDONED**  
2/25/08

*Cut wellhead off, set dry holer marker (2/25/08)*  
*Wellbore plugged out. (2/14/08)*  
*Circulated 25 Sx (240') cement surface plug.*

10# Mud

*Tagged TOC at 951'. (2/14/08)*  
*Spot 25 Sx cement at 1,145'. (2/13/08)*

*MIRU for PA. Circulated hole w/10# mud. (2/13/08)*

*Spot 25 Sx (240') cement at 1575'. (2/13/08)*

CIBP @ 1,575' (3/82)

1,708' PBDT

1,743' TD

11" Hole  
8-5/8", 24#, J55, @ 1.095'  
Cmt'd w/450 Sx. Circulated to surface.

SAN ANDRES  
1,652' - 1,660' (4 spf)

7-7/8" Hole  
5-1/2", 14#, J55, @ 1,740'  
Cmt'd w/475 Sx. Circulated to surface.