

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505



FEB 28 2008

OCD-ARTESIA

WELL API NO. <b>30-015-00309</b>
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name <b>ATOKA SAN ANDRES UNIT</b>
8. Well Number <b>119</b>
9. OGRID Number <b>6137</b>
10. Pool name or Wildcat <b>SAN ANDRES</b>

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other INJECTION WELL

2. Name of Operator  
**DEVON ENERGY PRODUCTION COMPANY, LP**

3. Address of Operator  
**20 North Broadway, Ste 1500, Oklahoma City, OK 73102 405-552-4615**

4. Well Location  
Unit Letter P : 330' feet from the SOUTH line and 330' feet from the EAST line  
Section 10 Township 18S Range 26E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
**3337' KB; 3329' GL**

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 2/24/08—MIRU for P&A. Unable to unseat packer @ 1,487'. Release tubing & circulate hole w/10 ppg mud.
- Set CIBP @ 1,470'. Dump 35' cement on top.
- Spot 25 sx cement in 5-1/2" casing @ 1,270'. Tagged TOC @ 1,008'. (8-5/8" casing shoe @ 1,207').
- 2/24/08--Perforated 5-1/2" casing @ 100'. Circulated 30 sx cement to surface.
- 2/25/08--Cut wellhead off. Set dry hole marker. Well plugged & abandoned.

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms, [www.emnrd.state.nm.us/oed](http://www.emnrd.state.nm.us/oed).

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ronnie Slack TITLE Engineering Technician DATE 2/25/08

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dvn.com Telephone No. 405-552-4615  
For State Use Only

APPROVED BY: [Signature] TITLE Comptroller DATE 2/28/08

Conditions of Approval (if any):

**DEVON ENERGY PRODUCTION COMPANY LP**

Well Name: ATOKA SAN ANDRES UNIT #119		Field: ATOKA	
Location: 330' FSL & 330' FEL; SEC 10-T18S-R26E		County: EDDY	State: NM
Elevation: 3337' KB; 3329' GL		Spud Date: 11/22/56	Compl Date: 12/7/56
API#: 30-015-00309	Prepared by: Ronnie Slack	Date: 2/25/08	Rev:

**PLUGGED & ABANDONED**  
2/25/08

1. Perforated 5-1/2" casing @ 100'.
2. Circulated 30 sx cement to surface (2/24/08)
3. Cut wellhead off & set dry hole marker (2/25/08)
4. Plugged & Abandoned

TOC @ 550' (temp survey)

10# Mud

1. Tagged TOC @ 1,008' (2/24/08)

11" Hole  
8-5/8", 24#, @ 1,207'  
Cmt'd w/450 Sx to surface

1. Spot 25 Sx (240') plug @ 1,270'. (2/24/08)

10# Mud

1. Set CIBP @ 1,470' w/35' cement on top. PBD @ 1,435'

**SAN ANDRES**  
1509', 79', 85', 1625', 34', 1636'-1666';  
1679'-1693'

1. MIRU for P&A. (2/24/08)
2. Unable to unseat packer @ 1,487'.
3. Release tubing, circulate hole w/10 ppg mud.

1,754' PBD

7-7/8" Hole  
5-1/2", 14#, @ 1,765'  
Cmt'd w/265 Sx. TOC @ 550' (temp survey)

1,766' TD