D-ARTESIA

Reclamation

Recomplete

__ Temporarily Abandon

Fracture Treat

New Construction

Plug and Abandon

Form 3160-5 (April 2004)

3a Address

Type of Well Oil Well ...

TYPE OF SUBMISSION

Notice of Intent

Subsequent Report

2 Name of Operator COG Operating LLC

550 W. Texas Ave., Suite 1300 Midland, TX 79701

4 Location of Well (Footage, Sec., T., R., M., or Survey Description)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OM B No 1004-0137
Expires March 31, 200

W.S.W.

SUNDRY NOTICES AND REPORTS ON WELLS

Alter Casing

Change Plans

Casing Repair

SUNDRY Do not use th	BUREAU OF LAND MAN NOTICES AND REI his form for proposals to ell. Use Form 3160-3 (5 Lease Serial No 6 If Indian, Allottee or Tribe Name			
		ructions on reverse side. APR - 3 2008	7 If Unit or CA/Agreement, Name and/or No	-	
Oil Well	Gas Well Da Other	OCD-ARTESIA	Polaris B Jedua Polaris B Jedua PAPI Well No	D#,	
s Ave., Suite 1300 i	Midland, TX 79701	3b Phone No. (include area code) 432-685-4332	30 0/5 3 5 3 9 5 10. Field and Pool, or Exploratory Area	-	
Vell (Footage, Sec , T	T., R., M., or Survey Description) T-17S, R-30E		Loco Hills; Glorieta Yeso 96718 11 County or Parish, State EDDY, NM	-	
12. CHECK AP	PROPRIATE BOX(ES) TO	INDICATE NATURE OF NOTICE, I	REPORT, OR OTHER DATA	•	
SUBMISSION		TYPE OF ACTION		•	
	Acidıze	Deepen Production (St	art/Resume) Water Shut-Off		

Well Integrity Other Change APD

Drill Plan

Final Abandonment Notice Convert to Injection Plug Back 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filled once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has

COG respectfully requests a variance for drill plan items #4: casing program, #5: cement program, and #6: minimum specifications for pressure control.

Also attached is well name list that this variance applies to.

determined that the site is ready for final inspection.)

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)						
Phyllis A. Edwards	le Regulatory Analyst					
Signature Anglie a Lawardo Di)e 03/5	APPROVED				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by	Title	DatAPR 1 2003				
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office	WESLEY W. INGRAM				
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any pers. States any false. Fictitious or fraudulent statements or representations as to any matter with	on knowingly and willfully to p	nake to Party department of a geney of the United				

(Instructions on page 2)

Sundry Notes to Change APD's

Loco Hills Area, T17S, R30E

3/26/08

4. Casing Program

Hole Size	Interval	OD Casing	Weight	Grade	Jt., Condition	Jt.	brst/clps/ten
17 1/2"	0-425'	13 3/8"	48#	H-40	ST&C/New	ST&C	9.22/3.943/15.8
11"or12 ¼"	0-1300'	8 5/8"	24or32#	J-55	ST&C/New	ST&C	3.03/2.029/7.82
7 7/8"	0-TD	5 1/2"	15.5or17#	J-55orL80	LT&C/New	LT&C	1.88/1.731/2.42

5. Cement Program

13 3/8" Surface Casing:

Class C, 475 sx, yield 1.32, back to surface

8 5/8" Intermediate Casing:

11" Hole: Class C, 400 sx lead, yield-2.45 + 200 sx

tail, yield-1.32, back to surface.

12-1/4" Hole: Class C, 600 sx lead, yield-2.45 + 200

sx tail, yield-1.32, back to surface.

5 1/2" Production Casing:

Class C, 700 sx Lead, yield-1.97 + 400 sx Tail, yield-1.37, to 200' minimum tie back to intermediate

casing

6. Minimum Specifications for Pressure Control

The blowout preventer equipment (BOP) shown in Exhibit #9 will consist of a double ram-type (2000 psi WP) preventer. This unit will be hydraulically operated and the ram type preventer will be equipped with blind rams on top of 4 1/2" drill pipe rams on the bottom. The BOP will be nippled up on the 13 3/8" surface casing and tested to 1000 psi by rig pump. The BOP will then be nippled up on the 8 5/8" intermediate casing and tested by a third party to 2000 psi and used continuously until total depth is reached. All BOP's and accessory equipment will be tested to 2000 psi before drilling out of the intermediate casing. Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment (Exhibit #10) will include a Kelly cock and floor safety valve, choke lines and a choke manifold (Exhibit #11) will a 2000 psi WP rating.

BLM	Permits	Submitted	
	25 of 2-1	วด_กฎ	1

			Unit	<u>Permit</u>		
Well Name	County	Location	Sec, Township, Range	Submitted	Approved	Area
Caddo Federal #5	Eddy	990 FNL, 330 FEL	Sec 17, T17S, R30E, Unit	09/25/07	12/07/07	LOCO HILLS
Electra Federal #13	Eddy	1741 FNL, 1060 FWL	Sec 10, T17S, R30E, Unit E	12/22/06	03/07/07	LOCO HILLS
Electra Federal #14	Eddy	1750 FNL, 2310 FWL	Sec 10, T17S, R30E, Unit F	12/26/06	02/09/07	LOCO HILLS
Electra Federal #18	Eddy	2310 FNL, 330 FWL	Sec 15, T17S, R30E, Unit E	07/18/07	09/05/07	LOCO HILLS
Electra Federal #20	Eddy	1650 FSL, 330 FWL	Sec 10, T17S, R30E, Unit L	09/14/07	10/27/07	LOCO HILLS
Electra Federal #21	Eddy	1650 FSL, 1650 FWL	Sec 10, T17S, R30E, Unit K	09/14/07	10/27/07	LOCO HILLS
Electra Federal #22	Eddy	2310 FNL, 1650 FWL	Sec 10, T17S, R30E, Unit F	09/20/07		LOCO HILLS
Electra Federal #23	Eddy	2510 FNL, 250 FWL	Sec 10, T17S, R30E, Unit E	08/19/07	12/07/07	LOCO HILLS
Harvard Federal #10	Eddy	1690 FNL, 1055 FWL	Sec 12, T17S, R30E, Unit E	10/05/07	11/01/07	LOCO HILLS
Harvard Federal #11	Eddy	330 FNL, 990 FWL	Sec 12, T17S, R30E, Unit D	10/05/07	12/05/07	LOCO HILLS
Harvard Federal #12	Eddy	700 FNL, 700 FEL	Sec 11, T17S, R30E, Unit A	10/08/07	12/05/07	LOCO HILLS
Holder CB Federal #13	Eddy	330 FSL, 380 FWL	Sec 9, T17S, R30E, Unit M	09/27/07	12/05/07	LOCO HILLS
Holder CB Federal #14	Eddy	1650 FSL, 330 FWL	Sec 9, T17S, R30E, Unit L	09/25/07	12/05/07	LOCO HILLS
Holder CB Federal #15	Eddy	2160 FSL, 890 FWL	Sec 9, T17S, R30E, Unit L	09/25/07	12/05/07	LOCO HILLS
Polaris B Federal #10	Eddy	2310 FSL, 330 FEL	Sec 9, T17S, R30E, Unit I	12/14/06	01/22/07	LOCO HILLS
Polaris B Federal #18	Eddy	330 FNL, 2310 FWL	Sec 17, T17S, R30E, Unit C	09/26/07	11/15/07	LOCO HILLS
Polaris B Federal #19	Eddy	1800 FNL, 2310 FWL	Sec 17, T17S, R30E, Unit F	09/27/07	12/05/07	LOCO HILLS
Polaris B Federal #20	Eddy	2310 FNL, 1650 FWL	Sec 17, T17S, R30E, Unit F	09/27/07	12/05/07	LOCO HILLS
Wooley-Federal #11	Eddy	990 FSL, 1650 FWL	Sec 21, T17S, R30E, Unit N	_01/0 8/07 _	03/06/07	LOCO HILLS

Woolley

not explied - Of