OCD-ARTESIA

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
OM B No 1004-0137
Expires March 31, 200

OM B No 1004-0137 Expires March 31, 2007	4
No	

	BUREAU OF LAND MANAGEMENT						
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					nal No		
SUBMIT IN TR	RIPLICATE- Other insti	ructions on rev	erse side.	7 If Unit	or CA/Agreement, Name and/or No		
1 Type of Well Oil Well 7 [Gas Well 🗁 🔲 Other	APR -	- 3 2008	8 Well N	ame and No. a . l		
2. Name of Operator COG Opera	iting LLC	OGU-/	KIESIA	S APIW	eris B Jederal		
3a Address 550 W. Texas Ave., Suite 1300) Midland, TX 79701	3b Phone No. (incli	ıde area code)	1300	9/S 3596 7 nd Pool, or Exploratory Area		
4 Location of Well (Footage, Sec.,	T, R, M., or Survey Description)	t — — — — — — — — — — — — — — — — — — —			lills; Glorieta Yeso 96718		
	T-17S, R-30E			11. County	11. County or Parish, State		
					EDDY, NM		
12. CHECK A	PPROPRIATE BOX(ES) TO	INDICATE NATU	TRE OF NOTICE, I	REPORT, O	ROTHER DATA		
TYPE OF SUBMISSION		T	YPE OF ACTION				
✓ Notice of Intent	Acidize ☐ Deepen ☐ Production (Start/Res						
Subsequent Report	Casing Repair	New Construction			Other Change APD		
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	Temporarily Al Water Disposal	oandon	Drill Plan		
#6: minimum specification	a variance for drill plan items		#5: cement program,	and			
14. I hereby certify that the foregon Name (Printed/Typed)	oing is true and correct	1					
Phyllis A. Edward	S	Title R	egulatory Analyst				
Signature Thy 11	is a Edwa	Dale	03/	^{26/2008} A	PPROVED		
0	THIS SPACE FOR FE	DERAL OR ST	TATE OFFICE U	SE			
Approved by Conditions of approval, if any, are attained that the applicant holds legal of			ile	Dar	APR 1 2008		
which would entitle the applicant to could be 18 U.S.C. Section 1001 and Title 4	onduct operations thereon,	- 01		Wi make to Passy d	SLEY W. INGRAM		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

Sundry Notes to Change APD's

Loco Hills Area, T17S, R30E

3/26/08

4. Casing Program

Hole Size	Interval	OD Casing	Weight	Grade	Jt., Condition	Jt.	brst/clps/ten
17 ½"	0-425'	13 3/8"	48#	H-40	ST&C/New	ST&C	9.22/3.943/15.8
11"or12 1/4"	0-1300'	8 5/8"	24or32#	J-55	ST&C/New	ST&C	3.03/2.029/7.82
7 7/8"	0-TD	5 1/2"	15.5or17#	J-55orL80	LT&C/New	LT&C	1.88/1.731/2.42

5. Cement Program

13 3/8" Surface Casing:

Class C, 475 sx, yield 1.32, back to surface

8 5/8" Intermediate Casing:

11" Hole: Class C, 400 sx lead, yield-2.45 + 200 sx

tail, yield-1.32, back to surface.

12-1/4" Hole: Class C, 600 sx lead, yield-2.45 + 200

sx tail, yield-1.32, back to surface.

5 1/2" Production Casing:

Class C, 700 sx Lead, yield-1.97 + 400 sx Tail, yield-1.37, to 200' minimum tie back to intermediate

casing

6. Minimum Specifications for Pressure Control

The blowout preventer equipment (BOP) shown in Exhibit #9 will consist of a double ram-type (2000 psi WP) preventer. This unit will be hydraulically operated and the ram type preventer will be equipped with blind rams on top of 4 1/2" drill pipe rams on the bottom. The BOP will be nippled up on the 13 3/8" surface casing and tested to 1000 psi by rig pump. The BOP will then be nippled up on the 8 5/8" intermediate casing and tested by a third party to 2000 psi and used continuously until total depth is reached. All BOP's and accessory equipment will be tested to 2000 psi before drilling out of the intermediate casing. Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment (Exhibit #10) will include a Kelly cock and floor safety valve, choke lines and a choke manifold (Exhibit #11) will a 2000 psi WP rating.

ELM	Permits	Submitted
	25 of 3-	26-08

]		Unit	<u>Permit</u>		
Well Name	County	Location	Sec, Township, Range	Submitted	Approved	Area
Caddo Federal #5	Eddy	990 FNL, 330 FEL	Sec 17, T17S, R30E, Unit	09/25/07	12/07/07	LOCO HILLS
Electra Federal #13	Eddy	1741 FNL, 1060 FWL	Sec 10, T17S, R30E, Unit E	12/22/06	03/07/07	LOCO HILLS
Electra Federal #14	Eddy	1750 FNL, 2310 FWL	Sec 10, T17S, R30E, Unit F	12/26/06	02/09/07	LOCO HILLS
Electra Federal #18	Eddy	2310 FNL, 330 FWL	Sec 15, T17S, R30E, Unit E	07/18/07	09/05/07	LOCO HILLS
Electra Federal #20	Eddy	1650 FSL, 330 FWL	Sec 10, T17S, R30E, Unit L	09/14/07	10/27/07	LOCO HILLS
Electra Federal #21	Eddy	1650 FSL, 1650 FWL	Sec 10, T17S, R30E, Unit K	09/14/07	10/27/07	LOCO HILLS
Electra Federal #22	Eddy	2310 FNL, 1650 FWL	:Sec 10, T17S, R30E, Unit F	09/20/07		LOCO HILLS
Electra Federal #23	Eddy	2510 FNL, 250 FWL	Sec 10, T17S, R30E, Unit E	08/19/07	12/07/07	LOCO HILLS
Harvard Federal #10	Eddy	1690 FNL, 1055 FWL	Sec 12, T17S, R30E, Unit E	10/05/07	11/01/07	LOCO HILLS
Harvard Federal #11	Eddy	330 FNL, 990 FWL	Sec 12, T17S, R30E, Unit D	10/05/07	12/05/07	LOCO HILLS
Harvard Federal #12	Eddy	700 FNL, 700 FEL	Sec 11, T17S, R30E, Unit A	10/08/07	12/05/07	LOCO HILLS
Holder CB Federal #13	Eddy	330 FSL, 380 FWL	Sec 9, T17S, R30E, Unit M	09/27/07	12/05/07	LOCO HILLS
Holder CB Federal #14	Eddy	1650 FSL, 330 FWL	Sec 9, T17S, R30E, Unit L	09/25/07	12/05/07	LOCO HILLS
Holder CB Federal #15	Eddy	2160 FSL, 890 FWL	Sec 9, T17S, R30E, Unit L	09/25/07	12/05/07	LOCO HILLS
Polaris B Federal #10	Eddy	2310 FSL, 330 FEL	Sec 9, T17S, R30E, Unit I	12/14/06	01/22/07	LOCO HILLS
Polaris B Federal #18	Eddy	330 FNL, 2310 FWL	Sec 17, T17S, R30E, Unit C	09/26/07	11/15/07	LOCO HILLS
Polaris B Federal #19	Eddy	1800 FNL, 2310 FWL	Sec 17, T17S, R30E, Unit F	09/27/07	12/05/07	LOCO HILLS
Polaris B Federal #20	Eddy	2310 FNL, 1650 FWL	Sec 17, T17S, R30E, Unit F	09/27/07	12/05/07	LOCO HILLS
Wooley Federal #11	Eddy	990 FSL, 1650 FWL	Sec 21, T17S, R30E, Unit N	_01/ 08/07	03/06/07	LOGO HILLS

Wolley

1901 6xp/121 - 04