Submit 3 Copies To Appropriate District Office	State of New Me	xico	Form C-103
<u>District I</u> E	nergy, Minerals and Natur	ral Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II		1	API NO. 30-015-10199
1301 W Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION		5. Indic	cate Type of Lease
District III 1000 Rio Brazos Rd, Aztec, NM 87410 APR 2 4 2008 Santa Fe, NM 87505		icis Dr.	STATE S FEE
District IV Santa Fe, NM 87505		505 6. State	Oil & Gas Lease No.
1220 S St. Francis Dr., Santa Fe, NMOCD-ARTESIA			
SUNDRY NOTICES AND REPORTS ON WELLS			e Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			A SAN ANDRES UNIT
PROPOSALS.)		9 1/01	Number
1. Type of Well: Oil Well Gas Well Other INJECTION WELL		N WELL	118
2. Name of Operator			AID Number
DEVON ENERGY PRODUCTION COMPANY, LP			ol name or Wildcat
3. Address of Operator 20 North Broadway, Ste 1500, Oklahoma City, OK 73102 405-552-4615			SAN ANDRES
4. Well Location		100 002 1010	SHITTA
Unit Letter K : 1650' feet from the SOUTH line and 2310' feet from the WEST line			
Section 10 Township 18S Range 26E NMPM County EDDY			
11. Elevation (Show whether DR, RKB, RT, GR, etc.)			
3349' KB; 3338' GL			
Pit or Below-grade Tank Application or Closure			
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water			
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING			
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLI			
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB			
07:170		L OZUED	
OTHER:	erations (Clearly state all n	OTHER:	tinent dates, including estimated date
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion			
or recompletion.			
1 4/11/09 MIDLL DOOL w/ 2 2/9" tubing 9 pooker from 1 459'			
 4/11/08MIRU. POOH w/ 2-3/8" tubing & packer from 1,458'. TIH w/CIBP & set @ 1,470'. Dump 35' cement on top. (San Andres perfs from 1,513' to 1,748') 			
3. Spot 80 Sx plug in 4-1/2" production casing from 1,180' to surface. (7" casing shoe @ 1,114').			
4. Cut wellhead off, set dry hole marker, cleaned location.			
5. 4/18/08Wellbore plugged & abandoned.			CEPTED FOR RECORD
Approve	d for plugging or well nore only.		
Liability	under bond is retained pending rec	reipt	APR 2 5 2008
of C-103	(Subsequent Report of Well Pluggi ay be found at OCD Web Page under	·)	p. 0 p. 7 2
Forms, w	ww.cmnrd.state.pm us/ocd.	derry	Guye, Deputy Field Inspector
	Se to see	NMO	CD-District II ARTESIA
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-			
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan .			
SIGNATURE Ronnie Slack	TITLE	Engineering Technician	DATE 4/22/08
SIGNATURE - WILLIAM	IIILE	_nagmeeting rechitician_	DATE 4/22/00
Type or print name Ronnie Slack	E-mail address: Ro	onnie.Slack@dvn.com	Telephone No. 405-552-4615
For State Use Only			
APPROVED BY:	TITLE		DATE
Conditions of Approval (if any):			

DEVON ENERGY PRODUCTION COMPANY LP Well Name: ATOKA SAN ANDRES UNIT #118 Field: ATOKA Location: 1650' FSL & 2310' FWL; SEC 10-185-26E County: EDDY State: NM Compl Date: 3/1/64 Elevation: 3349' KB; 3338' GL Spud Date: 12/26/63 API#: 30-015-10199 Date: 4/22/08 Prepared by: Ronnie Slack Rev: Cut wellhead off, set dry hole marker, cleaned location **PLUGGED & ABANDONED** 4/18/08 Spot 80 Sx cement from 1,180' to surface 9-5/8" Hole 7", 20#, J55, STC, @ 1,114' Cmt'd w/1000 Sx to surface 10 ppg mud Circulated wellbore w/10 ppg mud Set CIBP @ 1,470' w/35' cement on top. PBD @ 1,435' **SAN ANDRES** 1,513' - 1,748' 1,804' PBTD 6-1/4" Hole 4-1/2", 9.5#, J55, STC, @ 1,844' 1,850' TD Cmt'd w/300 Sx to surface