

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED
OMB No 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5 Lease Serial No
See attached
6 If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1 Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

JUN 24 2008

2 Name of Operator
Marbob Energy Corporation

OCD-ARTESIA

7 If Unit of CA/Agreement, Name and/or No
8 Well Name and No
See attached

9 API Well No.
See attached 30 015 36280

3a Address

P O Box 227, Artesia, NM 88211-0227

3b Phone No. (include area code)

575-748-3303

10 Field and Pool or Exploratory Area
See attached

4 Location of Well (Footage, Sec., T., R., M., or Survey Description)

See attached

11 Country or Parish, State
See attached

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Replacement Page
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13 Describe Proposed or Completed Operation. Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Marbob Energy respectfully requests approval for the following statement to be added to the cement program on the attached referenced approved APD's:

If cement does not circulate on surface casing and TOC is less than 100' then ready mix will be used to bring cement to surface. If cement top is more than 100' from surface 1" pipe will be run to TOC and cement pumped to surface. No temperature survey or bond log will be required.

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)

Nancy T. Agnew

Title Land Department

Signature

Nancy T. Agnew

Date 06/16/2008

APPROVED

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Office

Date

WESLEY W. INGRAM
PETROLEUM ENGINEER

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

Accepted for record - NMOCD

Attachment for Marbob Sundry dated 6/16/08

Well Name and #	API #	Lease #	Location	Field and Pool
Loco Federal #6	30-015-36164	NMNM 106231	1800' FNL & 2310' FEL, Sec 21, T17S - R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Birdie Federal #10	30-015-36371	NMNM 074936	1650' FNL & 530' FEL, Section 17, T17S - R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Thunder Road Federal #8	30-015-36280	NMLC0029342E	1675' FNL & 2310' FEL, Sec 20, T17S - R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Randy Federal #6	30-015-36361	NMLC 29020E	1750' FNL & 2310' FEL, Sec 22, T17S -R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Randy Federal #7	30-015-36264	NMLC 29020E	1800' FNL & 990' FEL, Sec 22, T17S - R30, Eddy County, NM	Loco Hills; Glorieta-Yeso

**Thunder Road Federal #8
API 30-015-36280
June 21, 2008
Conditions of Approval**

For the surface casing: If cement does not circulate to the surface, the appropriate BLM office shall be notified and a tag with 1" will be performed at four positions 90 degrees apart to verify cement depth. BLM Petroleum Engineer Technician to witness tags. If depth is greater than 100' or water is standing in the annulus, remedial cementing will be done. If no water and TOC tag is less than 100', when 100% excess cement of the annulus volume was run on the primary job, ready-mix can be used to bring cement to surface.

WWI 062108